

DIALOG(R)File 351:Derwent WPI
(c) 2004 Thomson Derwent. All rts. reserv.

013013309 **Image available**

WPI Acc No: 2000-185160/200017

XRPX Acc No: N00-136782

**Composite graphical objects creating according to compositing expression
by modifying the latter on basis of contribution of each of objects
within region to form optimized compositing expression for each the
region**

Patent Assignee: CANON KK (CANO); LONG T M (LONG-I); TLASKAL M P (TLAS-I)

Inventor: LONG T M; TLASKAL M P; LONG A M

Number of Countries: 028 Number of Patents: 005

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
EP 984396	A2	20000308	EP 99306891	A	19990831	200017 B
AU 9947329	A	20000316	AU 9947329	A	19990902	200024
JP 2000101829	A	20000407	JP 99250595	A	19990903	200028
AU 736530	B	20010802	AU 9947329	A	19990902	200152
US 20030118250	A1	20030626	US 99387564	A	19990901	200343
			US 2002234244	A	20020905	

Priority Applications (No Type Date): AU 985688 A 19980903; AU 985687 A
19980903

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
EP 984396	A2	E 137	G06T-011/60	
Designated States (Regional): AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT RO SE SI				
AU 9947329	A		G06T-011/00	
JP 2000101829	A	49	H04N-001/387	
AU 736530	B		G06T-011/00	Previous Publ. patent AU 9947329
US 20030118250	A1		G06F-017/00	Div ex application US 99387564

Abstract (Basic): EP 984396 A2

NOVELTY - Each of the regions (1-10) is defined by a region outline following at least one of the set outlines or their parts. Each region is examined to determine those the objects which contribute to the region. The compositing expression is modified on the basis of the contribution of each of the objects within the region to form an optimized compositing expression for each the region. The image is composited using each of the optimized compositing expressions.

USE - For creation of computer-generated images both in the form of still pictures and video imagery made up by compositing multiple components.

ADVANTAGE - Improved efficiency, reduced cost while excluding problems related to overlapping transparent and semi-transparent areas by handling a full range of compositing operations.

DESCRIPTION OF DRAWING(S) - The drawing illustrates the compositing operations after being optimized according to one example of the preferred embodiment.

Best Available Copy

This Page Blank (uspto)

(12) PATENT APPLICATION
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 199947329 A1

(54) Title
Optimizing image compositing

(51)⁶ International Patent Classification(s)
G06T 011/00 G06T 015/00

(21) Application No: 199947329

(22) Application Date: 1999.09.02

(30) Priority Data

(31) Number	(32) Date	(33) Country
PP5687	1998.09.03	AU
PP5688	1998.09.03	AU

(43) Publication Date : 2000.03.16

(43) Publication Journal Date : 2000.03.16

(71) Applicant(s)
Canon Kabushiki Kaisha

(72) Inventor(s)
Martin Paul Tlaskal; Timothy Merrick Long

(74) Agent/Attorney
SPRUSON and FERGUSON,GPO Box 3898,SYDNEY NSW 2001

Optimising Image Compositing

ABSTRACT

A method and apparatus for creating an image is disclosed. The image is formed
5 by rendering at least a plurality of graphical objects to be composited according to a
compositing expression. Each object has a predetermined outline. The method
comprises the following steps. Firstly, dividing a space in which the outlines are defined
into a plurality of mutually exclusive regions wherein each of the regions is defined by a
region outline substantially following at least one of the predetermined outlines or parts
10 thereof. Secondly, examining each of the regions to determine those objects which
contribute to the regions. Thirdly, modifying the compositing expression on the basis of
the contribution of each of the objects within the region to form an optimised compositing
expression for each region. Fourthly, compositing the image using each of the optimised
compositing expressions.




Fig. 23

AUSTRALIA

PATENTS ACT 1990

COMPLETE SPECIFICATION

FOR A STANDARD PATENT

ORIGINAL

Name and Address
of Applicant:

Canon Kabushiki Kaisha
30-2, Shimomaruko 3-chome
Ohta-ku
Tokyo 146
JAPAN

Actual Inventor(s): Martin Paul Tlaskal, Timothy Merrick Long

Address for Service: Spruson & Ferguson, Patent Attorneys
Level 33 St Martins Tower, 31 Market Street
Sydney, New South Wales, 2000, Australia

Invention Title: Optimizing Image Compositing

ASSOCIATED PROVISIONAL APPLICATION DETAILS

[31] Application No(s)
PP5688
PP5687

[33] Country
AU
AU

[32] Application Date
3 September 1998
3 September 1998

The following statement is a full description of this invention,
including the best method of performing it known to me/us:-

OPTIMISING IMAGE COMPOSITING

Field of the Invention

The present invention relates to the creation of computer-generated images both in the form of still pictures and video imagery, and, in particular, relates to efficient process, apparatus, and system for creating an image made up by compositing multiple components.

Background

Computer generated images are typically made up of many differing components or graphical elements which are rendered and composited together to create a final image. In recent times, an "opacity channel" (also known as a "matte", an "alpha channel", or simply "opacity") has been commonly used. The opacity channel contains information regarding the transparent nature of each element. The opacity channel is stored alongside each instance of a colour, so that, for example, a pixel-based image with opacity stores an opacity value as part of the representation of each pixel. An element without explicit opacity channel information is typically understood to be fully opaque within some defined bounds of the element, and assumed to be completely transparent outside those bounds.

An expression tree offers a systematic means for representating an image in terms of its constituent elements and which facilitates later rendering. Expression trees typically comprise a plurality of nodes including leaf nodes, unary nodes and binary nodes. Nodes of higher degree, or of alternative definition may also be used. A leaf node, being the outer most node of an expression tree, has no descendent nodes and represents a primitive constituent of an image. Unary nodes represent an operation which modifies the pixel data coming out of the part of the tree below the unary operator. Unary nodes include such operations as colour conversions, convolutions (blurring etc) and operations such as red-eye removal. A binary node typically branches to left and right subtrees, wherein each subtree is itself an expression tree comprising at least one leaf node. Binary nodes represent an operation which combines the pixel data of its two children to form a single result. For example, a binary node may be one of the standard "compositing operators" such as OVER, IN, OUT, ATOP and alpha-XOR, examples of which and other are seen in Fig. 20.

Several of the above types of nodes may be combined to form a compositing tree. An example of this is shown in Fig. 1. The result of the left-hand side of the compositing tree may be interpreted as a colour converted image being clipped to spline boundaries.

This construct is composited with a second image.

Although the non-transparent area of a graphical element may of itself be of a certain size, it need not be entirely visible in a final image, or only a portion of the element may have an effect on the final image. For example, assume an image of a certain size is to be displayed on a display. If the image is positioned so that only the top left corner of the image is displayed by the display device, the remainder of the image is not displayed. The final image as displayed on the display device thus comprises the visible portion of the image, and the invisible portion in such a case need not be rendered.

Another way in which only a portion of an element may have an effect is when the portion is obscured by another element. For example, a final image to be displayed (or rendered) may comprise one or more opaque graphical elements, some of which obscure other graphical elements. Hence, the obscured elements have no effect on the final image.

A conventional compositing model considers each node to be conceptually infinite in extent. Therefore, to construct the final image, a conventional system would apply a compositing equation at every pixel of the output image. Interactive frame rates of the order greater than 15 frames per second can be achieved by relatively brute-force approaches in most current systems, because the actual pixel operations are quite simple and can be highly optimised. This highly optimised code is fast enough to produce acceptable frame rates without requiring complex code. However, this is certainly not true in a compositing environment.

The per-pixel cost of compositing is quite high. This is because typically an image is rendered in 24-bit colour in addition to an 8-bit alpha channel, thus giving 32 bits per pixel. Each compositing operator has to deal with each of the four channels. Therefore, the approach of completely generating every pixel of every required frame when needed is inefficient, because the per-pixel cost is too high.

Problems arise with prior art methods when rendering graphical objects which include transparent and partially-transparent areas. Further, such methods typically do not handle the full range of compositing operators.

Summary of the Invention

It is an object of the present invention to substantially overcome, or ameliorate, one or more of the deficiencies of the above mentioned methods by the provision of a method for creating an image made up by compositing multiple components.

According to one aspect of the present invention there is provided a method of creating an image, said image being formed by rendering at least a plurality of graphical

objects to be composited according to a compositing expression, each said object having a predetermined outline, said method comprising the steps of:

- dividing a space in which said outlines are defined into a plurality of mutually exclusive regions wherein each of said regions is defined by a region outline substantially following at least one of said predetermined outlines or parts thereof;
- 5 examining each said region to determine those said objects which contribute to said region;
- modifying said compositing expression on the basis of the contribution of each of said objects within said region to form an optimized compositing expression for each said
- 10 region; and
- compositing said image using each of said optimized compositing expressions.

According to another aspect of the present invention there is provided a method of creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said method comprising the steps of:

15

dividing a space in which said outlines are defined into a plurality of mutually exclusive regions;

examining each said region to determine those said objects which contribute to said region;

20 modifying said compositing expression on the basis of the contribution of each of said objects within said region; and

compositing said image using said modified compositing expression.

According to still another aspect of the present invention there is provided a method of creating an image, said image comprising a plurality of graphical objects to be composited according to a compositing expression, said method comprising the steps of:

25

dividing a space in which said graphical objects are defined into a plurality of regions;

examining each said region to determine those said objects which contribute to said region;

30 modifying said compositing expression on the basis of said examination; and

compositing said image using said modified compositing expression.

According to still another aspect of the present invention there is provided an apparatus for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said apparatus comprising:

35

dividing means for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions wherein each of said regions is defined by a region outline substantially following at least one of said predetermined outlines or parts thereof;

5 examining means for examining each said region to determine those said objects which contribute to said region;

 modifying means for modifying said compositing expression on the basis of the contribution of each of said objects within said region to form an optimized compositing expression for each said region; and

10 compositing means for compositing said image using each of said optimized compositing expressions.

 According to still another aspect of the present invention there is provided an apparatus for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said
15 object having a predetermined outline, said apparatus comprising:

 dividing means for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions;

 examining means for examining each said region to determine those said objects which contribute to said region;

20 modifying means for modifying said compositing expression on the basis of the contribution of each of said objects within said region; and

 compositing means for compositing said image using said modified compositing expression.

 According to still another aspect of the present invention there is provided an
25 apparatus for creating an image, said image comprising a plurality of graphical objects to be composited according to a compositing expression, said apparatus comprising:

 dividing means for dividing a space in which said graphical objects are defined into a plurality of regions;

30 examining means for examining each said region to determine those said objects which contribute to said region;

 modifying means for modifying said compositing expression on the basis of said examination; and

 compositing means for compositing said image using said modified compositing expression.

35 According to still another aspect of the present invention there is provided a method

of creating a series of images, each member of said series being related to a preceding member, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure representing a compositing expression, said hierarchical structure including a plurality of nodes each representing a component
5 of at least one of said images, each of said objects having a predetermined outline, said method comprising the steps of:

- (a) for each said node:
 - (i) dividing a component image space in which said outlines are defined into at least one mutually exclusive region, each said region being related to at least one
10 graphical object;
 - (ii) examining each said region to determine those objects that contribute to the region;
- (b) creating internodal dependency information identifying those said regions that will be affected by a change in any one of said regions;
- 15 (c) rendering a first image of said series by compositing all regions substantially according to said hierarchical structure;
- (d) in response to at least one change to at least one of said nodes;
 - (i) examining said internodal dependency information to identify those of said regions affected by said at least one change;
 - 20 (ii) for each node with affected regions, updating the corresponding identified regions and incorporating into said node those (any) new regions arising from the change and/or removing any of said regions that are no longer relevant;
 - (iii) updating said internodal dependency information to reflect changes to said hierarchical structure;
 - 25 (iv) rendering a further image of said series by compositing (only) those regions affected by said at least one change; and
- (e) repeating step (d) for further changes to at least one of said nodes.

According to still another aspect of the present invention there is provided a method of creating a series of images, said images being formed by rendering a plurality of
30 graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a predetermined outline, said method comprising the steps of:

- (a) for each said node:
 - (iii) dividing a space in which said outlines are defined into at least one
35

mutually exclusive region;

(iv) examining each said region to determine those objects that contribute to the region;

- (b) creating internodal dependency information based on said examination;
- 5 (c) rendering a first image of said series utilising said hierarchical structure; and then, in response to at least one change to at least one of said nodes;
- (d) examining said internodal dependency information;
 - (i) for a node with affected regions, updating the corresponding regions;
 - (ii) updating said internodal dependency information;
 - 10 (iii) rendering a further image of said series by compositing those regions affected by said at least one change; and
- (e) repeating step (d) for further changes to at least one of said nodes.

According to still another aspect of the present invention there is provided a method of creating a series of images, said images being formed by rendering at least a plurality
15 of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, said method comprising the steps of:

- (a) for each said node:
 - (i) dividing a component image space in which said graphical objects are
20 defined into at least one region;
 - (ii) examining each said region;
- (b) creating internodal dependency information for each of said regions;
- (c) rendering a first image of said series utilising said hierarchical structure; and then, in response to at least one change to at least one of said nodes;
- 25 (d) examining said internodal dependency information;
 - (i) for a node with affected regions, updating the corresponding information;
 - (ii) updating said internodal dependency record;
 - (iii) rendering a further image of said series; and
- 30 (e) repeating step (d) for further changes to at least one of said nodes.

According to still another aspect of the present invention there is provided an apparatus for creating a series of images, each member of said series being related to a preceding member, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure representing a compositing
35 expression, said hierarchical structure including a plurality of nodes each representing a

component of at least of one of said images, each of said objects having a predetermined outline, said apparatus comprising:

dividing means for dividing a component image space in which said outlines are defined , for each said node, into at least one mutually exclusive region, each said region
5 being related to at least one graphical object ;

first examining means for examining each said region, for each said node, to determine those objects that contribute to the region;

creating means for creating an internodal dependency information identifying those said regions that will be affected by a change in any one of said regions;

10 rendering means for rendering a first image of said series by compositing all regions substantially according to said hierarchical structure;

second examining means for examining said internodal dependency information to identify those of said regions affected by at least one change to at least one of said nodes;

first updating means for updating the corresponding identified regions for each node
15 with affected regions and incorporating into said node those (any) new regions arising from the change;

second updating means for updating said internodal dependency information to reflect changes to said hierarchical structure; and

rendering means for rendering a further image of said series by compositing (only)
20 those regions affected by said at least one change.

According to still another aspect of the present invention there is provided an apparatus for creating a series of images, said images being formed by rendering at least a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at
25 least one of said images, each of said objects having a predetermined outline, said apparatus comprising:

dividing means for dividing a space in which said outlines are defined, for each said node, into at least one mutually exclusive region;

first examining means for examining each said region, for each said node, to
30 determine those objects that contribute to the region;

creating means for creating internodal dependency information based on said examination;

rendering means for rendering a first image of said series utilising said hierarchical structure; and

35 second examining means for examining said internodal dependency information in

response to at least one change to at least one of said nodes and, for a node with affected regions, updating the corresponding regions, updating said internodal dependency information and, rendering a further image of said series by compositing those regions affected by said at least one change.

5 According to still another aspect of the present invention there is provided an apparatus for creating a series of images, said images being formed by rendering at least a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, said apparatus comprising:

10 dividing means for dividing a component image space, for each said node, in which said graphical objects are defined into at least one region;

first examining means for examining each said region;

creating means for creating internodal dependency information for each of said regions;

15 rendering means for rendering a first image of said series utilising said hierarchical structure;

second examining means for examining said internodal dependency information, in response to at least one change to at least one of said nodes; and

first updating means for updating the corresponding regions for an affected node;

20 second updating means for updating said internodal dependency information; and rendering means for rendering a further image of said series.

According to still another aspect of the present invention there is provided a computer program product including a computer readable medium having a plurality of software modules for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said computer program product comprising:

25 dividing module for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions wherein each of said regions is defined by a region outline substantially following at least one of said predetermined outlines or parts thereof;

30 examining module for examining each said region to determine those said objects which contribute to said region;

35 modifying module for modifying said compositing expression on the basis of the contribution of each of said objects within said region to form an optimized compositing

expression for each said region; and

compositing module for compositing said image using each of said optimized compositing expressions.

According to still another aspect of the present invention there is provided a
5 computer program product including a computer readable medium having a plurality of software modules for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said computer program product comprising:

10 dividing module for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions;

examining module for examining each said region to determine those said objects which contribute to said region;

15 modifying module for modifying said compositing expression on the basis of the contribution of each of said objects within said region; and

compositing module for compositing said image using said modified compositing expression.

According to still another aspect of the present invention there is provided a
20 computer program product including a computer readable medium having a plurality of software modules for creating an image, said image comprising a plurality of graphical objects to be composited according to a compositing expression, said computer program product comprising:

dividing module for dividing a space in which said graphical objects are defined into a plurality of regions;

25 examining module for examining each said region to determine those said objects which contribute to said region;

modifying module for modifying said compositing expression on the basis of said examination; and

30 compositing module for compositing said image using said modified compositing expression.

According to still another aspect of the present invention there is provided a
computer program product including a computer readable medium having a plurality of software modules for creating a series of images, each member of said series being related to a preceding member, said images being formed by rendering a plurality of
35 graphical objects to be composited according to a hierarchical structure representing a

compositing expression, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a predetermined outline, said computer program product comprising:

5 dividing module for dividing a component image space in which said outlines are defined, for each said node, into at least one mutually exclusive region, each said region being related to at least one graphical object ;

 first examining module for examining each said region, for each said node, to determine those objects that contribute to the region;

10 creating module for creating an internodal dependency information identifying those said regions that will be affected by a change in any one of said regions;

 rendering module for rendering a first image of said series by compositing all regions of said hierarchical structure;

 second examining module for examining said internodal dependency information to identify those of said regions affected by at least one change to at least one of said nodes;

15 first updating module for updating the corresponding identified regions for each node with affected regions and incorporating into said node those (any) new regions arising from the change;

 second updating module for updating said internodal dependency information to reflect changes to said hierarchical structure; and

20 rendering module for rendering a further image of said series by compositing (only) those regions affected by said at least one change.

 According to still another aspect of the present invention there is provided a computer program product including a computer readable medium having a plurality of software modules for creating a series of images, said images being formed by rendering
25 a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a predetermined outline, said computer program product comprising:

30 dividing module for dividing a space in which said outlines are defined, for each said node, into at least one mutually exclusive region;

 first examining module for examining each said region, for each said node, to determine those objects that contribute to the region;

 creating module for creating an internodal dependency information based on said examination;

35 rendering module for rendering a first image of said series utilising said hierarchical

structure; and

second examining module for examining said internodal dependency information in response to at least one change to at least one of said nodes and, for a node with affected regions, updating the corresponding regions, updating said internodal dependency
5 information and, rendering a further image of said series by compositing those regions affected by said at least one change.

According to still another aspect of the present invention there is provided a computer program product including a computer readable medium having a plurality of software modules for creating a series of images, said images being formed by rendering
10 a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of said image, said computer program product comprising:

dividing module for dividing a component image space, for each said node, in which said graphical objects are defined into at least one region;

15 first examining module for examining each said region;

creating module for creating internodal dependency information for each of said regions;

rendering module for rendering a first image of said series utilising said hierarchical structure;

20 second examining module for examining said internodal dependency information, in response to at least one change to at least one of said nodes; and

first updating module for updating the corresponding regions for a node with affected regions;

25 second updating module for updating said internodal dependency information; and rendering module for rendering a further image of said series.

According to still another aspect of the present invention there is provided a method of processing image data for creating an image by rendering graphical objects to be composited according to a compositing expression, comprising the steps of:

30 dividing a space in which said objects are defined into a plurality of regions in accordance with outlines of the objects;

examining a part of the space by utilizing each said region; and

modifying the compositing expression based on a result of said examining step.

Brief Description of the Drawings

Embodiments of the present invention will now be described with reference to the
35 following drawings:

Fig. 1 is an example of a compositing tree;

Fig. 2 illustrates an image containing a number of overlapping objects and the corresponding compositing tree;

Fig. 3 shows the image of Fig. 2 illustrating the different regions which exist in the image and listing the compositing expression which would be used to generate the pixel data for each region;

Fig. 4 is the image of Fig. 3, illustrating the compositing operations after being optimised according to one example of the preferred embodiments;

Fig. 5 illustrates the result of combining two region descriptions using the Union operation according to the preferred embodiments;

Fig. 6 illustrates the result of combining two region descriptions using the Intersection operation according to the preferred embodiments;

Fig. 7 illustrates the result of combining two region descriptions using the Difference operation according to the preferred embodiments;

Figs. 8A to 8D illustrate the steps involved in combining two region groups using the Over operation according to the present invention;

Fig. 9 illustrates an image and compositing tree according to an example of a further embodiment of the present invention;

Fig. 10 illustrates an image and compositing tree according to another example of the further embodiment;

Fig. 11 illustrates the effect on the image of Fig. 10 of moving region A;

Fig. 12 illustrates an image and compositing tree according to still another example of the further embodiment;

Fig. 13 illustrates the effect on the image of Fig. 12 of moving region A;

Fig. 14 illustrates the effect on the image of Fig. 12 of moving region B; and

Fig. 15 illustrates those nodes in a compositing tree which need to have their region groups updated if leaf nodes B and H change;

Fig. 16 illustrates a region and its x and y co-ordinates;

Fig. 17 illustrates two regions and their x and y co-ordinates;

Fig. 18 illustrates an image and compositing tree according to still another example of the further embodiment;

Fig. 19 illustrates an apparatus upon which the preferred embodiments is implemented;

Fig. 20 depicts the result of a variety of compositing operators useful with the present invention;

Fig. 21 illustrates regions formed by combining two circles with non-grid-aligned regions;

Fig. 22 illustrates improved regions formed by combining two circles with grid-aligned regions;

5 Fig. 23 is a flowchart showing a method of creating an image in accordance with the preferred embodiments;

Fig. 24 is a flowchart showing a method of creating a series of images in accordance with the further embodiment of the present invention; and

Appendix 1 is a listing of source code according to the present invention

10

Detailed Description

1.0 Underlying Principles

The basic shape of operands to compositing operators in most current systems is the rectangle, regardless of the actual shape of the object being composited. It is extremely easy to write an operator which composites within the intersection area of two bounding boxes. However, as a bounding box typically does not accurately represent the actual bounds of a graphical object, this method results in a lot of unnecessary compositing of completely transparent pixels over completely transparent pixels. Furthermore, when the typical make-up of a composition is examined, it can be noticed that areas of many of the objects are completely opaque. This opaqueness can be exploited during the compositing operation. However, these areas of complete opaqueness are usually non-rectangular and so are difficult to exploit using compositing arguments described by bounding boxes. If irregular regions are used for exploiting the opaque objects, then these regions could be combined in some way to determine where compositing should occur. Furthermore, if any such region is known to be fully transparent or fully opaque, further optimisations are possible.

25

Most current systems fail to exploit similarities in composition between one frame and the next. It is rare for everything to change from frame to frame and therefore large areas of a compositing tree will remain unchanged. An example of this is where a cartoon type character comprising multiple graphical objects is rendered on a display. If, for example, the character spilt some paint on its shirt in the next frame, then it is not necessary to render the entire image again. For example, the head and legs of the character may remain the same. It is only necessary to render those components of the image that have been altered by the action. In this instance, the part of the shirt on which the paint has been spilt may be re-rendered to be the same colour as the paint, whilst the remainder of the character stays the same. Exploiting this principle may provide large

35

efficiency improvements. If incremental changes are made to the compositing tree, then only a reduced amount of updating is necessary to affect the change.

Many current graphical systems use what is known as an *immediate mode* application program interface (API). This means that for each frame to be rendered, the complete set of rendering commands is sent to the API. However, sending the complete set of rendering commands to the API is somewhat inefficient in a compositing environment, as typically, large sections of the compositing tree will be unchanged from one frame to the next, but would be completely re-rendered anyway in immediate mode. The preferred embodiment, on the other hand, is considered by the present inventors to be best described as a *retained mode* API. Retained mode means that instead of providing the complete compositing tree on a per-frame basis, the user provides an initial compositing tree, and then modifies it on a per-frame basis to effect change. Changes which can be made to the tree include geometrically transforming part or all of the tree, modifying the tree structure (unlinking and linking subtrees), and modifying attributes (eg: color) of individual nodes. Note that such modifications may not necessarily mean that the tree structure, for example as seen in Fig. 1, will change where only the attributes of an individual node have been modified.

The rendering operation of the preferred embodiments is a combination of a number of techniques and assumptions which combine to provide high quality images and high frame rates. Some of the contributing principles are:

- (i) The use of irregular regions to minimise per-pixel compositing. For example, if one graphical object is on top of another, then pixel compositing is only needed inside the area where the two objects intersect. Having the ability to use irregular regions gives the ability to narrow down areas of interest much more accurately.
- (ii) An assumption is made that in the transition from one frame to the next, only part of the tree will change. This can be exploited by caching away expensive-to-generate information regarding the composition so that it can be re-used from one frame to the next. Examples of expensive-to-generate information are - regions of interest (boundaries of areas of intersection between objects etc); pixel data (representing expensive composites etc); and topological relationships between objects.

- (iii) If an opaque object is composited with another object using the OVER operator, then the opaque object completely obscures what it is composited onto (inside the opaque objects area). This is a very useful property because it means that no expensive pixel compositing is required to achieve the output pixel within the area of overlap. (The pixel value is the same as that at the equivalent spot on the opaque object).

Opaque objects induce similar behaviour in most of the compositing operators. Therefore, the preferred embodiments attempts to exploit opaque areas as much as possible.

Fig. 23 is a flowchart showing a method of creating an image in accordance with the preferred embodiments of the present invention. The image is formed by rendering graphical objects to be composited according to a compositing expression. The process begins at step 2301, where a space in which the object boundary outlines are defined is divided into a number of mutually exclusive regions. Each of the regions is defined by at least one of the predetermined region boundary outlines or parts thereof. The process of dividing the space into a number of regions and manipulating those regions is described in detail particularly with reference to section 2.3 below. Section 2.3 includes two pseudocode listings which describe step 2301 for the "OVER" and "IN" compositing operations. The process continues at step 2303, where one of the regions is selected and examined to determine which objects contribute to the region. At the next step 2305, a compositing expression corresponding to the selected region is modified on the basis of the contribution of each of the objects within the region to form an optimised compositing expression for that region. The process of examining each of the regions and modifying the compositing expression is described in detail particularly with reference to section 2.4 below. Section 2.4 includes two pseudocode listings which describe steps 2303 and 2305 for the "OVER" and "IN" compositing operations. The process continues at step 2307, where image data for the selected region is rendered. At the next step 2309, a check is carried out to determine if any more regions require processing. If more regions require processing, then the process continues to step 2303, where another region is selected. Alternatively, if all of the mutually exclusive regions have been processed, the process concludes at step 2311, where region data for all of the regions is combined to form one image. Steps 2307, 2309 and 2311 are described in detail with reference to section 2.6, below, which includes a pseudocode listing.

2.0 Basic Static Rendering

Static Rendering deals with the problem of generating a single image from a compositing tree as quickly as possible. Some of the pixel compositing methods of the preferred embodiments will be explained using a static rendering example.

An example of a simple compositing tree which consists of leaf node objects and only using the "OVER" operator is shown in Fig. 2. Conventionally, each node is considered to be conceptually infinite in extent. One method to construct the final image is to apply the compositing equation (((D OVER B) OVER C) OVER (A OVER E)) at

every pixel of the output image. However, this is quite an inefficient method.

A composition can generally be subdivided into a number of mutually exclusive irregular regions. The above compositing expression may be simplified independently within each region. In the example of Fig. 2, A, C and E represent opaque objects. B and D, on the other hand are partially transparent. Fig. 3 shows the different regions (1-10) produced using the five objects which exist in the example, and the compositing expression which would be used to generate the pixel data for each specific region.

The compositing expressions provided in Fig. 3 make no attempt to exploit the properties of the object's opacity. If these properties are used to simplify the compositing expressions for each region, the expressions of Fig. 4 are obtained resulting in a simplification of the rendering of regions 2, 3, 5, 6, 7, 8 and 9 compared with Fig. 3. These simplified compositing expressions would result in far fewer pixel compositing operations being performed to produce the final picture.

Fig. 4 represents the region subdivision for the root of the compositing tree. However, every node in the compositing tree can itself be considered the root of a complete compositing tree. Therefore, every node in the compositing tree can have associated with it a group of regions which together represent the region subdivision of the subtree of which the node is the root. Region subdivision provides a convenient means of managing the complexity of a compositing tree and an efficient framework for caching expensive data.

Using the principles noted above, a compositing expression can be simplified dependent upon whether the graphical objects being composited are wholly opaque, wholly transparent or otherwise (herewith deemed "ordinary").

Table 1 shows how the compositing operations of Fig. 20 can be simplified when one or both operands are opaque or transparent.

TABLE 1

Expression	A's opacity	B's opacity	Optimised
AoverB	Transparent	Transparent	neither
	Transparent	Ordinary	B
	Transparent	Opaque	B
	Ordinary	Transparent	A
	Ordinary	Ordinary	AoverB
	Ordinary	Opaque	AoverB
	Opaque	Transparent	A
	Opaque	Ordinary	A
	Opaque	Opaque	A
AroverB	Transparent	Transparent	neither

	Transparent	Ordinary	B
	Transparent	Opaque	B
	Ordinary	Transparent	A
	Ordinary	Ordinary	BoverA
	Ordinary	Opaque	B
	Opaque	Transparent	A
	Opaque	Ordinary	BoverA
	Opaque	Opaque	B
AinB	Transparent	Transparent	neither
	Transparent	Ordinary	neither
	Transparent	Opaque	neither
	Ordinary	Transparent	neither
	Ordinary	Ordinary	AinB
	Ordinary	Opaque	A
	Opaque	Transparent	neither
	Opaque	Ordinary	AinB
	Opaque	Opaque	A
ArinB	Transparent	Transparent	neither
	Transparent	Ordinary	neither
	Transparent	Opaque	neither
	Ordinary	Transparent	neither
	Ordinary	Ordinary	BinA
	Ordinary	Opaque	BinA
	Opaque	Transparent	neither
	Opaque	Ordinary	B
	Opaque	Opaque	B
AoutB	Transparent	Transparent	neither
	Transparent	Ordinary	neither
	Transparent	Opaque	neither
	Ordinary	Transparent	A
	Ordinary	Ordinary	AoutB
	Ordinary	Opaque	neither
	Opaque	Transparent	A
	Opaque	Ordinary	AoutB
	Opaque	Opaque	neither
AroutB	Transparent	Transparent	neither
	Transparent	Ordinary	B
	Transparent	Opaque	B
	Ordinary	Transparent	neither
	Ordinary	Ordinary	BoutA
	Ordinary	Opaque	BoutA
	Opaque	Transparent	neither
	Opaque	Ordinary	neither
	Opaque	Opaque	neither
AatopB	Transparent	Transparent	neither
	Transparent	Ordinary	B
	Transparent	Opaque	B
	Ordinary	Transparent	neither

	Ordinary	Ordinary	AatopB
	Ordinary	Opaque	AatopB
	Opaque	Transparent	neither
	Opaque	Ordinary	AatopB
	Opaque	Opaque	A
AratopB	Transparent	Transparent	neither
	Transparent	Ordinary	neither
	Transparent	Opaque	neither
	Ordinary	Transparent	A
	Ordinary	Ordinary	BatopA
	Ordinary	Opaque	BatopA
	Opaque	Transparent	A
	Opaque	Ordinary	BatopA
	Opaque	Opaque	B
AxorB	Transparent	Transparent	neither
	Transparent	Ordinary	B
	Transparent	Opaque	B
	Ordinary	Transparent	A
	Ordinary	Ordinary	AxorB
	Ordinary	Opaque	AxorB
	Opaque	Transparent	A
	Opaque	Ordinary	AxorB
	Opaque	Opaque	neither

2.1 Basic Data Model

Associated with every node in a compositing tree is a group of mutually exclusive regions which together represent the non-transparent area of the node. It should be noted that the region descriptions that the preferred embodiments uses are generally not pixel accurate. A region may in fact contain some transparent pixels. However, any point lying outside of all the regions at a node is certain to be transparent. The set of the mutually exclusive regions at a node is known as a *region group*. A leaf node region group may contain only one or two regions. The region group at the root of the tree may contain hundreds of regions. Each region in a region group contains the following basic data:

(i) A **Region Description** is a low-level representation of the boundaries of the region. The region descriptions of all the regions in a region group must be mutually exclusive (non-intersecting). However, the preferred embodiments is not limited to using axis-parallel (ie: every side parallel or perpendicular to a scan line of an output device) region descriptions. The preferred embodiments allows region descriptions which more closely represent arbitrary shaped regions.

(ii) A **Proxy** is some means of caching the pixel data resulting from applying the

operations specified by the compositing expression at every pixel inside the region description. A proxy can be as simple as a 24-bit colour bitmap, or something much more complicated (such as a run-length encoded description). Fundamentally, a proxy simply has to represent pixel data in some way which makes it efficient to retrieve and use.

Every region group also contains a region description which is the union of all the region descriptions of the regions in the region group. The region description essentially represents the entire coverage of the region group.

2.2 Region Descriptions and Region Arithmetic

The region arithmetic and data structure of the preferred embodiments has the following properties:

- to allow the representation of *complex* regions, including convex regions, concave regions and regions with holes. This is necessary so that a region will be reasonably able to follow the geometry of the graphic object it represents;

- is space efficient. In a complicated composition there will be many regions. For memory efficiency, it is therefore preferable that the cost of storing these regions is reasonably small;

- the region arithmetic should support basic set operations - Union, Intersection and Difference;

- the above-noted basic operations should be efficient in terms of speed. In a complex compositing tree, it is possible that a large amount of region arithmetic will be undertaken. A poor implementation of region arithmetic could lead to the time taken by region arithmetic being greater than the time saved from the reduction in per-pixel compositing;

- it is advantageous if the region description can be geometrically translated efficiently. In cases where a graphic object is translated, the graphic objects associated regions can then be translated quickly; and

- it is sometimes helpful to be able to quickly compare two regions to determine if they are the same. It is not necessary to obtain any other statistics on their similarity, simple equality is all that is required.

Two conventional region description techniques were considered and rejected for the preferred embodiment. These were-

Polygons: A polygon can be used to represent almost any object, the disadvantage of using a polygon, however, is that a polygon's generality makes implementing the set operations slow and inefficient.

Quadtrees: Using quadtrees, set operations are easy to implement and are quite efficient. In addition, they can represent a wide variety of regions given sufficient granularity (all edges in a quadtree have to be axis-parallel). Their major failing is that all quadtrees must be aligned on the same grid (granularity). This means that it is impossible to simply translate a quadtree by an arbitrary amount. Unless that amount is a multiple of the underlying grid size, the quadtree will need to be recalculated from the object it describes (otherwise it will keep growing). Therefore, quadtrees are not suitable in application domains where geometric translation is a frequent operation.

The region description data structure of the preferred embodiments can be understood by imagining that along a vertical line every coordinate has a state which is one of either inside or outside the region. The data structure stores those y co-ordinates at which some change of state between inside and outside occurs. For each such y co-ordinate, the data contains spans of coordinates each of which toggles the state of every vertical line running through the data. Each span of x co-ordinates is called a run. The sequence of runs associated with a y co-ordinate is called a row. For example, the region of Fig. 16 could be described by the following:

row y = 10 : x = 10, x = 100

row y = 100 : x = 10, x = 100

Similarly, the regions of Fig. 17 could be described by the following:

row y = 10 : x = 10, x = 100

row y = 30 : x = 30, x = 70

row y = 70 : x = 30, x = 70

row y = 100 : x = 10, x = 100

The data representing a region is represented by an array of integer values. There are two "special" values -

R_NEXT_IS_Y A beginning-of-row marker. Indicates that the next integer in the sequence will represent a y coordinate.

R_EOR Stands for End-of-Region. Indicates that the region description has finished.

All other values represent x or y coordinates. The x coordinates in a row represent runs. The first two co-ordinates represent a run, then the next two represent the next run and so on. Therefore, the x coordinates in a row should always be increasing. Also, there should always be an even number of x-coordinates in a row. The region data stream for

Fig. 17 is shown below.

5 R_NEXT_IS_Y 10 10 100
 R_NEXT_IS_Y 30 30 70
 R_NEXT_IS_Y 70 30 70
 R_NEXT_IS_Y 100 10 100
 R_EOR

The preferred embodiments also contains the bounding box of the region, as this is useful in certain set operations.

10 As seen in Fig. 6, if two region descriptions are combined using a Union operation, then the resultant region description will describe an area in which either region description is active.

15 As seen in Fig. 7, if two region descriptions are combined using the Intersection operation, then the resultant region description will describe an area in which both the region descriptions are active.

 If two region descriptions are combined using the Difference operation, then the resultant region will describe an area in which *only the first region is active*, as seen in Fig. 8.

20 2.3 Constructing Region Groups:

2.3.1 Constructing Leaf Node Region Groups

25 A region group for a leaf node will typically contain one or more regions, which together fully contain the non-transparent area of the graphical object represented by the leaf node. Typically, the non-transparent area is divided into regions where each region has some property that facilitates optimization. For example, the non-transparent area of some graphical object can be divided into two regions, one fully opaque and the other with ordinary opacity. The above mentioned compositing optimizations would apply where the opaque region is composited.

30 Alternatively, the leaf node could be subdivided based on some other attribute. For example, a leaf node could be divided into two regions, one representing an area of constant colour, the other representing blended colour. Areas of constant colour may be composited more efficiently than areas with more general colour description.

2.3.1.1 Region Formation and Phasing

35 When creating regions, it is not always beneficial that region boundaries follow graphical object boundaries precisely. What is important is that any property that

facilitates optimization is valid at all points within a region said to have that property. For example, an opaque circle could be covered exactly by one circular region which is classified as opaque, or by two approximate regions, one fully opaque octagonal region inscribed in the circle, and one annular octagonal region of ordinary opacity that includes the remainder of the circle plus some area exterior to the circle.

There is typically a trade-off between how closely region boundaries follow graphical object boundaries and the benefits obtained. If region boundaries follow object boundaries very closely, a lot of work is usually involved in creating the region boundaries and in performing intersections and differences of regions (the reasons for needing to perform such operations are explained in later sections). However, if region boundaries are too approximate, they may either include large areas that are outside the objects' boundaries, resulting in too much unnecessary compositing, or they may fail to include large areas where known properties lead to optimization.

One approach, as illustrated in the appendix, is to limit region boundaries to sequences of horizontal and vertical segments. Using this approach, the typical segment size is chosen so that there is neither too much detail so that the region operations are overburdened, nor too much approximation to result in wasted compositing or insufficient optimization.

One method to improve the efficiency of region operations is to choose as many, as is practical, of the horizontal and vertical segments of substantially all region boundaries to be in phase. In other words, the horizontal and vertical segments are to be chosen from the horizontal and vertical lines of the same grid. The grid need not be regularly spaced, nor have the same spacing horizontally and vertically, although typically it will.

Choosing the horizontal and vertical segments from the horizontal and vertical lines of the same grid improves the efficiency of region operations by seeking to keep all region boundary detail to the level of detail contained in the underlying grid. Without constraining the majority of region boundary segments to a grid, region operators such as difference and intersection tend to produce a lot more fine detail. For example, in Figure 21, two circles 901 and 902 are shown with respective regions 903 and 904 that are not grid-aligned. These circles are overlapped yielding difference regions 905 and 907, and intersection region 906. In Figure 22, the same circles 901 and 902 have regions 913 and 914 that are aligned to grid 910. These circles are overlapped yielding difference regions 915 and 917 and intersection region 916. It can be seen in this example that the grid-aligned regions yield less detailed results at the expense of slightly less efficient region coverage. Regions 905, 906 and 907 together contain a total of sixty segments, while

regions 915, 916 and 917 together contain only fifty-two.

2.3.2 Creating Binary Region Groups

5 The region groups of binary nodes in the compositing tree on the other hand are the result of combining the region groups of their child nodes. It will now be explained how region groups are combined to form new region groups. In this section, for simplicity only "OVER" and "IN" binary nodes will be dealt with. The operations required for binary nodes representing other compositing operators can easily be inferred from combining the "OVER" and "IN" cases in various ways.

10 For the sake of clarity, the method of the preferred embodiments is initially described without reference to optimization based properties such as opacity.

The following notation will be beneficial when considering binary region group creation:

Notation	
RG1	The region group of the binary node's left child
RG2	The region group of the binary node's right child
RG	The region group of the binary node. It is this region group that is being initialised
RG1→urn	The region description representing the union of all RG1's region descriptions (RG1's coverage region).
RG2→urn	The region description representing the union of all RG2's region descriptions (RG2's coverage region).
RG→urn	The union of all RG's region descriptions (to be initialised) (RG's coverage region)
rg1i	The current region in RG1
rg2j	The current region in RG2
rg1i→rgn	rg1i's region description
rg2j→rgn	rg2j's region description
rg1i→proxy	rg1i's proxy
rg2j→proxy	rg2j's proxy

15 2.3.2.1 Constructing "OVER" Region Groups

When constructing "OVER" region groups, only areas where the contributing region groups intersect need to be composited. Areas where one operand does not overlap the other involve no compositing. The method is broken into three iterative steps.

First, the coverage region of the region group of the binary node that is being initialised (RG→urn) is made equal to the union of the coverage regions of the binary nodes left child (RG1→urn) and the binary node's right child (RG2→urn). Then, for each region rg_i in RG1, the difference (diff_rgn) between that region and RG2's coverage region (RG2→urn) is then calculated. If the difference (diff_rgn) is non-empty then a new region with diff_rgn as its region description is added to RG. The proxy of this new difference region can be the same as the proxy rgl_i . No compositing is required to generate it. The difference regions between RG2's regions and RG1's coverage region are similarly constructed and added to RG. Finally, the intersection (inter_rgn) between each region rgl_i in RG1 and each region $rg2_j$ in RG2 is calculated. If the result of this intersection is non-empty, then a new proxy (new_p) is created by compositing rgl_i 's proxy with $rg2_j$'s proxy using the over operation with the inter_rgn. A new region is then added to RG with inter_rgn as its region description and new_p as its proxy. The method of constructing "OVER" region groups in accordance with the preferred embodiment is described below using pseudo-code.

```
RG→urn = RG1→urn union RG2→urn
FOR i = 0 TO number of regions in RG1 DO
    diff_rgn =  $rg1_i$ →rgn difference RG2→urn
    IF diff_rgn is non-empty THEN
        20      ADD to RG a new region with diff_rgn as its region description and
         $rg1_i$ →proxy as its proxy. (*)
    END IF
    FOR j = 0 TO number of regions in RG2 DO
        inter_rgn =  $rg1_i$ →rgn intersection  $rg2_j$ →rgn
        25      IF inter_rgn is non-empty THEN
            create new proxy new_p initialised to OVER of  $rg1_i$ →proxy and
             $rg2_j$ →proxy inside inter_rgn.
            ADD to RG a new region with inter_rgn as its region description
            and new_p as its proxy. (+)
        30      END IF
    END DO
END DO
FOR j = 0 TO number of regions in RG2 DO
    diff_rgn =  $rg2_j$ →rgn difference RG1→urn
    35      IF diff_rgn is non-empty THEN
```

ADD to RG a new region with diff_rgn as its region description and
rg2_j→proxy as its proxy. (*)

END IF

END DO

5

The regions added by the ADD operations marked with asterisks (*) above are termed difference regions since their shape is the result of a difference operation. Such regions are very cheap computationally because their proxies require no compositing. The only work involved is the administrative overhead of adding a new region to the region group and the cost of the difference operation itself. In the preferred embodiment, a proxy is inherited from the region (in one of the child region groups) on which it is based. It can be seen that proxies which originate low in the compositing tree can be propagated upwards towards the root with minimal overhead (both in terms of speed and memory) by the use of difference regions.

10

15

The regions added by the ADD operation marked with the plus (+) are termed intersection regions. This is because their shape is the result of an intersection operation. The proxies of such regions are more expensive to generate than difference regions because they involve per-pixel compositing operations to be done within the area defined by the intersection. The more fidelity granted the region descriptions, the greater the saving in pixel processing costs, at the cost of a greater administrative overhead (more complex regions require longer to intersect etc).

20

25

30

Figs. 8A to 8D provide a simple example of combining "OVER" region groups using the above method. The region group resulting from the combination contains 5 regions, 3 difference regions and 2 are intersection regions. Fig. 8A represents two region groups RG1 and RG2 which are to be combined. RG1 contains two regions 81 and 82, whereas RG2 only contains a single region 83. As seen in Fig 8B, for each region in RG1, RG2's region coverage is subtracted from the corresponding region in RG1. If the resultant region is non-empty, the resultant region becomes a region in the new region group. In this example both regions 81 and 83 produce non-empty difference regions 84 and 85 respectively. For each region in RG2, RG1's region coverage is subtracted from it, as seen in Fig 8C. In this example difference region 86 is produced. Finally, every region in RG1 is intersected with every region in RG2, as seen in Fig 8D. Any non-empty region becomes a region in the new region group. In this example, regions 81 and 83 produce 87. Further, regions 82 and 83 produce 88.

35 2.3.2.2 Constructing "IN" Region Groups

The properties of the "IN" operator lead to the fact that an "IN" binary region group only produces pixel data in the region of intersection between the two contributing region groups. Essentially, when compared to the algorithm used for "OVER" region groups, only intersection regions are generated. Therefore, for each region $rg1_i$ of RG1, and for each region $rg2_j$ of RG2 the intersection ($inter_rgn_{ij}$) between $rg1_i$ and $rg2_j$ is calculated. If the intersection is non-empty then a new proxy (new_p) is created by compositing $rg1_i$'s proxy with $rg2_j$'s proxy using the "in" operation within $inter_rgn_{ij}$. A new region is then added to RG with $inter_rgn$ as its region description and new_p as its proxy. The pseudocode for the method of constructing "IN" region groups according to the preferred embodiment is provided below:

```
RG→urn = RG1→urn intersection RG2→urn
FOR i = 0 TO number of regions in RG1 DO
    FOR j = 0 TO number of regions in RG2 DO
        inter_rgn =  $rg1_i$ →rgn intersection  $rg2_j$ →rgn
        IF inter_rgn is non-empty THEN
            create new proxy new_p initialised to IN of  $rg1_i$ →proxy and
             $rg2_j$ →proxy inside inter_rgn.
            ADD to RG a new region with inter_rgn as its region description
            and new_p as its proxy. (+)
        END IF
    END DO
END DO
```

The major difference between the "IN" and the "OVER" cases is that the "OVER" case generates difference regions while "IN" does not. In the example demonstrated by Figs. 8A to 8D, only new regions 97 and 98 would be generated, as these are intersection regions. Difference regions 94, 95 and 96 would not be generated using "IN".

Using Table 2 below and the pseudocode examples of "OVER" and "IN", the relevant code for other compositing operators can be derived.

2.3.2.3 Constructing Region Groups of Other Compositing Operators

Other compositing operators typically generate the same intersection regions as the "OVER" and "IN" cases do. However, they typically differ from one another (as indeed from "OVER" and "IN") in what difference regions they generate. This is dependent on the particular properties of each compositing operator. Table 2 summarises which difference regions are generated for some commonly used compositing operators.

TABLE 2

Compositing Operator	Generate Diff Rgns from RG1 ?	Generate Diff Rgns from RG2 ?
Over	Yes	Yes
In	No	No
Out	Yes	No
Atop	No	Yes
Xor	Yes	Yes
Plus	Yes	Yes

2.4 Optimising using Opaque Areas

5 The preferred embodiment stores within each region a flag indicating whether the pixel data in the region proxy is completely opaque. It is therefore possible to reduce the number of per-pixel compositing operations by exploiting the effect opaque operands have on the compositing operators.

2.4.1 Opaque Area Optimisation for "Over" Region Groups

10 If an opaque region is "OVER" another region, then there is no need to compute the result of the composite, as no part of the right operand region's proxy is visible through the left operand's opaque proxy. In the preferred embodiment, the resultant region is made to reference the right operand's proxy, which has the same effect as actually doing the composite.

15 The method of opaque area optimisation for "OVER" region groups is a slightly modified version of the "OVER" region group construction method provided previously. The only difference is that when calculating the intersection region of the current region in RG1 and each region of RG2, a check is carried out to see whether the current region in RG1 is opaque. If this is the case, then the proxy of the newly calculated region (new_p) will be the proxy of the current region in RG1.

20 The method is illustrated using the following pseudocode :

RG→urn = RG1→urn union RG2→urn

FOR i = 0 TO number of regions in RG1 DO

diff_rgn = rg1_i→rgn difference RG2→urn

25 IF diff_rgn is non-empty THEN

ADD to RG a new region with diff_rgn as its region description and

```

rg1i→proxy as its proxy. (*)
    END IF
    FOR j = 0 TO number of regions in RG2 DO
        inter_rgn = rg1i→rgn intersection rg2j→rgn
5        IF inter_rgn is non-empty THEN
            IF rg1i is OPAQUE THEN
                new_p = rg1i→proxy
            ELSE
                create new proxy new_p initialised to OVER of rg1i→proxy
10        and rg2j→proxy inside inter_rgn.
            END IF
            ADD to RG a new region with inter_rgn as its region description
            and new_p as its proxy. (+)
            END IF
15        END DO
    END DO
    FOR j = 0 TO number of regions in RG2 DO
        diff_rgn = rg2j→rgn difference RG1→urn
        IF diff_rgn is non-empty THEN
20        ADD to RG a new region with diff_rgn as its region description and
        rg2j→proxy as its proxy. (*)
        END IF
    END DO

```

25 2.4.2 Opaque Area Optimisation for "IN" Region Groups

If a region is "IN" an opaque region, then according to the properties of the "IN" operator, the resultant pixel data is the same as that of the left operand. This can be achieved by having the resultant region simply reference the proxy of the left operand. The method of the preferred embodiments is a slightly modified version of the "IN" region group construction method provided previously. The only difference is that when calculating the intersection region of the current region in RG1 and each region of RG2, a check is carried out to see whether the current region in RG2 is opaque. If this is the case, then the proxy of the newly calculated region (new_p) will be the proxy of the current region in RG1.

35 The technique is illustrated using the following pseudocode:

```
RG→urn = RG1→urn intersection RG2→urn
FOR i = 0 TO number of regions in RG1 DO
    FOR j = 0 TO number of regions in RG2 DO
5        inter_rgn = rg1i→rgn intersection rg2j→rgn
        IF inter_rgn is non-empty THEN
            IF rg2j is OPAQUE THEN
                new_p = rg1i→proxy
            ELSE
10                create new proxy new_p initialised to IN of rg1i→proxy and
                rg2j→proxy inside inter_rgn.
            END IF
            ADD to RG a new region with inter_rgn as its region description
            and new_p as its proxy. (+)
15        END IF
    END DO
END DO
```

2.5 Initialising the Entire Tree

```
20    The entire compositing tree can be initialised by using the above-described method
    of the preferred embodiments on every binary region group in the tree. A node cannot be
    initialised until its children have been initialised. Therefore the process simply starts at
    the bottom of the tree and works its way up towards the root. The process first checks to
    see if the current node is a leaf node. If this is the case, then a leaf node region group is
25    constructed. However, in the case that the current node is a binary node then a binary
    node region group is constructed using the method of the preferred embodiments outlined
    in sections 2.4.1 and 2.4.2. The following pseudocode outlines a method for initialising
    all the region groups of the tree. The method utilises a recursive function, which is called
    passing the root of the tree as an argument.
30
```

```
tree_init(node : tree ptr)
BEGIN
    IF node is a leaf node THEN
        CONSTRUCT leaf node region group
35    ELSE
```

```
tree_init(node→left)
```

```
tree_init(node→right)
```

CONSTRUCT binary node region group by combining region groups of the left and right children

```
5      END IF  
      END tree_init
```

2.6 Constructing the Resultant Image

Once the compositing tree has been initialised, the region group at the root of the tree contains a group of zero or more regions which together represent the partitioning of the resultant image into areas which differ in the way the image data was generated. Some of the regions' proxies can refer to image data directly from leaf nodes of the tree, having not required any compositing. Other regions, on the other hand, may have proxies which are the result of compositing operations. If a single resultant image is required, such as an image stored in a pixel buffer, this can be achieved by copying the image data from each region's proxy to the pixel buffer within the area corresponding to the region. The process is demonstrated in the pseudocode provided below, which is generalised and able to restrict the construction of the final image to any nominated update region.

```
20  construct_image  
    (  
        output_image : pixel data ptr,  
        urn : region description  
    )  
25  BEGIN  
    FOR i = 0 TO number of region in RG DO  
        int_rgn = rgi→rgn intersection urn  
        IF int_rgn is non-empty THEN  
            COPY image data from rgi→proxy to output_image inside int_rgn  
30      END IF  
    END DO  
  END construct_image
```

3.0 Dynamic Rendering

35 Dynamic Rendering refers to the problem of generating multiple successive images.

Given a compositing tree, it is possible to generate it's region groups (containing regions and proxies) using the method described above. A further embodiment to the above-mentioned method, which supports dynamic rendering is described below. The compositing tree represents an image. Changes to the tree can be made to make the tree
5 represent a new image. The tree's region groups (and tree region description and proxies) are updated to reflect the modified tree. Performance is improved by exploiting commonality between the two images. An example will illustrate the techniques and terminology of the further embodiment.

Fig. 3 shows the region subdivision and the respective compositing expressions
10 (advantage is not taken of opacity) for the simple compositing tree. Consider therefore the situation in which object A moves by a small amount relative to the other objects. Some regions in the region group at the root of the tree will be affected by A moving.

If opaque case optimisations are ignored, the regions with compositing expressions which include A will be significantly affected by A moving. The region numbers which
15 are so affected are 2, 3, 5 and 6. When updating the region group at the root of the tree, those regions will need both their region descriptions and their proxies completely recalculated. This situation is known in the further embodiment as primary damage. Any region whose compositing equation includes an object which has changed in some way, may be said to suffer primary damage.

Regions that abut regions which have A in their compositing expression are also
20 effected by A moving, though not as severely as those regions with primary damage. In the example, these other affected regions are 1, 4, 7 and 8. When updating the region group at the root of the tree, these regions will need their region descriptions recalculated. However, their proxies will only need to be recalculated in areas of the new region which
25 were not included in the corresponding earlier region. This situation is known in the further embodiment as secondary damage. Generally, secondary damage is incurred if an object upon which a region's boundary (but not content) depends, changes in some way.

In order to reduce the per-frame update cost, it is important to reduce, as far as is practicable, the amount of work necessary, both in terms of per-pixel operations, but also
30 in terms of region group operations. The concepts of primary and secondary damage are a way of facilitating this. If the further embodiment is able to accurately determine the minimum set of regions throughout all the compositing tree which have some kind of damage, then obviously the amount of work being done is reduced.

Fig. 24 is a flowchart showing a method of creating a series of images in
35 accordance with a further embodiment of the present invention. Each member of the

series of images is related to a preceding member. The images are formed by rendering a number of graphical objects to be composited according to a hierarchical compositing tree representing a compositing expression. Each node of the hierarchical compositing tree represents a component of at least one of the images and each of the objects has a predetermined outline. The process begins at step 2401, where a hierarchical compositing tree representing a first image is accessed. At the next step 2403, for each node of hierarchical compositing tree, the component image space is subdivided into a number of mutually exclusive regions. The process continues at step 2405, where each of the mutually exclusive regions is examined and internodal dependency information is created. The data structure of the internodal dependency information and the process for creating it are described in sections 3.1 to 3.9 below. At the next step 2407, the first image is rendered according to the hierarchical structure. The process continues at step 2409, where the image changes resulting in changes to the hierarchical compositing tree. At the next step 2411, the dependency information is examined to determine which regions have been affected by the changes to the hierarchical compositing tree. The process continues at the next step 2413, where affected regions are updated. At the next step 2415, the internodal dependency information is updated to reflect the changes to the hierarchical compositing tree. The process of examining and updating the regions is described in sections 3.6 to 3.9, below. In particular, section 3.9 includes a pseudocoding listing which illustrates a method for updating a binary "OVER" region. The process continues at step 2417, where the changed portions of the first image are rendered according to the hierarchical compositing tree to produce the updated image. Only those regions affected by the change are rendered at step 2417.

3.1 Basic Data Model

The data model used for static rendering, consisting as it does of a region description and a proxy, is insufficient for use in dynamic rendering. This is because, for primary and secondary damage to be determined, it must be possible to associate regions of the same content between frames. To support the association of regions of the same content, some extra information is required in each region in a region group. Therefore, each region in a region group now contains the following data:

(i) A Region Description: A low-level representation of the boundaries of the region. The region descriptions of all the regions in a region group must be mutually exclusive (non-intersecting, non-overlapping).

(ii) A Proxy: Some means of caching the pixel data resulting from applying the

operation specified by the compositing expression at every pixel inside the region description. A proxy can be as simple as a 24-bit colour bit-map, or something much more complicated (such as a run-length encoded description). Fundamentally, a proxy simply has to represent pixel data in some way which makes it efficient to retrieve and use.

(iii) A Contents Label: A contents label represents a unique symbolic expression that describes the method of construction of image data. The terms in the symbolic expression distinguish between different categorisations of a source of image data. Therefore, the region groups of two distinct leaf nodes in the compositing tree will contain regions which are labelled with distinct contents labels even if their actual image data is equivalent. The further embodiment uses a system of unique integers to represent contents labels. For example "23" could represent "(A over B) over C".

(iv) A Flag Register: A general-purpose flag register used to store state during the region group update process. The exact flags stored here will be outlined in a later section.

3.2 Contents Labels

Leaf node region groups can contain multiple regions, with each region naturally having a unique contents label. For example, the region group of a leaf node in a compositing tree could contain a single region (tagged with a single contents label) representing the non-transparent area of the leaf node. Alternatively, the leaf node region group could contain two regions (each tagged with a different contents label), one representing the area of the leaf node which is completely opaque, the other representing the remaining non-transparent area. A leaf node can also be categorised even further, into an arbitrary number of regions (and associated contents labels).

One way a contents label can be created is by assigning a new one to a region of a leaf node region group. Another way is taking other contents labels and combining them to create a new contents label that represents the symbolic expression that represents the combination of the contributing expressions. For example, if the contents label representing ((A comp B) comp C) is combined with the contents label representing (D comp E) then a new contents label will be created which represents (((A comp B) comp C) comp (D comp E)).

As well as contents labels, dependency information is also required. Dependency information indicates how a given contents label is related to other contents labels, both in terms of how the contents of one region contribute to contents of other regions, and how change of a region boundary affect the boundary of other regions. The further

embodiment associates the following data with each contents label.

(i) Primary Dependency List: Each primary dependency is a contents label L' to which a contents label L directly contributes. In other words, a "primary dependency" is a contents label L' representing an expression which has been constructed by combining L and some other contents label. Each time contents labels are combined, the contents label for the combination is added to the primary dependencies of all contributors.

(ii) Secondary Dependency List: Each secondary dependency is a contents label L'' which can be indirectly affected if the image represented by the contents label L has changed in some way that affects its boundary. Whenever contents labels are combined, a contributing contents label is added to the secondary steps of the continuation if and only if the compositing operator yields a difference region with said contributing contents label. Table 2 shows which of some commonly used operators yield difference regions for their left and right operands. In addition, for a combination of $(A \text{ comp } B)$, the secondary dependencies of the combination contents labels for all $(A \text{ comp } b_i)$ and all $(a_j \text{ comp } B)$ are added, where a_j are the secondary dependencies of A and b_i are the secondary dependencies of B .

(iii) Property Information: Each contents label can represent contents which have properties which the compositing engine may be able to exploit. An example is that of opacity. If a contents label represents opaque content, then compositing that content could be much faster, as for certain operators, no per-pixel compositing operations would be required.

3.3 Contents Label Implementation

The further embodiment uses unique integers as contents labels, and stores a number representing the number of contents labels which currently exist. When a new contents label is created, the number is incremented and becomes the unique integer representing the contents label. This technique of assigning a contents label by monotonically incrementing an integer means that the contents labels' associated data structures can be stored in a one dimensional array which grows as more contents labels are added. A content label's data structure can be referenced simply by using the contents label as an index. When a leaf node contents label is created, the contents label is initialised to have no primary or secondary dependencies. If the current leaf node contents label is opaque, then a flag is set in content label i 's properties.

The pseudocode below illustrates the basic techniques used to create a new contents label which is not dependent on other contents labels (ie: a leaf node region group contents label):

Notation

opaque	A flag passed to the function which indicates whether or not the contents label represents opaque content or not.
cur_clab	A global integer which stores the last contents label created.
clabs	A global array which stores the associated data structures of the contents label.
clabs[i]->pri_deps	A pointer to the head of content label i's primary dependency list.
clabs[i]->sec_deps	A pointer to the head of content label i's secondary dependency list.
clabs[i]->properties	A flag register representing contents label i's properties.

create_new_contents_label

```

(
    opaque : boolean
5  ) : RETURNS unsigned int
BEGIN
    INCREMENT cur_clab.
    clabs[cur_clab]→pri_deps = NULL.
    clabs[cur_clab]→sec_deps = NULL.
10  IF opaque THEN
        clabs[cur_clab]→properties = OPAQUE.
    ELSE
        clabs[cur_clab]→properties = 0.
    END IF
15  RETURN cur_clab.
END create_new_contents_label.
```

Contents labels can also be created to represent the combination of existing contents labels. This is achieved in the further embodiment by a hash table which maps an operation and the contents labels of its operands (hashed together to create a key) to a single contents label representing the result.

When a region is created which represents an intersection between two other regions (each with its own contents label), a new contents label is generated which is used to tag the new region. When this new contents label is generated, it must be added to the primary dependency lists of both its contributing operands. A secondary dependency list

which depends on the secondary dependencies of the two contributing contents labels as well as the properties of the compositing operator must also be generated.

The process is recursive and begins by adding the newly created contents label (new_cl) to the primary dependency lists of the contributing contents labels. Then, depending on the properties of the compositing operator, none, either or both of the contributing contents labels are added to the secondary dependency list. Then every contents label representing (clab1 op sd2_i) and (sd1_i op tab2) are added to the secondary dependency list.

Notation

clab1	The first contributing contents label.
clab2	The second contributing contents label.
sd1 _i	The i'th element of clab1's secondary dependency list.
sd2 _i	The i'th element of clab2's secondary dependency list.

10

```
create_binary_contents_label
(
    clab1 : contents label,
    clab2 : contents label,
    op: compositing operator
)
BEGIN
```

15

```
    IF the hash table already contains an entry representing clab1 op clab2
    THEN
```

20

```
        RETURN the existing contents label representing the combination.
    END IF
```

```
    Generate a new entry in the hash table representing clab1 op clab2, map-
    ping to new_cl.
```

25

```
    (Add the new contents label to the primary dependency lists of the contrib-
    uting contents labels if the compositing op requires it)
    add_to_primary_dep_list(clab1, new_cl)
    add_to_primary_dep_list(clab2, new_cl)
```

```
(Generate the secondary dependencies)
IF op generates left diff rgns THEN
    add clab1 to secondary deps
5  END IF
IF op generates right diff rgns THEN
    add clab2 to secondary deps
END IF
FOR i = 0 TO number of elements in sd1 DO
10  add_to_secondary_dep_list
    (
        new_cl,
        create_binary_contents_label(sd1i, clab2)
    )
15  END DO

FOR i = 0 TO number of elements in sd2 DO
    add_to_secondary_dep_list
    (
20  new_cl,
        create_binary_contents_label(clab1, sd2i)
    )
END DO
END construct_binary_contents_label
25
```

3.4 Combining Region Groups for Dynamic Rendering

Before any incremental updates can be made to a compositing tree, the compositing tree must be constructed to be in a consistent initial state. The basic technique for achieving this is the same as that used for static rendering, except that support for contents labels is included.

Leaf node region groups are initialised essentially as with static rendering, except that each region in each leaf node region group is tagged with a unique contents label. Each contents label can in turn be tagged with various categorisation properties which may help the renderer to be more efficient. For example, a contents label can be tagged as being completely opaque.

The initialisation of binary nodes is also similar to the static rendering case. By way of example, the way in which the region group for an "OVER" binary node is constructed will now be explained. The techniques for constructing the region groups of the other compositing operators can easily be inferred from the "OVER" case.

- 5 When a difference region between rg_i of one operand and the coverage region of the other operand is calculated, the difference region inherits the contents label rg_i . When an intersection region is created, on the other hand, a new contents label is created by combining the contents labels of the two contributing regions since the two contributing regions had their proxies composited into a new proxy which means new content. The
- 10 pseudocode for constructing an "OVER" region group which includes contents label management is provided below:

Notation	
RG1	The region group of the binary node's left child
RG2	The region group of the binary node's right child
RG	The region group of the binary node. It is this region group that we are initialising
RG1→urn	The region description representing the union of all RG1's region descriptions (RG1's coverage region).
RG2→urn	The region description representing the union of all RG2's region descriptions (RG2's coverage region).
RG→urn	The union of all RG's region descriptions.
rg1i	The current region in RG1
rg2j	The current region in RG2
rg1i→rgn	rg1i's region description
rg2j→rgn	rg2j's region description
rg1i→proxy	rg1i's proxy
rg2j→proxy	rg2j's proxy

RG→urn = RG1→urn union RG2→urn

- 15 FOR i = 0 TO number of regions in RG1 DO
 diff_rgn = rg1i→rgn difference RG2→urn

```

    IF diff_rgn is non-empty THEN
        ADD to RG a new region with diff_rgn as its region description,
        rg1i→proxy as its proxy and rg1i→clab as its contents label.
    END IF
5    FOR j = 0 TO number of regions in RG2 DO
        inter_rgn = rg1i→rgn intersection rg2j→rgn
        IF inter_rgn is non-empty THEN
            new_clab = GENERATE a new unique contents label as a result
            of combining rg1i→clab and rg2j→clab.
10           IF rg1i→clab is OPAQUE THEN
                new_p = rg1i→proxy
            ELSE
                create new proxy new_p initialised to OVER of rg1i→proxy
                and rg2j→proxy inside inter_rgn.
15           END IF
                ADD to RG a new region with inter_rgn as its region description,
                new_p as its proxy and new_clab as its contents label.
            END IF
        END DO
20    END DO
    FOR j = 0 TO number of regions in RG2 DO
        diff_rgn = rg2j→rgn difference RG1→rgn
        IF diff_rgn is non-empty THEN
            ADD to RG a new region with diff_rgn as its region description,
25    rg2j→proxy as its proxy and rg2j→clab as its contents label.
        END IF
    END DO
```

3.5 Secondary Dependencies and Over

30 The rationale behind the method used for generating secondary dependencies requires more explanation. Secondary dependencies are only generated when a new contents label is created by combining two other contents labels. As can be seen in the above pseudocode, this only occurs when an intersection region is generated. Essentially, the further embodiment uses contents labels generated for intersection regions as triggers

35 - the regions tagged with two contents labels cannot indirectly affect one another unless

they intersect. The secondary dependency list for a particular contents label is dependent on the compositing operator the composite contents label represents, the two contributing contents labels and their secondary dependency lists.

The method of the further embodiment of generating a secondary dependency list for a new contents label (C) which represents one contents label (A) composited over another contents label (B) using the "OVER" operator will now be explained. Elements of A's and B's secondary dependency lists are referred to as A_i and B_i respectively. First, both A and B are added to C's secondary dependency list. This is because if the region tagged with C changes its boundary, then it is likely that any regions tagged with A and B will need to be recalculated (because their regions are likely to abut C's region). Next, for each element of B's secondary dependency list, each contents labels representing (A OVER B_i) is added. A mapping representing A OVER B_i can not currently exist in the system and needs to be created. A secondary dependency list can contain contents labels which are not represented by any region in a region group. They could come into existence by changes in region boundaries. The rationale is that A intersects B, and therefore it is likely that A also intersects regions tagged with contents labels which exist in B's secondary dependency list. Similarly, for each element of A's secondary dependency list, each contents label representing (A_i OVER B) is added.

3.6 Contents Labels and Damage

The concepts of primary and secondary damage were introduced with reference to Fig. 3 to demonstrate that it is not always necessary to regenerate an entire image as a result of a change to the compositing tree. By keeping track of dependencies between regions of different content, it only becomes necessary to regenerate image data in regions whose contents have become damaged. The following explanation outlines the dependencies and damage for simple compositing tree changes. "Simple" means that only leaf nodes are modified. More complex change scenarios such as tree structure changes etc will be outlined in later sections.

If a leaf node is modified, the contents labels of its affected regions are said to be "primary damaged". Primary-damaging a contents label involves recursively primary-damaging all its primary dependencies. Whenever a contents label is primary-damaged, all its secondary dependencies are non-recursively marked with secondary damage. The process begins by flagging the contents label to be damaged. The following pseudocode demonstrates how contents labels can be damaged:

Notation

clab	The contents label to be damaged
pdi	The i'th element of clab's primary dependency list.
sdi	The i'th element of clab's secondary dependency list.

damage_contents_label

(

clab : contents label,

5)

BEGIN

FLAG clab with PRIMARY damage

FOR i = 0 TO number of elements in sd DO

10

FLAG sdi with SECONDARY damage

END DO

FOR i = 0 TO number of elements in pd DO

damage_contents_label(pdi)

15

END DO

END damage_contents_label

When a tree update occurs, any region with its contents label marked as having primary damage will need to recalculate both its region boundaries and its proxy. Any region with its contents label marked as having secondary damage will need to recalculate its region description but will only need to recalculate its proxy in areas of the new region that were not included in the earlier region.

3.7 Examples of Contents Labels and Dependencies

25 In order to clarify the concepts of contents labels and damage, some examples of varying complexity will be presented.

3.7.1 Example 1

30 Fig. 9 will result in the following contents label table after the compositing tree is initially constructed (Note: in the following table contents labels are represented as unique strings not as integers where "over" has been abbreviated to "o". This is simply for readability):

Contents Label	Primary Deps.	Secondary Deps.
A	AoB	
B	AoB	
AoB		A, B

5 If A moves, then AoB will have primary damage, resulting in B having secondary damage.

3.7.2 Example 2

Fig. 10 will result in the following contents label table after the compositing tree is initially constructed:

Contents Label	Primary Deps.	Secondary Deps.
A	AoB, AoC	
B	AoB, BoC	
AoB	AoBoC	A, B
C	AoC, BoC, (AoB)oC	
AoC		A, C
BoC		B, C
(AoB)oC		AoB, C, AoC, BoC

10

In this example, every object intersects every other object, so if something changes, everything will be damaged in some way - everything which is a primary dependency of the changed object will have primary damage, whereas everything else will have secondary damage.

15 Fig. 11 illustrates the effect of A moving in a subsequent frame. As can be seen, if A is damaged, the regions defined by A, AoB, AoC and (AoB)oC will each have primary damage. The regions defined by B, C and BoC will each have secondary damage.

3.7.3 Example 3

20 Fig. 12 will result in the following contents label table after the compositing tree is initially constructed:

Contents Label	Primary Deps.	Secondary Deps.
A	AoB, AoC, AoE, Ao(DoE), AoD	
B	AoB, BoC, BoE	
AoB	AoBoE	A, B

D	DoE, AoD, CoD, (AoC)oD	
E	DoE, AoE, (AoB)oE, BoE, CoE, (BoC)oE, (AoC)oE	
DoE	Ao(DoE), (AoC)o(DoE), Co(DoE)	D, E
C	AoC, BoC, Co(DoE), CoE, CoD	
AoC	AoCoE, (AoC)o(DoE), (AoC)oD	A, C
BoC	(BoC)oE	B, C
AoE		A, E
(AoB)oE		AoB, E, AoE, BoE
BoE		B, E
CoE		C, E
(BoC)oE		BoC, E, BoE, CoE
AoD		A, D
CoD		C, D
(AoC)oE		AoC, E, AoE, CoE
Ao(DoE)		A, DoE, AoD, AoE
Co(DoE)		C, DoE, CoD, CoE
(AoC)o(DoE)		AoC, DoE, Ao(DoE), Co(DoE), (AoC)oD, (AoC)oE
(AoC)oD		AoC, D, AoD, CoD

Since A intersects every other object, if A moves, a large amount of the compositing tree will need to be recomputed. Fig. 13 shows that the only part left alone is the area corresponding to BoC and its dependent BoCoE. To summarise:

- 5
- Primary Damage - A, AoB, AoC, AoE, Ao(DoE), (AoB)oE, (AoC)oE, (AoC)o(DoE), AoD, (AoC)oD
 - Secondary Damage - B, C, E, DoE, BoE, CoE, DoE, CoDoE

On the other hand, if B moves, the amount of damage is less than if A moved. This is because B doesn't intersect D. DoE, Ao(DoE), (AoC)o(DoE), Co(DoE) and (AoC)oE (and their ancestors) are not damaged when B moves. This is shown in Fig. 14. The rest of the damage is summarised as:

- 10
- Primary Damage - B, AoB, BoC, BoE, (AoB)oE, (BoC)oE
 - Secondary Damage - A, E, C, AoE, CoE

The examples presented so far are simple, but they are sufficient to demonstrate that the dependencies techniques presented so far will damage those contents labels which are affected when a particular contents label/s is(are) damaged. In a typical complex composite, it is rare for large numbers of objects to intersect a large number of other

15

objects, meaning that large areas of the compositing tree should be untouched during updates using the above technique.

3.8 Example of Secondary Dependencies and Compositing Operators

Consider a modified version of Example 3 above. Fig. 18, will result in the following contents label table after the compositing tree is initially constructed. Note that AaB represents A ATOP B and AiB represents A IN B etc:

Contents Label	Primary Deps	Secondary Deps
A	AaB	
B	AaB, BoC	
AaB		B
C	BoC, Co(DiE)	
BoC		B, C
D	DiE	
E	DiE	
DiE	Co(DiE)	
Co(DiE)		C, DiE

As seen in Fig. 18, the ATOP operator clips A to B's bounds, meaning that intersections between A and any of C, D or E never occur. Similar things occur with the IN operator. This means that the objects in this scene are less tightly coupled. For example, if A is changed, then only B and AaB are immediately damaged. Similarly, if E is damaged, it is only possible for DiE to be damaged.

3.9 Updating Region Groups

The further embodiment uses the contents label and damage framework to reduce the amount of work that has to be done to make a binary region group consistent with its updated operands during an update. The further embodiment does this by only updating those regions in a region group whose contents labels have primary or secondary damage, adding any new region which comes into existence as a result of the changes made to the compositing tree, and deleting any region in the right group whose contact no longer exists.

Each different binary operator has a different updating function which deals with the specific requirement of that operator. The process of updating region groups is a two-pass process. The first pass updates any intersection regions that have been primary damaged and adds any new intersection regions generated due to the damage. Each region of one operand's region group is intersected with each region of the other operand's

region group whenever one or both of their corresponding contents labels are primary damaged. If the intersection is non-empty, then the further embodiment determines if a contents label representing the combination exists. If the contents label doesn't exist, one is created and primary damaged. Note that primary damaging a contents label will mark all it's secondary dependencies with secondary damage.

If a region in the region group is currently tagged with the primary damage contents label, the region boundary and proxy are updated. If no such region exists in this region group, then a new region keyed by this contents label is added to the region group. A new proxy is generated and assigned to this region along with the right description relating from the intersection operation.

A difference between each region group of one operand and the coverage region of the other operand is calculated whenever the regions contents label has primary or secondary damage. If the difference is non-empty and a region tagged with the contents label exists in the region group, then it's region description and proxy reference are updated. If such a region doesn't exist then a region keyed by the contents label is added to the region group. The added region is assigned as a coverage region of the difference result and references the proxy of current region.

Each region of one operand's region group is interacted with each region of the other operand's region group whenever the contents label representing their combination has secondary damage and no primary damage. If the intersection is non-empty, the region group is searched looking for a region keyed by the contents label. If such a region exists its region description is updated and it's proxy is updated as the difference between the new and old regions. If such a region doesn't exist, then a region keyed by the contents label is created. The created region description is assigned the result of the interaction operation and it's proxy generated.

Pseudocode which illustrates a simple algorithm for updating a binary "OVER" region group is provided below.

Notation

RG1	The region group of the binary node's left child
RG2	The region group of the binary node's right child
RG	The region group of the binary node. It is this region group that is being initialised.
RG1→urgn	The region description representing the union of all RG1's region descriptions (RG1's coverage region).

RG1→urn	The region description representing the union of all RG2's region descriptions (RG2's coverage region).
RG→urn	The union of all RG's region descriptions.
rg1i	The current region in RG1
rg2j	The current region in RG2
rg1i→rgn	rg1i's region description
rg2j→rgn	rg2j's region description
rg1i→proxy	rg1i's proxy
rg2j→proxy	rg2j's proxy
rg1i→clab	rg1i's contents label
rg2j→clab	rg2j's contents label

RG→urn = RG1→urn union RG2→urn

(First Pass - this pass is used to deal with primary damage of intersection regions

5

and any new intersection regions generated)

FOR i = 0 TO number of regions in RG1 DO

FOR j = 0 TO number of regions in RG2 DO

IF rg1i→clab has PRIMARY damage OR rg2j→clab has PRIMARY

10 DAMAGE THEN

inter_rgn = rg1i→rgn intersection rg2j→rgn

IF inter_rgn is non-empty THEN

comp_clab = SEARCH for an existing contents label which
represents (rg1i→clab comp rg2j→clab).

15

IF a region tagged with comp_clab already exists in RG

THEN

IF rg1i→clab is OPAQUE THEN

new_p = rg1i→proxy

ELSE

20

create new proxy new_p initialised to OVER of
rg1i→proxy and rg2j→proxy inside inter_rgn.

END IF

MODIFY the existing region to have inter_rgn as its
region description and new_p as its proxy.

```

ELSE
    new_clab = create_binary_contents_label(rg1i→clab,
rg2j→clab).

    IF rg1i→clab is OPAQUE THEN
5        new_p = rg1i→proxy
    ELSE
        create new proxy new_p initialised to OVER of
rg1i→proxy and rg2j→proxy inside inter_rgn.
    END IF
10    damage_contents_label(new_clab)
    ADD to RG a new region with inter_rgn as its region
description, new_p as its proxy and new_clab as its contents label. (+)
    END IF
    FLAG the region as being 'RETAIN AFTER UPDATE'
15    END IF
    END IF
    END DO
    END DO

20 (Second Pass - this pass is used to deal with primary and secondary damage of
difference regions and secondary damage of intersection regions)
FOR i = 0 TO number of regions in RG1 DO
    IF rg1i→clab has PRIMARY or SECONDARY damage THEN
        diff_rgn = rg1i→rgn difference RG2→urn
25    IF diff_rgn is non-empty THEN
        IF a region tagged with rg1i→clab already exists in RG THEN
            MODIFY it to have diff_rgn as its region description and
rg1i→proxy as its proxy.
        ELSE
30            ADD to RG a new region with diff_rgn as its region descrip-
tion, rg1i→proxy as its proxy and rg1i→clab as its contents label. (*)
        END IF
        FLAG the region as being 'RETAIN AFTER UPDATE'
    END IF
35    END IF
END IF
```

```
FOR j = 0 TO number of regions in RG2 DO
    comp_clab = SEARCH for an existing contents label which represents
    (rg1i→clab comp rg2j→clab).
    IF comp_clab exists AND comp_clab has SECONDARY damage but
5    NO PRIMARY damage THEN
        inter_rgn = rg1i→rgn intersection rg2j→rgn
        IF inter_rgn is non-empty THEN
            GET a reference to the existing region tagged in this region
            group with comp_clab which MUST exist in this region group
10            IF rg1i→clab is OPAQUE THEN
                existing regions proxy = rg1i→proxy
            ELSE
                update_rgn = inter_rgn difference the region's previous
                region description.
15                update existing regions proxy to include OVER of
                rg1i→proxy and rg2j→proxy inside update region.
                END IF
                MODIFY the existing region to have inter_rgn as its region
                description and new_p as its proxy.
20                FLAG the region as being 'RETAIN AFTER UPDATE'
            END IF
        END IF
    END DO
END DO
25
FOR j= 0 TO number of regions in RG2 DO
    IF rg2j→clab has PRIMARY or SECONDARY damage THEN
        diff_rgn = rg2j→rgn difference RG1→urgn
        IF diff_rgn is non-empty THEN
30            IF a region tagged with rg2j→clab already exists in RG THEN
                MODIFY it to have diff_rgn as its region description and
                rg2j→proxy as its proxy.
            ELSE
                ADD to RG a new region with diff_rgn as its region
35    description,                rg2j→proxy as its proxy and rg2j→clab as its contents
```

label. (*)

END IF

FLAG the region as being 'RETAIN AFTER UPDATE'

END IF

5 END IF

END DO

DELETE all regions of RG which are not marked RETAIN AFTER UPDATE but whose contents labels have damage, and CLEAR flag in retained regions.

10

4.0 Tree Modifications (Linking and Unlinking)

More complex changes to a compositing tree can be achieved by changing the tree's structure. Most typical tree structure changes can be made by using two low level operations, link and unlink.

15 The unlink operation is used to separate a child node from its parent. After the operation is completed, the child node has no parent (meaning the child node can be linked in somewhere else), and the parent has a link available (meaning that some other node can be linked there instead). Nodes in the compositing tree above the unlinked child contain content which is dependent on the unlinked child. Therefore, at the time of the

20 next update, the contents label present in the unlinked child at the time of unlinking must be damaged to ensure that the dependent region groups higher in the tree are appropriately updated. The updating is achieved by the parent node caching away those contents labels existing in its unlinked child. If another subtree is linked in its place and subsequently unlinked without the region group of the parent being updated, it is not

25 necessary to cache the contents labels of this new subtree. Pseudocode for the unlink operation is provided below. Note that the UNLINKED_LEFT or UNLINKED_RIGHT flag is set so that the contents labels of a newly linked subtree may be damaged when region groups (including their proxies) higher in the tree must then be updated.

unlink

30 (

 node : compositing tree node

)

BEGIN

 parent = node →parent.

35 node →parent = NULL.

```
IF node is parent's left child THEN
    parent →left = NULL.
    IF parent doesn't have UNLINKED_LEFT set THEN
        SET the UNLINKED_LEFT flag in parent.
5      ELSE.
        RETURN.
    END IF
ELSE IF node is parent's right child THEN
    parent →right = NULL.
10     IF parent doesn't have UNLINKED_RIGHT set THEN
        SET the UNLINKED_RIGHT flat in parent.
    ELSE
        RETURN
    END IF
15  END IF
    COPY all the contents labels in node's region group into an array stored in
    parent →unlinked_clabs.
    END unlink
    The link operation involves linking a node with no parent to a free link of a parent node.
20  Pseudocode for the operation is provided below.
    link
    (
        child : compositing tree node,
        parent : compositing tree node,
25    which_link : either LEFT or RIGHT
    )
    BEGIN
        child →parent = parent
        IF which_link is LEFT THEN
30          parent →left = child.
        ELSE
            parent → right = child.
        END IF
    END LINK
35  4.1    Updating the Entire Compositing Tree
```


If a leaf node in the compositing tree changes, the region group of every node in a direct line from the leaf node to the root of tree must be updated using the methods described above. Fig. 15 shows circled those nodes which need to have their region groups updated if leaf nodes B and H change in some way.

5

Pseudocode for the tree updating method is provided below:

update_tree

(

node : compositing tree node

10

)

BEGIN

IF node is leaf node THEN

Rerender the leaf node and update its region group.

ELSE

15

IF unlinking occurred in left subtree or left subtree contains dirty leaf nodes THEN

update_tree(node →left).

END IF.

20

IF unlinking occurred in right subtree or right subtree contains dirty leaf nodes THEN

update_tree(node →right).

END IF.

IF node has UNLINKED_LEFT or UNLINKED_RIGHT flags set THEN

CALL damage_contents_label on every element of

25

node→unlinked_clabs.

IF node has UNLINKED_LEFT set THEN

CALL damage_contents_label on every contents label existing in node→left's region group.

CLEAR the UNLINKED_LEFT flag in node.

30

END IF

IF node has UNLINKED_RIGHT set THEN

CALL damage_contents_label on every contents label existing in node→right's region group.

CLEAR the UNLINKED_RIGHT flag in node.

35

END IF

END IF

CALL the region group update routine appropriate for node's composit-
ing operator.

END IF

5 END update_tree

10 The embodiments of the invention can be implemented using a conventional gen-
eral-purpose computer system 2100, such as that shown in Fig. 19, wherein the process
described with reference to Fig. 1 to Fig. 18 are implemented as software recorded on a
computer readable medium that can be loaded into and carried out by the computer. The
computer system 2100 includes a computer module 2101, input devices 2102, 2103 and a
display device 2104.

15 With reference to Fig 19, the computer module 2101 includes at least one processor
unit 2105, a memory unit 2106 which typically includes random access memory (RAM)
and read only memory (ROM), input/output (I/O) interfaces including a video interface
2107, keyboard 2118 and mouse 2120 interface 2108 and an I/O interface 2110. The
storage device 2109 can include one or more of the following devices: a floppy disk, a
hard disk drive, a CD-ROM drive or similar a non-volatile storage device known to those
skilled in the art. The components 2105 to 2110 of the computer module 2101, typically
20 communicate via an interconnected bus 2114 and in a manner which results in a usual
mode of operation of the computer system 2100 known to those in the relevant art.
Examples of computer systems on which the embodiments can be practised include IBM-
PC/ ATs and compatibles, Sun Sparcstations or alike computer system. In particular, the
pseudocode described herein can be programmed into any appropriate language and
25 stored for example on the HDD and executed in the RAM 2106 under control of the
processor 2105 with the results being stored in RAM within the video interface 2107 and
reproduced on the display 2116. The programs may be supplied to the system 2100 on a
pre-programmed floppy disk or CD-ROM or accessed via a connection with a computer
network, such as the Internet.

30 The aforementioned preferred method(s) comprise a particular control flow. There
are many other variants of the preferred method(s) which use different control flows
without departing the spirit or scope of the invention. Furthermore one or more of the
steps of the preferred method(s) may be performed in parallel rather sequential.

35 The foregoing describes only several embodiments of the present invention, and
modifications, obvious to those skilled in the art, can be made thereto without departing

from the scope of the present invention.

In the context of this specification, the word "comprising" means "including principally but not necessarily solely" or "having" or "including" and not "consisting only of". Variations of the word comprising, such as "comprise" and "comprises" have
5 corresponding meanings.



```
/*
 * region.cpp
 *
 * The implementation of the region manipulation functionality in
 * the Screen OpenPage prototype.
 */

#include "protos.h"

static int union_tot = 0;
static int int_tot = 0;
static int diff_tot = 0;
static int union_full = 0;
static int int_full = 0;
static int diff_full = 0;

/*
 * Some #defs which are used to control the optimisations used in the region
 * builder implementation..
 */
#define R_USE_NEW_IMP
#define RB_FAST_SHIFT_AND_DUP_LOOPS
#define RB_USE_LOOKUP
#define R_NEW_IMP_CONSTRUCTION_LOOP

/*
 * The global variables used to store the temporary results needed during
 * region manipulation operations. Two statically allocated
 * R_RegionBuilder structures are used. This is to allow data to be
 * read from one of them whilst the data required for the next operation
 * is written into the other one. Two pointers r_PrevRB and R_CurRB are
 * used to swap access to the two static structures. The
 * r_grow_region_builder function is called to grow a R_RegionBuilder
 * structure if required.
 */
static R_RegionBuilder r_RB1 = {0, 0, NULL, NULL};
static R_RegionBuilder r_RB2 = {0, 0, NULL, NULL};
static R_RegionBuilder *r_PrevRB = &r_RB1;
R_RegionBuilder *R_CurRB = &r_RB2;

/*
 * r_shift_and_dup
 *
 * A 16-byte lookup table which when provided with an unsigned char
 * of the following form xxyy, simply produces xxxx. This lookup table
 * _assumes_ that R_STATE_SIZE is 2. It _won't_ work (and will die
 * horribly) if this isn't the case.
 */
unsigned char r_shift_and_dup[16] = {
    0x00, 0x00, 0x00, 0x00,
    0x05, 0x05, 0x05, 0x05,
    0x0A, 0x0A, 0x0A, 0x0A,
    0x0F, 0x0F, 0x0F, 0x0F
};

/*
 * A buffer is required to store the new region data whilst a region is
 * being constructed. This buffer is expanded when required.
 */
static R_Int *r_RgnBuf = NULL;
static int r_RgnBufSize = 0;

/*
 * A buffer of IntXYMinMax structures is required to store the rectangles
 * generated during R_rects_from_region. This buffer is expanded when
 * required.
 */
static IntXYMinMax *r_RectBuf = NULL;
```

```
static int          r_RectBufSize = 0;

/*
 * R_FREE_LIST_GROWTH_SIZE
 *
 * This macro defines the number of elements which will be added to
 * free list whenever it is grown.
 */
#define R_FREE_LIST_GROWTH_SIZE      100

/*
 * r_free_list
 *
 * A linked list of unused R_RgnGrowItems which may be used during
 * region construction.
 */
R_RgnGrowItem  *r_free_list = NULL;

/*
 * r_growth_list
 *
 * A linked list of R_RgnGrowItems which represents the current
 * state during region construction.
 */
R_RgnGrowItem  *r_growth_list = NULL;

/*
 * r_grow_region_builder
 *
 * This function simply checks to see if a R_RegionBuilder structure
 * is of the required size. If it isn't the size of both
 * arrays in the R_RegionBuilder structure are doubled.
 *
 * Parameters:
 *   rb      The region builder to be grown.
 *   size    The required size of the arrays in the R_RegionBuilder.
 * Returns:
 *   TRUE on success, FALSE on failure.
 */
static int
r_grow_region_builder
(
    R_RegionBuilder  *rb,
    R_Int            size
)
{
    unsigned char    *new_state_data;
    R_Int            *new_rgn_data;
    int              new_size;

    new_size = max(size, rb->rrb_Size * 2);
    new_state_data = (unsigned char *)malloc(new_size * sizeof(unsigned char));
    if (new_state_data == NULL)
        new_rgn_data = (R_Int *)malloc(new_size * sizeof(R_Int));
    if (new_rgn_data == NULL)
    {
        free(new_state_data);
        return FALSE;
    }
    if (rb->rrb_StateData != NULL)
    {
        memcpy
        (
            new_state_data,
            rb->rrb_StateData,
            rb->rrb_Size * sizeof(unsigned char)
        );
        free(rb->rrb_StateData);
    }
}
```

```
    }
    if (rb->rrb_RgnData != NULL)
    {
        memcpy
        (
            new_rgn_data,
            rb->rrb_RgnData,
            rb->rrb_Size * sizeof(R_Int)
        );
        free(rb->rrb_RgnData);
    }
    rb->rrb_StateData = new_state_data;
    rb->rrb_RgnData = new_rgn_data;
    rb->rrb_Size = new_size;
    return TRUE;
}

/*
 * r_swap_region_builders
 *
 * This function simply swaps the static pointers to the r_RB1 and r_RB2
 * region builders.
 *
 * Parameters:
 *     None.
 * Returns:
 *     Nothing.
 */
inline static void
r_swap_region_builders()
{
    R_RegionBuilder *tmp;
    tmp = R_CurRB;
    R_CurRB = r_PrevRB;
    r_PrevRB = tmp;
}

/*
 * R_add_row_to_region_builder
 *
 * This function adds a row from a R_Region to a R_RegionBuilder structure.
 * The region from which the row comes is passed as an argument. "Adding"
 * has the following conditions: the row does not exist in the region builder
 * it is added and it's current state is tagged with the region
 * to which the row belongs. The previous state is set to 0,
 * indicating that it did not exist before.
 *
 * * If a pixel run in the row did exist before, but it's present state
 * indicates that it came from the other region then the run
 * is retained but it's state is modified to indicate that
 * both regions are active at this point.
 *
 * * If a pixel run in the row did exist before, and it's present
 * state indicates that the current region then the region is
 * removed and it's state is modified to indicate that the run is
 * now empty.
 *
 * * If a pixel run in the row did exist before, and it's present state
 * indicates that both regions are currently active then the run
 * is retained, but its state is modified to indicate that only the
 * other region is active in this run.
 *
 * Parameters:
 *     row_ptr    A R_Int ** pointer to the row in the region. Used
 *                to return the updates row pointer.
 *     rgn_mask    A mask for the region the row comes from. Must
 *                be either 1 or 2.
 *     first       Whether this is the first region to be processed
 *                on the current scanline.
 * Returns:
```

```

*      TRUE on success, FALSE on failure.
*/
#if 1
int
R_add_row_to_region_builder
(
    R_Int      **row_ptr,
    int        rgn_mask,
    int        first
)
{
    R_Int      *row;
    int        src_index;
    int        dest_index;
    R_Int      rb_run_start;
    unsigned char rb_prev_run_state;
    int        row_on;

    ASSERT(rgn_mask == 1 || rgn_mask == 2);

    row = *row_ptr;
    r_swap_region_builders();
    /*
     * Skip over the row's y value at the beginning.
     */
    ASSERT(*row == R_NEXT_IS_Y);
    row += 2;
    ASSERT(*row != R_NEXT_IS_Y && *row != R_EOR);

    if (r_PrevRB->rrb_Nels == 0)
    {
        /*
         * If the current region builder's src region data array is empty, then
         * we are dealing with an empty region builder. We simply convert
         * the input row to the region builder format.
         */
        row_on = TRUE;
        while (dest_index < R_CurRB->rrb_Size)
        while (dest_index < R_CurRB->rrb_Size)
        {
            if (++dest_index > R_CurRB->rrb_Size)
            {
                if (!r_grow_region_builder(R_CurRB, dest_index))
                    return FALSE;
            }
            R_CurRB->rrb_RgnData[dest_index - 1] = *row;
            if (row_on)
                R_CurRB->rrb_StateData[dest_index - 1] =
                    (rgn_mask << RB_STATE_SIZE);
            else
                R_CurRB->rrb_StateData[dest_index - 1] = 0;
            row_on = !row_on;
            row++;
        }
        *row_ptr = row;
        R_CurRB->rrb_Nels = dest_index;
        return TRUE;
    }
    /*
     * Firstly, we copy any runs from the region builder which
     * precede this run from the region. We are checking the
     * starting row against the start of each pixel run. Therefore
     * we start checking against the 1st region builder data
     * element.
     */
    ASSERT(r_PrevRB->rrb_Nels >= 2);
    src_index = 0;
    while (src_index < r_PrevRB->rrb_Nels && *row > r_PrevRB->rrb_RgnData[src_index])

```

```
        src_index++;
dest_index = src_index;
if (src_index > 0)
{
    if (src_index > R_CurRB->rrb_Size)
    {
        if (!r_grow_region_builder(R_CurRB, src_index))
            return FALSE;
    }
    memcpy
    (
        R_CurRB->rrb_RgnData,
        r_PrevRB->rrb_RgnData,
        src_index * sizeof(R_Int)
    );
    if (!first)
    {
        memcpy
        (
            R_CurRB->rrb_StateData,
            r_PrevRB->rrb_StateData,
            src_index * sizeof(unsigned char)
        );
    }
    else
    {
        int            i = 0;
        unsigned char  *src;
        unsigned char  *dest;

        src = r_PrevRB->rrb_StateData + src_index;
        dest = R_CurRB->rrb_StateData + src_index;
        switch (src_index)
        {
            default:
                for (i = src_index; i > 10; i--)
                {
#ifndef RB_USE_LOOKUP
                    *(dest - i) = (*(src - i) & RB_CUR_STATE_MASK) |
                                   (*(src - i) >> RB_STATE_SIZE);
#else
                    *(dest - i) = r_shift_and_dup(*(src - i));
#endif
                }
                /* FALLTHROUGH!! */
                case 10:
#ifndef RB_USE_LOOKUP
                    *(dest - 10) = (*(src - 10) & RB_CUR_STATE_MASK) |
                                   (*(src - 10) >> RB_STATE_SIZE);
#else
                    *(dest - 10) = r_shift_and_dup(*(src - 10));
#endif
                case 9: /* FALLTHROUGH!! */
#ifndef RB_USE_LOOKUP
                    *(dest - 9) = (*(src - 9) & RB_CUR_STATE_MASK) |
                                   (*(src - 9) >> RB_STATE_SIZE);
#else
                    *(dest - 9) = r_shift_and_dup(*(src - 9));
#endif
                /* FALLTHROUGH!! */
                case 8:
#ifndef RB_USE_LOOKUP
                    *(dest - 8) = (*(src - 8) & RB_CUR_STATE_MASK) |
                                   (*(src - 8) >> RB_STATE_SIZE);
#else
                    *(dest - 8) = r_shift_and_dup(*(src - 8));
#endif
                }
    }
}
```



```
/* FALLTHROUGH!! */
case 7:
#ifdef RB_USE_LOOKUP
    *(dest - 7) = (*(src - 7) & RB_CUR_STATE_MASK) |
                  (*(src - 7) >> RB_STATE_SIZE);
#else
    *(dest - 7) = r_shift_and_dup[*(src - 7)];
#endif
/* FALLTHROUGH!! */
case 6:
#ifdef R_USE_LOOKUP
    *(dest - 6) = (*(src - 6) & RB_CUR_STATE_MASK) |
                  (*(src - 6) >> RB_STATE_SIZE);
#else
    *(dest - 6) = r_shift_and_dup[*(src - 6)];
#endif
/* FALLTHROUGH!! */
case 5:
#ifdef RB_USE_LOOKUP
    *(dest - 5) = (*(src - 5) & RB_CUR_STATE_MASK) |
                  (*(src - 5) >> RB_STATE_SIZE);
#else
    *(dest - 5) = r_shift_and_dup[*(src - 5)];
#endif
/* FALLTHROUGH!! */
case 4:
#ifdef RB_USE_LOOKUP
    *(dest - 4) = (*(src - 4) & RB_CUR_STATE_MASK) |
                  (*(src - 4) >> RB_STATE_SIZE);
#else
    *(dest - 4) = r_shift_and_dup[*(src - 4)];
#endif
/* FALLTHROUGH!! */
case 3:
#ifdef RB_USE_LOOKUP
    *(dest - 3) = (*(src - 3) & RB_CUR_STATE_MASK) |
                  (*(src - 3) >> RB_STATE_SIZE);
#else
    *(dest - 3) = r_shift_and_dup[*(src - 3)];
#endif
/* FALLTHROUGH!! */
case 2:
#ifdef RB_USE_LOOKUP
    *(dest - 2) = (*(src - 2) & RB_CUR_STATE_MASK) |
                  (*(src - 2) >> RB_STATE_SIZE);
#else
    *(dest - 2) = r_shift_and_dup[*(src - 2)];
#endif
/* FALLTHROUGH!! */
case 1:
#ifdef RB_USE_LOOKUP
    *(dest - 1) = (*(src - 1) & RB_CUR_STATE_MASK) |
                  (*(src - 1) >> RB_STATE_SIZE);
#else
    *(dest - 1) = r_shift_and_dup[*(src - 1)];
#endif
/* FALLTHROUGH!! */
case 0:
    ;
/* FALLTHROUGH!! */
}
}
if (src_index == r_PrevRB->rrb_Nels)
{
    /*
     * We've already exhausted the previous region builder. Set the start
     * of the next pixel run to be the max. possible and set the state

```

```

    * to be 0.
    */
    rb_run_start = R_INT_MAX_VALUE - 2;
    rb_prev_run_state = 0;
}
else
{
    /*
    * We are still within the previous region builder bounds. Set up
    * the run info appropriately.
    */
    rb_run_start = r_PrevRB->rrb_RgnData[src_index];
    if (src_index == 0)
        rb_prev_run_state = 0;
    else
        rb_prev_run_state = r_PrevRB->rrb_StateData[src_index - 1];
}

/*
* We can now start dealing with the elements in the row.
*/
row_on = 1;
while (R_NOT_END_OF_ROW(*row))
{
    if (*row < rb_run_start)
    {
        if (dest_index + 1 > R_CurRB->rrb_Size)
        {
            if (!r_grow_region_builder(R_CurRB, dest_index + 1))
                return FALSE;
        }
        R_CurRB->rrb_RgnData[dest_index] = *row;
        if (first)
        {
            /*
            * We are processing the first region. Therefore, we
            * copy the current state of the run to the lowest
            * RB_STATE_SIZE bits.
            */
            R_CurRB->rrb_StateData[dest_index] =
                (rb_prev_run_state & RB_CUR_STATE_MASK) |
                (rb_prev_run_state >> RB_STATE_SIZE);
        }
        else
        {
            /*
            * We are processing the second region. Therefore, the state data
            * has already been copied to the previous state area so we
            * just copy the state.
            */
            R_CurRB->rrb_StateData[dest_index] = rb_prev_run_state;
        }
    }
    /*
    * Now, if the row for the current region is active at this transition,
    * we xor the region mask with the current contents of the new region
    * builder slot. This gives the desired behaviour of making that region
    * active if it is not there already, but turns it off if it is...
    */
    if (row_on)
        R_CurRB->rrb_StateData[dest_index] ^= (rgn_mask << RB_STATE_SIZE);
    dest_index++;
    /*
    * We now move onto the next row element.
    */
    row++;
    row_on = !row_on;
    continue;
}
}
```

```
/*
 * If the current row transition point is equal in x position to the current
 * previous region builder transition point, we advance the row counter to
 * the next position.
 */
if (*row == rb_run_start)
{
    row++;
    row_on = !row_on;
}
/*
 * Output the previous regions builder's transition region. We do similiar
 * things as for the region transition stuff above.. Firstly though, we
 * advance the rb_prev_run_state variable to the next element. We know
 * we can do this because if we were on the last element, we wouldn't
 * have hit this section of code.
 */
rb_prev_run_state = r_PrevRB->rrb_StateData[src_index];
if (dest_index + 1 > R_CurRB->rrb_Size)
{
    if (!r_grow_region_builder(R_CurRB, dest_index + 1))
        return FALSE;
}
R_CurRB->rrb_RgnData[dest_index] = rb_run_start;
if (first)
{
    R_CurRB->rrb_StateData[dest_index] = (rb_prev_run_state &
                                         RB_CUR_STATE_MASK) |
                                         rb_prev_run_state >> RB_STATE_SIZE;
}
else
{
    R_CurRB->rrb_StateData[dest_index] = rb_prev_run_state;
}
if (!row_on)
    R_CurRB->rrb_StateData[dest_index] ^= (rgn_mask << RB_STATE_SIZE);
dest_index++;
/*
 * We've output the previous region builder's transitions. We now move
 * over onto the next transition. If the previous src_index increment
 * has moved us onto the last element, we declare that we have run
 * out of previous region builder data.
 */
ASSERT(rb_run_start != R_EOR);
if (++src_index >= r_PrevRB->rrb_Nels)
{
    /*
     * We've run out of data..
     */
    rb_run_start = R_INT_MAX_VALUE - 2;
    continue;
}
/*
 * Otherwise, we still have stuff left to do, so we move onto
 * the next run in the previous region builder.
 */
rb_run_start = r_PrevRB->rrb_RgnData[src_index];
}
/*
 * Now, we simply blast out any remaining region builder transition
 * points.
 */
if (r_PrevRB->rrb_Nels - src_index > 0)
{
    R_Intnels_to_copy;
    nels_to_copy = r_PrevRB->rrb_Nels - src_index;
    if (dest_index + nels_to_copy > R_CurRB->rrb_Size)
    {
```

```
        if (!r_grow_region_builder(R_CurRB, dest_index + nels_to_copy))
            return FALSE;
    }

    memcpy
    (
        R_CurRB->rrb_RgnData + dest_index,
        r_PrevRB->rrb_RgnData + src_index,
        nels_to_copy * sizeof(R_Int)
    );
    if (!first)
    {
        memcpy
        (
            R_CurRB->rrb_StateData + dest_index,
            r_PrevRB->rrb_StateData + src_index,
            nels_to_copy * sizeof(unsigned char)
        );
        dest_index += nels_to_copy;
    }
    else
    {
        int            i = 0;
        unsigned char  *src;
        unsigned char  *dest;

        i = r_PrevRB->rrb_Nels - src_index;
        src = r_PrevRB->rrb_StateData + r_PrevRB->rrb_Nels;
        dest_index += i;
        dest = R_CurRB->rrb_StateData + dest_index;
        switch (i)
        {
            default:
                for (; i > 10; i--)
                {
                    #ifndef RB_USE_LOOKUP
                        *(dest - i) = (*(src - i) & RB_CUR_STATE_MASK) |
                                      (*(src - i) >> RB_STATE_SIZE);
                    #else
                        *(dest - i) = r_shift_and_dup(*(src - i));
                    #endif
                }
                case 10: FALLTHROUGH!! */
            #ifndef RB_USE_LOOKUP
                *(dest - 10) = (*(src - 10) & RB_CUR_STATE_MASK) |
                              (*(src - 10) >> RB_STATE_SIZE);
            #else
                *(dest - 10) = r_shift_and_dup(*(src - 10));
            #endif
                /* FALLTHROUGH!! */
            case 9:
            #ifndef RB_USE_LOOKUP
                *(dest - 9) = (*(src - 9) & RB_CUR_STATE_MASK) |
                             (*(src - 9) >> RB_STATE_SIZE);
            #else
                *(dest - 9) = r_shift_and_dup(*(src - 9));
            #endif
                /* FALLTHROUGH!! */
            case 8:
            #ifndef RB_USE_LOOKUP
                *(dest - 8) = (*(src - 8) & RB_CUR_STATE_MASK) |
                             (*(src - 8) >> RB_STATE_SIZE);
            #else
                *(dest - 8) = r_shift_and_dup(*(src - 8));
            #endif
                /* FALLTHROUGH!! */
            case 7:
```

```
#ifndef RB_USE_LOOKUP
    *(dest - 7) = (*(src - 7) & RB_CUR_STATE_MASK) |
                  (*(src - 7) >> RB_STATE_SIZE);
#else
    *(dest - 7) = r_shift_and_dup(*(src - 7));
#endif
    /* FALLTHROUGH!! */
case 6:
#ifndef RB_USE_LOOKUP
    *(dest - 6) = (*(src - 6) & RB_CUR_STATE_MASK) |
                  (*(src - 6) >> RB_STATE_SIZE);
#else
    *(dest - 6) = r_shift_and_dup(*(src - 6));
#endif
    /* FALLTHROUGH!! */
case 5:
#ifndef RB_USE_LOOKUP
    *(dest - 5) = (*(src - 5) & RB_CUR_STATE_MASK) |
                  (*(src - 5) >> RB_STATE_SIZE);
#else
    *(dest - 5) = r_shift_and_dup(*(src - 5));
#endif
    /* FALLTHROUGH!! */
case 4:
#ifndef RB_USE_LOOKUP
    *(dest - 4) = (*(src - 4) & RB_CUR_STATE_MASK) |
                  (*(src - 4) >> RB_STATE_SIZE);
#else
    *(dest - 4) = r_shift_and_dup(*(src - 4));
#endif
    /* FALLTHROUGH!! */
case 3:
#ifndef RB_USE_LOOKUP
    *(dest - 3) = (*(src - 3) & RB_CUR_STATE_MASK) |
                  (*(src - 3) >> RB_STATE_SIZE);
#else
    *(dest - 3) = r_shift_and_dup(*(src - 3));
#endif
    /* FALLTHROUGH!! */
case 2:
#ifndef RB_USE_LOOKUP
    *(dest - 2) = (*(src - 2) & RB_CUR_STATE_MASK) |
                  (*(src - 2) >> RB_STATE_SIZE);
#else
    *(dest - 2) = r_shift_and_dup(*(src - 2));
#endif
    /* FALLTHROUGH!! */
case 1:
#ifndef RB_USE_LOOKUP
    *(dest - 1) = (*(src - 1) & RB_CUR_STATE_MASK) |
                  (*(src - 1) >> RB_STATE_SIZE);
#else
    *(dest - 1) = r_shift_and_dup(*(src - 1));
#endif
    /* FALLTHROUGH!! */
case 0:
    ;
    /* FALLTHROUGH!! */
)
)
)
/*
 * Finally, we set the number of elements of the latest region
 * builder. We also return the updates row variable.
 */
R_CurRB->rrb_Nels = dest_index;
*row_ptr = row;
return TRUE;
```

```
}
#else
int
R_add_row_to_region_builder
(
    R_Int      **row_ptr,
    int        rgn_mask,
    int        first
)
{
    R_Int      *row;
    R_Int      rb_run_start;
    unsigned char rb_prev_run_state;
    int        row_on;

    int        dest_index;
    unsigned char *src_state_ptr;
    unsigned char *dest_state_ptr;
    unsigned char *src_state_end_ptr;
    register R_Int *src_rgn_ptr;
    R_Int      *src_rgn_end_ptr;
    register R_Int *dest_rgn_ptr;
    R_Int      *dest_rgn_end_ptr;
    int        inc;
    int        i;

    ASSERT(rgn_mask == 1 || rgn_mask == 2);

    row = *row_ptr;
    r_swap_region_builders();
    /*
     * Skip over the row's y value at the beginning.
     */
    ASSERT(*row == R_NEXT_IS_Y);
    row += 2;
    ASSERT(*row != R_NEXT_IS_Y && *row != R_EOR);

    if (r_PrevRB->rrb_Nels == 0)
    {
        /*
         * If the current region builder's src region data array is empty, then
         * we are dealing with an empty region builder. We simply convert
         * the input row to the region builder format.
         */
        row_on = TRUE;
        dest_index = 0;
        while (R_NOT_END_OF_ROW(*row))
        {
            if (++dest_index > R_CurRB->rrb_Size)
            {
                if (!r_grow_region_builder(R_CurRB, dest_index))
                    return FALSE;
            }
            R_CurRB->rrb_RgnData[dest_index - 1] = *row;
            if (row_on)
                R_CurRB->rrb_StateData[dest_index - 1] =
                    (rgn_mask << RB_STATE_SIZE);
            else
                R_CurRB->rrb_StateData[dest_index - 1] = 0;
            row_on = !row_on;
            row++;
        }
        *row_ptr = row;
        R_CurRB->rrb_Nels = dest_index;
        return TRUE;
    }
    /*
     * Firstly, we copy any runs from the region builder which

```

```
* precede this run from the region. We are checking the
* starting row against the start of each pixel run. Therefore
* we start checking against the 1st region builder data
* element.
*/
src_state_ptr = r_PrevRB->rrb_StateData;
src_rgn_ptr = r_PrevRB->rrb_RgnData;
src_state_end_ptr = src_state_ptr + r_PrevRB->rrb_Nels;
src_rgn_end_ptr = src_rgn_ptr + r_PrevRB->rrb_Nels;
dest_state_ptr = R_CurRB->rrb_StateData;
dest_rgn_ptr = R_CurRB->rrb_RgnData;
dest_rgn_end_ptr = dest_rgn_ptr + R_CurRB->rrb_Size;

ASSERT(r_PrevRB->rrb_Nels >= 2);
while (src_rgn_ptr != src_rgn_end_ptr && *row > *src_rgn_ptr)
    src_rgn_ptr++;
inc = src_rgn_ptr - r_PrevRB->rrb_RgnData;

if (inc > 0)
{
    src_state_ptr += inc;
    dest_state_ptr += inc;
    dest_rgn_ptr += inc;
    if (dest_rgn_ptr > dest_rgn_end_ptr)
    {
        if (!r_grow_region_builder(R_CurRB, inc))
            return FALSE;
        dest_state_ptr = R_CurRB->rrb_StateData;
        dest_rgn_ptr = R_CurRB->rrb_RgnData;
        dest_rgn_end_ptr = dest_rgn_ptr + R_CurRB->rrb_Size;
    }
}

#if 1
const R_Int      * const src_rgn_ptr2 = src_rgn_ptr;
R_Int            *dest_rgn_ptr2 = dest_rgn_ptr;
switch(inc)
{
    default:
        for (i = inc; i > 10; i--)
        {
            *(dest_rgn_ptr2 - i) = *(src_rgn_ptr2 - i);
        }
        /* FALLTHROUGH!! */
    case 10:
        *(dest_rgn_ptr2 - 10) = *(src_rgn_ptr2 - 10);
        /* FALLTHROUGH!! */
    case 9:
        *(dest_rgn_ptr2 - 9) = *(src_rgn_ptr2 - 9);
        /* FALLTHROUGH!! */
    case 8:
        *(dest_rgn_ptr2 - 8) = *(src_rgn_ptr2 - 8);
        /* FALLTHROUGH!! */
    case 7:
        *(dest_rgn_ptr2 - 7) = *(src_rgn_ptr2 - 7);
        /* FALLTHROUGH!! */
    case 6:
        *(dest_rgn_ptr2 - 6) = *(src_rgn_ptr2 - 6);
        /* FALLTHROUGH!! */
    case 5:
        *(dest_rgn_ptr2 - 5) = *(src_rgn_ptr2 - 5);
        /* FALLTHROUGH!! */
    case 4:
        *(dest_rgn_ptr2 - 4) = *(src_rgn_ptr2 - 4);
        /* FALLTHROUGH!! */
    case 3:
        *(dest_rgn_ptr2 - 3) = *(src_rgn_ptr2 - 3);
        /* FALLTHROUGH!! */
    case 2:
        *(dest_rgn_ptr2 - 2) = *(src_rgn_ptr2 - 2);
```

```
        /* FALLTHROUGH!! */
case 1:
    *(dest_rgn_ptr2 - 1) = *(src_rgn_ptr2 - 1);
    /* FALLTHROUGH!! */
case 0:
    ;
    /* FALLTHROUGH!! */
}
#else
memcpy
(
    R_CurRB->rrb_RgnData,
    r_PrevRB->rrb_RgnData,
    inc * sizeof(R_Int)
);
#endif
if (!first)
{
    memcpy
    (
        R_CurRB->rrb_StateData,
        r_PrevRB->rrb_StateData,
        inc * sizeof(unsigned char)
    );
}
else
{
    switch (inc)
    {
        default:
            for (i = inc; i > 10; i--)
            {
#ifdef RB_USE_LOOKUP
                *(dest_state_ptr - i) = (*(src_state_ptr - i) &
                    RB_CUR_STATE_MASK) |
                    (*(src_state_ptr - i) >>
                    RB_STATE_SIZE);
#else
                *(dest_state_ptr - i) = r_shift_and_dup[*(src_state_ptr - i)];
#endif
            }
            /* FALLTHROUGH!! */
case 10:
#ifdef RB_USE_LOOKUP
                *(dest_state_ptr - 10) = (*(src_state_ptr - 10) &
                    RB_CUR_STATE_MASK) |
                    (*(src_state_ptr - 10) >>
                    RB_STATE_SIZE);
#else
                *(dest_state_ptr - 10) = r_shift_and_dup[*(src_state_ptr - 10)];
#endif
            /* FALLTHROUGH!! */
case 9:
#ifdef RB_USE_LOOKUP
                *(dest_state_ptr - 9) = (*(src_state_ptr - 9) & RB_CUR_STATE_MASK) |
                    (*(src_state_ptr - 9) >> RB_STATE_SIZE);
#else
                *(dest_state_ptr - 9) = r_shift_and_dup[*(src_state_ptr - 9)];
#endif
            /* FALLTHROUGH!! */
case 8:
#ifdef RB_USE_LOOKUP
                *(dest_state_ptr - 8) = (*(src_state_ptr - 8) & RB_CUR_STATE_MASK) |
                    (*(src_state_ptr - 8) >> RB_STATE_SIZE);
#else
                *(dest_state_ptr - 8) = r_shift_and_dup[*(src_state_ptr - 8)];
#endif
            /* FALLTHROUGH!! */

```



```
        case 7:
#ifdef RB_USE_LOOKUP
            *(dest_state_ptr - 7) = (*(src_state_ptr - 7) & RB_CUR_STATE_MASK) |
                                    (*(src_state_ptr - 7) >> RB_STATE_SIZE);
#else
            *(dest_state_ptr - 7) = r_shift_and_dup(*(src_state_ptr - 7));
#endif
            /* FALLTHROUGH!! */
        case 6:
#ifdef R_USE_LOOKUP
            *(dest_state_ptr - 6) = (*(src_state_ptr - 6) & RB_CUR_STATE_MASK) |
                                    (*(src_state_ptr - 6) >> RB_STATE_SIZE);
#else
            *(dest_state_ptr - 6) = r_shift_and_dup(*(src_state_ptr - 6));
#endif
            /* FALLTHROUGH!! */
        case 5:
#ifdef RB_USE_LOOKUP
            *(dest_state_ptr - 5) = (*(src_state_ptr - 5) & RB_CUR_STATE_MASK) |
                                    (*(src_state_ptr - 5) >> RB_STATE_SIZE);
#else
            *(dest_state_ptr - 5) = r_shift_and_dup(*(src_state_ptr - 5));
#endif
            /* FALLTHROUGH!! */
        case 4:
#ifdef RB_USE_LOOKUP
            *(dest_state_ptr - 4) = (*(src_state_ptr - 4) & RB_CUR_STATE_MASK) |
                                    (*(src_state_ptr - 4) >> RB_STATE_SIZE);
#else
            *(dest_state_ptr - 4) = r_shift_and_dup(*(src_state_ptr - 4));
#endif
            /* FALLTHROUGH!! */
        case 3:
#ifdef RB_USE_LOOKUP
            *(dest_state_ptr - 3) = (*(src_state_ptr - 3) & RB_CUR_STATE_MASK) |
                                    (*(src_state_ptr - 3) >> RB_STATE_SIZE);
#else
            *(dest_state_ptr - 3) = r_shift_and_dup(*(src_state_ptr - 3));
#endif
            /* FALLTHROUGH!! */
        case 2:
#ifdef RB_USE_LOOKUP
            *(dest_state_ptr - 2) = (*(src_state_ptr - 2) & RB_CUR_STATE_MASK) |
                                    (*(src_state_ptr - 2) >> RB_STATE_SIZE);
#else
            *(dest_state_ptr - 2) = r_shift_and_dup(*(src_state_ptr - 2));
#endif
            /* FALLTHROUGH!! */
        case 1:
#ifdef RB_USE_LOOKUP
            *(dest_state_ptr - 1) = (*(src_state_ptr - 1) & RB_CUR_STATE_MASK) |
                                    (*(src_state_ptr - 1) >> RB_STATE_SIZE);
#else
            *(dest_state_ptr - 1) = r_shift_and_dup(*(src_state_ptr - 1));
#endif
            /* FALLTHROUGH!! */
        case 0:
            ;
            /* FALLTHROUGH!! */
    }
}

if (src_state_ptr == src_state_end_ptr)
{
    /*
     * We've already exhausted the previous region builder. Set the start
     * of the next pixel run to be the max. possible and set the state
     * to be 0.
    */
}
```

```
    */
    rb_run_start = R_INT_MAX_VALUE - 2;
    rb_prev_run_state = 0;
}
else
{
    /*
     * We are still within the previous region builder bounds. Set up
     * the run info appropriately.
     */
    rb_run_start = *src_rgn_ptr;
    if (src_state_ptr == r_PrevRB->rrb_StateData)
        rb_prev_run_state = 0;
    else rb_prev_run_state = *(src_state_ptr - 1);
}

/*
 * We can now start dealing with the elements in the row.
 */
row_on = 1;
while (R_NOT_END_OF_ROW(*row))
{
    if (*row < rb_run_start)
    {
        if (dest_rgn_ptr + 1 > dest_rgn_end_ptr)
        {
            if (!r_grow_region_builder(R_CurRB, dest_rgn_ptr - R_CurRB->rrb_RgnData + 1)) return FALSE;
            dest_state_ptr = R_CurRB->rrb_StateData;
            dest_rgn_ptr = R_CurRB->rrb_RgnData;
            dest_rgn_end_ptr = dest_rgn_ptr + R_CurRB->rrb_Size;
        }
        *dest_rgn_ptr = *row;
        if (first)
        {
            /*
             * We are processing the first region. Therefore, we
             * copy the current state of the run to the lowest
             * RB_STATE_SIZE bits.
             */
            *dest_state_ptr = (rb_prev_run_state & RB_CUR_STATE_MASK) |
                             (rb_prev_run_state >> RB_STATE_SIZE);
        }
        else
        {
            /*
             * We are processing the second region. Therefore, the state data
             * has already been copied to the previous state area so we
             * just copy the state.
             */
            *dest_state_ptr = rb_prev_run_state;
        }
        /*
         * Now, if the row for the current region is active at this transition,
         * we xor the region mask with the current contents of the new region
         * builder slot. This gives the desired behaviour of making that region
         * active if it is not there already, but turns it off if it is...
         */
        if (row_on)
            *dest_state_ptr ^= (rgn_mask << RB_STATE_SIZE);
        dest_state_ptr++;
        dest_rgn_ptr++;
        /*
         * We now move onto the next row element.
         */
        row++;
        row_on = !row_on;
    }
}
```

```
        continue;
    }
    /*
     * If the current row transition point is equal in x position to the current
     * previous region builder transition point, we advance the row counter to
     * the next position.
     */
    if (*row == rb_run_start)
    {
        row++;
        row_on = !row_on;
    }
    /*
     * Output the previous regions builder's transition region. We do similiar
     * things as for the region transition stuff above.. Firstly though, we
     * advance the rb_prev_run_state variable to the next element. We know
     * we can do this because if we were on the last element, we wouldn't
     * have hit this section of code.
     */
    rb_prev_run_state = *src_state_ptr;
    if (dest_rgn_ptr + 1 > dest_rgn_end_ptr)
    {
        if (!r_grow_region_builder(R_CurRB, dest_rgn_ptr - R_CurRB->rrb_RgnData
            + 1)) return FALSE;
        dest_state_ptr = R_CurRB->rrb_StateData;
        dest_rgn_ptr = R_CurRB->rrb_RgnData;
        dest_rgn_end_ptr = dest_rgn_ptr + R_CurRB->rrb_Size;
    }
    *dest_rgn_ptr = rb_run_start;
    if (first)
    {
        *dest_state_ptr = (rb_prev_run_state & RB_CUR_STATE_MASK) |
            (rb_prev_run_state >> RB_STATE_SIZE);
    }
    else
    {
        *dest_state_ptr = rb_prev_run_state;
    }
    if (!row_on)
        *dest_state_ptr ^= (rgn_mask << RB_STATE_SIZE);
    dest_state_ptr++;
    dest_rgn_ptr++;
    /* We've output the previous region builder's transitions. We now move
     * over onto the next transition. If the previous src_index increment
     * has moved us onto the last element, we declare that we have run
     * out of previous region builder data.
     */
    ASSERT(rb_run_start != R_EOR);
    ++src_rgn_ptr;
    if (++src_state_ptr == src_state_end_ptr)
    {
        /*
         * We've run out of data..
         */
        rb_run_start = R_INT_MAX_VALUE - 2;
        continue;
    }
    /*
     * Otherwise, we still have stuff left to do, so we move onto
     * the next run in the previous region builder.
     */
    rb_run_start = *src_rgn_ptr;
}
/*
 * Now, we simply blast out any remaining region builder transition
 * points.
 */
```

```
if (src_state_ptr != src_state_end_ptr)
{
    R_Int nels_to_copy;
    nels_to_copy = src_state_end_ptr - src_state_ptr;
    if (dest_rgn_ptr + nels_to_copy > dest_rgn_end_ptr)
    {
        if
        (
            !r_grow_region_builder
            (
                R_CurRB,
                dest_rgn_ptr - R_CurRB->rrb_RgnData + nels_to_copy
            )
        )
            return FALSE;
        dest_state_ptr = R_CurRB->rrb_StateData;
        dest_rgn_ptr = R_CurRB->rrb_RgnData;
    }
    memcpy
    (
        dest_rgn_ptr,
        src_rgn_ptr,
        nels_to_copy * sizeof(R_Int)
    );
    dest_rgn_ptr += nels_to_copy;
    if (!first)
    {
        memcpy
        (
            dest_state_ptr,
            src_state_ptr,
            nels_to_copy * sizeof(unsigned char)
        );
    }
    else
    {
        r_reset_ptr = src_state_end_ptr;
        dest_state_ptr += nels_to_copy;
        switch (i)
        {
            default:
                for (; i > 10; i--)
                {
#ifndef RB_USE_LOOKUP
                    *(dest_state_ptr - i) = (*(src_state_ptr - i) & RB_CUR_STATE_MASK) |
                                            (*(src_state_ptr - i) >> RB_STATE_SIZE);
#else
                    *(dest_state_ptr - i) = r_shift_and_dup(*(src_state_ptr - i));
#endif
                }
                /* FALLTHROUGH!! */
                case 10:
#ifndef RB_USE_LOOKUP
                    *(dest_state_ptr - 10) = (*(src_state_ptr - 10) & RB_CUR_STATE_MASK) |
                                              (*(src_state_ptr - 10) >> RB_STATE_SIZE);
#else
                    *(dest_state_ptr - 10) = r_shift_and_dup(*(src_state_ptr - 10));
#endif
                /* FALLTHROUGH!! */
                case 9:
#ifndef RB_USE_LOOKUP
                    *(dest_state_ptr - 9) = (*(src_state_ptr - 9) & RB_CUR_STATE_MASK) |
                                             (*(src_state_ptr - 9) >> RB_STATE_SIZE);
#else
                    *(dest_state_ptr - 9) = r_shift_and_dup(*(src_state_ptr - 9));
#endif
                /* FALLTHROUGH!! */

```

```

        case 8:
#ifdef RB_USE_LOOKUP
        *(dest_state_ptr - 8) = (*(src_state_ptr - 8) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 8) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 8) = r_shift_and_dup(*(src_state_ptr - 8));
#endif
        /* FALLTHROUGH!! */
        case 7:
#ifdef RB_USE_LOOKUP
        *(dest_state_ptr - 7) = (*(src_state_ptr - 7) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 7) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 7) = r_shift_and_dup(*(src_state_ptr - 7));
#endif
        /* FALLTHROUGH!! */
        case 6:
#ifdef R_USE_LOOKUP
        *(dest_state_ptr - 6) = (*(src_state_ptr - 6) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 6) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 6) = r_shift_and_dup(*(src_state_ptr - 6));
#endif
        /* FALLTHROUGH!! */
        case 5:
#ifdef RB_USE_LOOKUP
        *(dest_state_ptr - 5) = (*(src_state_ptr - 5) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 5) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 5) = r_shift_and_dup(*(src_state_ptr - 5));
#endif
        /* FALLTHROUGH!! */
        case 4:
#ifdef RB_USE_LOOKUP
        *(dest_state_ptr - 4) = (*(src_state_ptr - 4) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 4) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 4) = r_shift_and_dup(*(src_state_ptr - 4));
#endif
        /* FALLTHROUGH!! */
        case 3:
#ifdef RB_USE_LOOKUP
        *(dest_state_ptr - 3) = (*(src_state_ptr - 3) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 3) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 3) = r_shift_and_dup(*(src_state_ptr - 3));
#endif
        /* FALLTHROUGH!! */
        case 2:
#ifdef RB_USE_LOOKUP
        *(dest_state_ptr - 2) = (*(src_state_ptr - 2) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 2) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 2) = r_shift_and_dup(*(src_state_ptr - 2));
#endif
        /* FALLTHROUGH!! */
        case 1:
#ifdef RB_USE_LOOKUP
        *(dest_state_ptr - 1) = (*(src_state_ptr - 1) & RB_CUR_STATE_MASK) |
                                (*(src_state_ptr - 1) >> RB_STATE_SIZE);
#else
        *(dest_state_ptr - 1) = r_shift_and_dup(*(src_state_ptr - 1));
#endif
        /* FALLTHROUGH!! */
        case 0:
        ;
        /* FALLTHROUGH!! */
    }
}
```

```
    }
}
/*
 * Finally, we set the number of elements of the latest region
 * builder. We also return the updates row variable.
 */
R_CurRB->rrb_Nels = dest_rgn_ptr - R_CurRB->rrb_RgnData;
*row_ptr = row;
return TRUE;
}
#endif

/*
 * r_check_rgn_buf_len
 *
 * This function checks to see if the static region buffer is large enough.
 * If it isn't then it is reallocated to make it large enough.
 *
 * Parameters:
 *     size The required size of the r_RegBuf array.
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
static int
r_check_rgn_buf_len
(
    int        size
)
{
    ASSERT(size >= 0);
    if (size > r_RgnBufSize)
    {
        int        new_buf_size;
        R_Int      *new_buf;
        new_buf_size = max(size, r_RgnBufSize * 2);
        new_buf = (R_Int *)malloc(new_buf_size * sizeof(R_Int));
        if (new_buf == NULL)
            if (r_RgnBuf != NULL)
            {
                memcpy(new_buf, r_RgnBuf, r_RgnBufSize * sizeof(R_Int));
                free(r_RgnBuf);
            }
        r_RgnBuf = new_buf;
        r_RgnBufSize = new_buf_size;
    }
    return TRUE;
}

/*
 * R_init_region_with_rect
 *
 * This function initialises a R_Region structure to represent a rectangular
 * region. It is assumed that the region is currently uninitialised.
 *
 * Parameters:
 *     rgn        A pointer to the R_Region to be initialised.
 *     rect       A pointer to an IntXYMinMax structure representing
 *               the rectangular area requiring an equivalent region
 *               description.
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
int
R_init_region_with_rect
(
    R_Region      *rgn,
    IntXYMinMax   *rect
)
```

```

    }
    {
        R_Int      *rgn_data;

        ASSERT(rect->X.Min <= rect->X.Max);
        ASSERT(rect->Y.Min <= rect->Y.Max);

        rgn->rr_BBox = *rect;
        rgn_data = (R_Int *)malloc(9 * sizeof(R_Int));
        if (rgn_data == NULL)
        {
            return FALSE;
        }
        rgn_data[0] = R_NEXT_IS_Y;
        rgn_data[1] = rect->Y.Min;
        rgn_data[2] = rect->X.Min;
        rgn_data[3] = rect->X.Max + 1;
        rgn_data[4] = R_NEXT_IS_Y;
        rgn_data[5] = rect->Y.Max + 1;
        rgn_data[6] = rect->X.Min;
        rgn_data[7] = rect->X.Max + 1;
        rgn_data[8] = R_EOR;
        rgn->rr_RgnData = rgn_data;
        rgn->rr_RgnDataSize = 9;
        return TRUE;
    }
}

/*
 * R_region_with_region
 *
 * This function initialises a R_Region structure to represent a the region
 * passed as an argument. It is assumed that the region is currently
 * uninitialised.
 *
 * Parameters:
 *     rgn      A pointer to the R_Region to be initialised.
 *     src_rgn  A pointer to an R_Region structure representing
 *              the region to which this region is to be initialised.
 *
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
int
R_init_region_with_region
(
    R_Region      *rgn,
    R_Region      *src_rgn
)
{
    R_Int      *rgn_data;

    rgn->rr_BBox = src_rgn->rr_BBox;
    rgn_data = (R_Int *)malloc(src_rgn->rr_RgnDataSize * sizeof(R_Int));
    if (rgn_data == NULL)
    {
        return FALSE;
    }
    memcpy
    (
        rgn_data,
        src_rgn->rr_RgnData,
        src_rgn->rr_RgnDataSize * sizeof(R_Int)
    );
    rgn->rr_RgnData = rgn_data;
    rgn->rr_RgnDataSize = src_rgn->rr_RgnDataSize;
    return TRUE;
}

/*
```

```
* R_region_with_translated_region
*
* This function initialises a R_Region structure to represent a the region
* passed as an argument translated by delta. It is assumed that the region
* is currently uninitialised.
*
* Parameters:
*     rgn        A pointer to the R_Region to be initialised.
*     src_rgn    A pointer to an R_Region structure representing
*               the region to which this region is to be initialised.
*     delta      A pointer to a IntXY structure representing the
*               translation required.
* Returns:
*     TRUE on success, FALSE on failure.
*/
int
R_init_region_with_translated_region
(
    R_Region    *rgn,
    R_Region    *src_rgn,
    IntXY       *delta
)
{
    R_Int        *rgn_data;
    R_Int        *src_data;

    rgn->rr_BBox.X.Min = src_rgn->rr_BBox.X.Min + delta->X;
    rgn->rr_BBox.X.Max = src_rgn->rr_BBox.X.Max + delta->X;
    rgn->rr_BBox.Y.Min = src_rgn->rr_BBox.Y.Min + delta->Y;
    rgn->rr_BBox.Y.Max = src_rgn->rr_BBox.Y.Max + delta->Y;
    rgn_data = (R_Int *)malloc(src_rgn->rr_RgnDataSize * sizeof(R_Int));
    if (rgn_data == NULL)
    {
        return FALSE;
    }
    src_data = src_rgn->rr_RgnData;
    for (int i = 0; i < src_rgn->rr_RgnDataSize; i++)
    {
        if (src_data[i] == R_NEXT_IS_Y)
        {
            rgn_data[i] = src_data[i];
            i++;
            rgn_data[i] = src_data[i] + delta->Y;
            continue;
        }
        else if (src_data[i] == R_EOR)
            rgn_data[i] = src_data[i];
        else
            rgn_data[i] = src_data[i] + delta->X;
    }
    rgn->rr_RgnData = rgn_data;
    rgn->rr_RgnDataSize = src_rgn->rr_RgnDataSize;
    return TRUE;
}

/*
* R_empty_region
*
* Deallocates the region data allocated for a region. Only the
* data is freed. The R_Region structure itself is not.
*
* Parameters:
*     rgn        The region whose region data is to be deallocated.
* Returns:
*     Nothing.
*/
void
```



```
R_empty_region
(
    R_Region *rgn
)
{
    if (rgn != NULL && rgn->rr_RgnData != NULL)
    {
        free(rgn->rr_RgnData);
        rgn->rr_RgnData = NULL;
    }
}

#ifdef R_USE_NEW_IMP
/*
 * R_union
 *
 * This function inits a R_Region structure to represent the union
 * of it's two arguments.
 *
 * Parameters:
 *     rgn    The R_Region to be initialised.
 *     r1     A R_Region ptr representing the first region.
 *     r2     A R_Region ptr representing the second region.
 *
 * Returns
 *     TRUE on success, FALSE on failure.
 */
int
R_union
(
    R_Region *rgn,
    R_Region *r1,
    R_Region *r2
)
{
    R_Int *r1_dat;
    R_Int *r2_dat;
    int overlap_flags;

    union_tot++;

    if (!BB_intersect_test(&r1->rr_BBox, &r2->rr_BBox, &overlap_flags))
    {
        /*
         * The bounding boxes don't intersect. This means we can do the
         * union very easily, simply by copying data from the two regions.
         * We malloc a new region data array of size r1->rr_RgnDataSize +
         * r2->rr_RgnDataSize - 1. This is the maximum possible size of
         * resulting region. Not all of this memory will be utilised if
         * the two regions being combined have rows with the same y coordinate
         * (R_NEXT_IS_Y marker is not duplicated).
         */
        rgn->rr_RgnDataSize = r1->rr_RgnDataSize + r2->rr_RgnDataSize - 1;
        rgn->rr_RgnData = (R_Int *)malloc(rgn->rr_RgnDataSize *
                                         sizeof(R_Int));

        if (rgn->rr_RgnData == NULL)
        {
            return FALSE;
        }
        /*
         * Now, check to see if the regions overlap in y...
         */
        if (!(overlap_flags & BB_INTERSECT_OVERLAP_Y))
        {
            /*
             * The regions don't overlap in y. We simply copy one region
             * and then another into the array we malloced. We ensure
             * that r1 points to the region with the smallest y coordinate.
             */
            if (r2->rr_BBox.Y.Min < r1->rr_BBox.Y.Min)
```

```
{
    R_Region *tmp;
    tmp = r1;
    r1 = r2;
    r2 = tmp;
}
memcpy
(
    rgn->rr_RgnData,
    r1->rr_RgnData,
    (r1->rr_RgnDataSize - 1) * sizeof(R_Int)
);
memcpy
(
    rgn->rr_RgnData + r1->rr_RgnDataSize - 1,
    r2->rr_RgnData,
    r2->rr_RgnDataSize * sizeof(R_Int)
);
ASSERT(rgn->rr_RgnData[rgn->rr_RgnDataSize - 1] == R_EOR);
}
else
(
    R_Int *r1_tmp;
    R_Int *r2_tmp;
    R_Int *dest;
    R_Int min_row;
    int r1_done;
    int r1_consumed;
    int r2_consumed;
    int num_written;
    /*
     * The bboxes overlap in y but not in x. We simply go row
     * by row through each region and memcpy the individual rows as
     * appropriate. We ensure that r1 points to the region with
     * the smallest x coordinate.
     */
    if (r2->rr_BBox.X.Min < r1->rr_BBox.X.Min)
    {
        R_Region *tmp;
        tmp = r1;
        r1 = r2;
        r2 = tmp;
    }
    r1_dat = r1->rr_RgnData;
    r2_dat = r2->rr_RgnData;
    dest = rgn->rr_RgnData;
    rgn->rr_RgnDataSize = 0;
    r1_consumed = 0;
    r2_consumed = 0;
    while (*r1_dat != R_EOR && *r2_dat != R_EOR)
    {
        ASSERT(*r1_dat == R_NEXT_IS_Y);
        ASSERT(*r2_dat == R_NEXT_IS_Y);
        min_row = min(r1_dat[1], r2_dat[1]);
        r1_done = FALSE;
        if (r1_dat[1] == min_row)
        {
            /*
             * We need to emit r1. We therefore need to find where
             * the next row (if any) starts. When we do this we
             * recall that a y value _must be followed by at least
             * two x values..
             */
            r1_tmp = r1_dat + 4;
            while (*r1_tmp != R_NEXT_IS_Y && *r1_tmp != R_EOR)
                r1_tmp++;
            num_written = r1_tmp - r1_dat;
            memcpy(dest, r1_dat, num_written * sizeof(R_Int));

```

```
dest += num_written;
r1_consumed += num_written;
rgn->rr_RgnDataSize += num_written;
r1_dat = r1_tmp;
r1_done = TRUE;
}
if (r2_dat[1] == min_row)
{
    /*
     * We need to emit r1. We therefore need to find where
     * the next row (if any) starts. When we do this we
     * recall that a y value _must_ be followed by at least
     * two x values. If r1's current row has already been
     * emitted for this y value, we do _not_ emit the
     * R_NEXT_IS_Y marker or the y value itself.
     */
    if (r1_done)
    {
        r2_dat += 2;
        r2_tmp = r2_dat + 2;
        r2_consumed += 2;
    }
    else
    {
        r2_tmp = r2_dat + 4;
    }
    while (*r2_tmp != R_NEXT_IS_Y && *r2_tmp != R_EOR)
        r2_tmp++;
    num_written = r2_tmp - r2_dat;
    memcpy(dest, r2_dat, num_written * sizeof(R_Int));
    dest += num_written;
    r2_consumed += num_written;
    rgn->rr_RgnDataSize += num_written;
    r2_dat = r2_tmp;
}
}
if (*r1_dat != R_EOR)
{
    /*
     * r1 is the last region left standing. We memcpy
     * the remainder of the region (including the
     * R_EOR marker) to the destination.
     */
    ASSERT(r2_consumed == r2->rr_RgnDataSize - 1);
    memcpy
    (
        dest,
        r1_dat,
        (r1->rr_RgnDataSize - r1_consumed) * sizeof(R_Int)
    );
    rgn->rr_RgnDataSize += (r1->rr_RgnDataSize - r1_consumed);
}
else
{
    /*
     * r2 is the last region left standing. We memcpy
     * the remainder of the region (including the
     * R_EOR marker) to the destination.
     */
    ASSERT(r1_consumed == r1->rr_RgnDataSize - 1);
    memcpy
    (
        dest,
        r2_dat,
        (r2->rr_RgnDataSize - r2_consumed) * sizeof(R_Int)
    );
    rgn->rr_RgnDataSize += (r2->rr_RgnDataSize - r2_consumed);
}
```

```

        ASSERT
        (
            rgn->rr_RgnData[rgn->rr_RgnDataSize - 1] == R_EOR
        );
    }
}
else
{
    R_Int          min_row;
    int             dest_size;
    unsigned char   *rgn_bld_stat;
    R_Int           *rgn_bld_dat;
    int             i;
    int             in_run;
    int             done_r1_in_row;

    union_full++;

    /*
     * The two regions do overlap in x_and y. We therefore have
     * regions built together as a single region the union of the two
     * regarding the currently active regions as we progress through
     * the rows of each region. After any rows relevant to a y-coord
     * are added to the region builder, we examine the state of each
     * pixel run in the region builder. If the addition of the row(s)
     * for the y-coord have caused a transition to or from 0, then
     * the pixel run is emitted. However, the first thing we do is
     * ensure the current region builder is empty.
     */
    r1_dat = r1->rr_RgnData;
    r2_dat = r2->rr_RgnData;
    R_CurRB->rrb_Nels = 0;
    dest_size = 0;
    /*
     * We are now ready to loop through the data of both regions.
     * We continue building the new region whilst there is data
     * remaining in either of the two regions.
     */
    while (*r1_dat != R_EOR || *r2_dat != R_EOR)
    {
        ASSERT(*r1_dat == R_NEXT_IS_Y || *r1_dat == R_EOR);
        ASSERT(*r2_dat == R_NEXT_IS_Y || *r2_dat == R_EOR);
        if (*r1_dat == R_EOR)
            min_row = r2_dat[1];
        else if (*r2_dat == R_EOR)
            min_row = r1_dat[1];
        else
            min_row = min(r1_dat[1], r2_dat[1]);
        done_r1_in_row = FALSE;
        if (*r1_dat != R_EOR && r1_dat[1] == min_row)
        {
            /*
             * The first region is active on this y coord. We add this
             * row to the current region builder.
             */
            if (!R_add_row_to_region_builder(&r1_dat, 0x1, TRUE))
                return FALSE;
            done_r1_in_row = TRUE;
        }
        if (*r2_dat != R_EOR && r2_dat[1] == min_row)
        {
            /*
             * The first region is active on this y coord. We add this
             * row to the current region builder.
             */
            if (!R_add_row_to_region_builder(&r2_dat, 0x2, !done_r1_in_row))

```

```
        return FALSE;
    }
    /*
     * Now, we generate the output row for the input rows.
     */
    if (!r_check_rgn_buf_len(dest_size + 2))
    {
        return FALSE;
    }
    r_RgnBuf[dest_size++] = R_NEXT_IS_Y;
    r_RgnBuf[dest_size++] = min_row;
    rgn_bld_stat = R_CurRB->rrb_StateData;
    rgn_bld_dat = R_CurRB->rrb_RgnData;
    in_run = FALSE;
    for (i = R_CurRB->rrb_Nels; i > 0; i--)
    {
        if
        (
            *rgn_bld_stat > 0
            &&
            (
                (*rgn_bld_stat & RB_CUR_STATE_MASK) == 0
                ||
                (*rgn_bld_stat & RB_PREV_STATE_MASK) == 0
            )
        )
        {
            /*
             * We have to emit a run here, if we're not already
             * in one..
             */
            if (!in_run)
            {
                if (!r_check_rgn_buf_len(dest_size + 1))
                {
                    return FALSE;
                }
                r_RgnBuf[dest_size++] = *rgn_bld_dat;
                in_run = TRUE;
            }
        }
        else
        {
            if (in_run)
            {
                /*
                 * We've come to the end of a run. We output the next
                 * element to end it.
                 */
                if (!r_check_rgn_buf_len(dest_size + 1))
                {
                    return FALSE;
                }
                r_RgnBuf[dest_size++] = *rgn_bld_dat;
            }
            in_run = FALSE;
        }
        rgn_bld_stat++;
        rgn_bld_dat++;
    }
    if (r_RgnBuf[dest_size - 2] == R_NEXT_IS_Y)
    {
        /*
         * We didn't output anything for these input rows. Rewind..
         */
        dest_size -= 2;
    }
}
```

```
/*
 * We've completed constructing the data for the region. We
 * make a copy the constructed data from the permanent buffer to
 * an exactly fitting buffer.
 */
rgn->rr_RgnData = (R_Int *)malloc(++dest_size * sizeof(R_Int));
if (rgn->rr_RgnData == NULL)
{
    return FALSE;
}
memcpy(rgn->rr_RgnData, r_RgnBuf, (dest_size - 1) * sizeof(R_Int));
rgn->rr_RgnData[dest_size - 1] = R_EOR;
rgn->rr_RgnDataSize = dest_size;
ASSERT(rgn->rr_RgnDataSize >= 9);
}
/*
 * We now do a bounding box union of the two component bboxes and place
 * the result in the new region.
 */
BB_union(&r1->rr_BBox, &r2->rr_BBox, &rgn->rr_BBox);
/*
 * Done! We can get out..
 */
return TRUE;
}

/*
 * R_union_equals
 *
 * This function basically implements a r1 union= r2 type operation. Ie
 * r1 union r2 is calculated and the result returned in r1.
 *
 * Parameters:
 *     r1          A pointer to an R_Region. This represents
 *                 the first half of the union, and is also used to return
 *                 the eventual result.
 *     r2          A pointer to an R_Region. This represents the second
 *                 half of the union.
 *
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
int
R_union_equals
(
    R_Region  *r1,
    R_Region  *r2
)
{
    R_Region  new_rgn;
    if (r1->rr_RgnData == NULL)
        return R_init_region_with_region(r1, r2);
    if (!R_union(&new_rgn, r1, r2))
        return FALSE;
    R_empty_region(r1);
    *r1 = new_rgn;
    return TRUE;
}

/*
 * R_intersection
 *
 * This function inits a R_Region structure to represent the intersection
 * of it's two arguments.
 *
 * Parameters:
 *     rgn          A R_Region ptr to the R_Region structure to be initialised.
 *     r1           A R_Region ptr representing the first region.
 *     r2           A R_Region ptr representing the second region.
```

```
* Returns
*      TRUE on success, FALSE on failure.
*/
int
R_intersection
(
    R_Region  *rgn,
    R_Region  *r1,
    R_Region  *r2
)
{
    R_Int      *r1_dat;
    R_Int      *r2_dat;
    int         overlap_flags;

    int_tot++;

    rgn->rr_RgnData = NULL;
    if (!BB_intersect_test(&r1->rr_BBox, &r2->rr_BBox, &overlap_flags))
    {
        /*
         * The bounding boxes don't intersect. This means that the regions
         * don't intersect. Therefore, we simply set rgn->rr_RgnData to NULL
         * (signifying an empty region) and get out..
         */
        return TRUE;
    }
    R_Int      min_row;
    int         dest_size;
    unsigned char *rgn_bld_stat;
    R_Int      *rgn_bld_dat;
    int         i;
    int         in_run;
    int         done_r1_in_row;
    IntXYMinMax new_bbox;

    int_full++;

    /*
     * The two regions _do_ overlap in x _and_ y. We therefore have
     * to do a bit more work in calculating the intersection of the two
     * regions. We use the R_RegionBuilder struct to store state
     * regarding the currently active regions as we progress through
     * the rows of each region. After any rows relevant to a y-coord
     * are added to the region builder, we examine the state of each
     * pixel run in the region builder. If the addition of the row(s)
     * for the y-coord have caused a transition to or from 0x3, then
     * the pixel run is emitted.
     */
    /*
     * Initialise the new_bbox structure for determining the new bounding box.
     */
    new_bbox.X.Min = R_INT_MAX_VALUE;
    new_bbox.Y.Min = R_INT_MAX_VALUE;
    new_bbox.X.Max = R_INT_MIN_VALUE;
    new_bbox.Y.Max = R_INT_MIN_VALUE;

    /*
     * The next thing we do is ensure the current region builder is empty,
     * and set up pointers into the region data of the two regions.
     */
    r1_dat = r1->rr_RgnData;
    r2_dat = r2->rr_RgnData;
    R_CurRB->rrb_Nels = 0;
    dest_size = 0;
    /*
     * We are now ready to loop through the data from both regions. Notice
```

```
* that we only keep looping whilst _both_ regions have some data left
* to give. As soon as either of the region's data has been exhausted,
* then we stop as the intersection region has already been calculated
* and is sitting in the rgn_buf.
*/
while (*r1_dat != R_EOR && *r2_dat != R_EOR)
{
    ASSERT(*r1_dat == R_NEXT_IS_Y || *r1_dat == R_EOR);
    ASSERT(*r2_dat == R_NEXT_IS_Y || *r2_dat == R_EOR);
    if (*r1_dat == R_EOR)
        min_row = r2_dat[1];
    else if (*r2_dat == R_EOR)
        min_row = r1_dat[1];
    else
        min_row = min(r1_dat[1], r2_dat[1]);
    done_r1_in_row = FALSE;
    if (*r1_dat != R_EOR && r1_dat[1] == min_row)
    {
        /*
         * The first region is active on this y coord. We add this
         * row to the current region builder.
         */
        if (!R_add_row_to_region_builder(&r1_dat, 0x1, TRUE))
            return FALSE;
        done_r1_in_row = TRUE;
    }
    if (*r2_dat != R_EOR && r2_dat[1] == min_row)
    {
        /*
         * The first region is active on this y coord. We add this
         * row to the current region builder.
         */
        if (!R_add_row_to_region_builder(&r2_dat, 0x2, !done_r1_in_row))
            return FALSE;
    }
    /*
     * Now, we generate the output row for the input rows.
     */
    if (!r_check_rgn_buf_len(dest_size + 2))
    {
        return FALSE;
    }
    r_RgnBuf[dest_size++] = R_NEXT_IS_Y;
    r_RgnBuf[dest_size++] = min_row;
    rgn_bld_stat = R_CurRB->rrb_StateData;
    rgn_bld_dat = R_CurRB->rrb_RgnData;
    in_run = FALSE;
    for (i = R_CurRB->rrb_Nels; i > 0; i--)
    {
        if
        (
            *rgn_bld_stat != (3 | (3 << RB_STATE_SIZE))
            &&
            (
                (*rgn_bld_stat & RB_PREV_STATE_MASK) == 3
                ||
                (*rgn_bld_stat & RB_CUR_STATE_MASK) == (3 << RB_STATE_SIZE))
        )
        {
            /*
             * We have to emit a run here, if we're not already
             * in one..
             */
            if (!in_run)
            {
                if (!r_check_rgn_buf_len(dest_size + 1))
                {
                    return FALSE;
                }
            }
        }
    }
}
```



```
    )
    r_RgnBuf[dest_size++] = *rgn_bld_dat;
    in_run = TRUE;
    new_bbox.X.Min = min(new_bbox.X.Min, *rgn_bld_dat);
  }
}
else
{
    if (in_run)
    {
        /*
         * We've come to the end of a run. We output the next element
         * to end it.
         */
        if (!r_check_rgn_buf_len(dest_size + 1))
        {
            return FALSE;
        }
        r_RgnBuf[dest_size++] = *rgn_bld_dat;
        new_bbox.X.Max = max(new_bbox.X.Max, *rgn_bld_dat);
    }
    in_run = FALSE;
}
rgn_bld_stat++;
rgn_bld_dat++;
}
if (r_RgnBuf[dest_size - 2] == R_NEXT_IS_Y)
{
    /*
     * We didn't output anything for these input rows. Rewind..
     */
    dest_size -= 2;
}
else
{
    if (min_row < new_bbox.Y.Min)
        new_bbox.Y.Min = min_row;
    else if (min_row > new_bbox.Y.Max)
        new_bbox.Y.Max = min_row;
}
}
/*
 * We've completed constructing the data for the region. Firstly
 * we check to see if we've emitted anything at all. If we have
 * then dest_size must be > 0. If it isn't we simply free the
 * region we created and get out, as the regions don't really
 * intersect, in spite of their intersecting bounding boxes.
 */
if (dest_size == 0)
{
    return TRUE;
}
/*
 * We make a copy the constructed data from the permanent buffer to
 * an exactly fitting buffer.
 */
rgn->rr_RgnData = (R_Int *)malloc(++dest_size * sizeof(R_Int));
if (rgn->rr_RgnData == NULL)
{
    return FALSE;
}
memcpy(rgn->rr_RgnData, r_RgnBuf, (dest_size - 1) * sizeof(R_Int));
rgn->rr_RgnData[dest_size - 1] = R_EOR;
rgn->rr_RgnDataSize = dest_size;
ASSERT(rgn->rr_RgnDataSize >= 9);
/*
 * Now, copy across the bounding box.. Before we do this, we subtract
 * 1 from X.Max and Y.Max because of the region format.
 */

```

```
    */
    new_bbox.X.Max--;
    new_bbox.Y.Max--;
    rgn->rr_BBox = new_bbox;
    /*
     * Done! We can get out..
     */
    return TRUE;
}

/*
 * R_difference
 *
 * This function inits a R_Region structure to represent the difference of
 * it's two arguments. It essentially calculates r1 - r2
 *
 * Parameters:
 *     rgn      A R_Region ptr representing the R_Region to be initied.
 *     r1      A R_Region ptr representing the first region.
 *     r2      A R_Region ptr representing the second region.
 * Returns
 *     TRUE on success, FALSE on failure.
 */
int
R_difference
(
    R_Region  *rgn,
    R_Region  *r1,
    R_Region  *r2
)
{
    R_Int      *r1_dat;
    R_Int      *r2_dat;
    int        overlap_flags;

    diff_tot++;

    rgn->rr_RgnData = NULL;
    if (!BB_intersect_test(&r1->rr_BBox, &r2->rr_BBox, &overlap_flags))
    {
        /*
         * The bounding boxes don't intersect. This means that r1 - r2
         * simply equals r1. We make a copy of the relevant bits and get out..
         */
        rgn->rr_BBox = r1->rr_BBox;
        rgn->rr_RgnDataSize = r1->rr_RgnDataSize;
        rgn->rr_RgnData = (R_Int *)malloc(r1->rr_RgnDataSize * sizeof(R_Int));
        if (rgn->rr_RgnData == NULL)
        {
            return FALSE;
        }
        memcpy
        (
            rgn->rr_RgnData,
            r1->rr_RgnData,
            r1->rr_RgnDataSize * sizeof(R_Int)
        );
        return TRUE;
    }
    R_Int      min_row;
    unsigned char  degg_bldstat;
    R_Int      *rgn_bld_dat;
    int        i;
    int        in_run;
    int        done_r1_in_row;
    unsigned char  m_high;
```

```
unsigned char  m_low;
IntXYMinMax    new_bbox;
```

```
diff_full++;
```

```
/*
 * The two regions _do_ overlap in x_and y. We therefore have
 * to do a bit more work in calculating the difference of the two
 * regions. We use the R_RegionBuilder struct to store state
 * regarding the currently active regions as we progress through
 * the rows of each region. After any rows relevant to a y-coord
 * are added to the region builder, we examine the state of each
 * pixel run in the region builder. If the addition of the row(s)
 * for the y-coord have caused the following transitions -
 *
 *          r1      -> 0
 *          0       -> r2
 *          r1 + r2 -> r2
 *          r2      -> r1 + r2
 * ..then the relevant runs are emitted. Firstly, though,
 * we ensure the current region builder is empty,
 * and set up pointers into the region data of the two regions.
 */
r1_dat = r1->rr_RgnData;
r2_dat = r2->rr_RgnData;
R_CurRB->rrb_Nels = 0;
dest_size = 0;

/*
 * Initialise the new_bbox structure for determining the new bounding box.
 */
new_bbox.X.Min = 32767;
new_bbox.Y.Min = 32767;
new_bbox.X.Max = -32768;
new_bbox.Y.Max = -32768;

/*
 * We are now ready to loop through the data from both regions. Notice
 * that we only keep looping whilst r1 has data outstanding. When
 * r1's data is consumed, then any transitions made by r2 are
 * irrelevant.
 */
while (*r1_dat != R_EOR)
{
    ASSERT(*r1_dat == R_NEXT_IS_Y || *r1_dat == R_EOR);
    ASSERT(*r2_dat == R_NEXT_IS_Y || *r2_dat == R_EOR);
    if (*r1_dat == R_EOR)
        min_row = r2_dat[1];
    else if (*r2_dat == R_EOR)
        min_row = r1_dat[1];
    else
        min_row = min(r1_dat[1], r2_dat[1]);
    done_r1_in_row = FALSE;
    if (*r1_dat != R_EOR && r1_dat[1] == min_row)
    {
        /*
         * The first region is active on this y coord. We add this
         * row to the current region builder.
         */
        if (!R_add_row_to_region_builder(&r1_dat, 0x1, TRUE))
            return FALSE;
        done_r1_in_row = TRUE;
    }
    if (*r2_dat != R_EOR && r2_dat[1] == min_row)
    {
        /*
         * The first region is active on this y coord. We add this
         * row to the current region builder.
         */
    }
}
```

```
        if (!R_add_row_to_region_builder(&r2_dat, 0x2, !done_r1_in_row))
            return FALSE;
    }
    /*
     * Now, we generate the output row for the input rows.
     */
    if (!r_check_rgn_buf_len(dest_size + 2))
    {
        return FALSE;
    }
    r_RgnBuf[dest_size++] = R_NEXT_IS_Y;
    r_RgnBuf[dest_size++] = min_row;
    rgn_bld_stat = R_CurRB->rrb_StateData;
    rgn_bld_dat = R_CurRB->rrb_RgnData;
    in_run = FALSE;
    for (i = R_CurRB->rrb_Nels; i > 0; i--)
    {
        m_high = (*rgn_bld_stat & RB_CUR_STATE_MASK) >> RB_STATE_SIZE;
        m_low = *rgn_bld_stat & RB_PREV_STATE_MASK;
        if
        (
            (
                (m_low != 1 && m_high == 1)
                ||
                (m_low == 1 && m_high != 1)
            )
        )
        {
            /*
             * We have to emit a run here, if we're not already
             * in one..
             */
            if (!in_run)
            {
                if (!r_check_rgn_buf_len(dest_size + 1))
                {
                    return FALSE;
                }
                r_RgnBuf[dest_size++] = *rgn_bld_dat;
                in_run = TRUE;
                new_bbox.X.Min = min(new_bbox.X.Min, *rgn_bld_dat);
            }
        }
        else
        {
            if (in_run)
            {
                /*
                 * We've come to the end of a run. We output the next element
                 * to end it.
                 */
                if (!r_check_rgn_buf_len(dest_size + 1))
                {
                    return FALSE;
                }
                r_RgnBuf[dest_size++] = *rgn_bld_dat;
                new_bbox.X.Max = max(new_bbox.X.Max, *rgn_bld_dat);
            }
            in_run = FALSE;
        }
        rgn_bld_stat++;
        rgn_bld_dat++;
    }
    if (r_RgnBuf[dest_size - 2] == R_NEXT_IS_Y)
    {
        /*
         * We didn't output anything for these input rows. Rewind..
         */
    }
```

```
        dest_size -= 2;
    }
    else
    {
        if (min_row < new_bbox.Y.Min)
            new_bbox.Y.Min = min_row;
        else if (min_row > new_bbox.Y.Max)
            new_bbox.Y.Max = min_row;
    }
}

/*
 * We've completed constructing the data for the region. Firstly
 * we check to see if we've emitted anything at all. If we have
 * then dest_size must be > 0. If it isn't we simply free the
 * region we created and get out, as r2 - r1 must be empty.
 */
if (dest_size == 0)
{
    return TRUE;
}

/*
 * We make a copy the constructed data from the permanent buffer to
 * an exactly fitting buffer.
 */
rgn->rr_RgnData = (R_Int *)malloc(++dest_size * sizeof(R_Int));
if (rgn->rr_RgnData == NULL)
{
    return FALSE;
}
memcpy(rgn->rr_RgnData, r_RgnBuf, (dest_size - 1) * sizeof(R_Int));
rgn->rr_RgnData[dest_size - 1] = R_EOR;
rgn->rr_RgnDataSize = dest_size;
ASSERT(rgn->rr_RgnDataSize >= 9);

/*
 * Now, copy across the bounding box..
 */
rgn->rr_BBox = new_bbox;

/*
 * Done! We can get out..
 */
return TRUE;
}

#endif /* R_USE_NEW_IMP */

/*
 * r_grow_free_list
 *
 * This function mallocs and adds R_FREE_LIST_GROWTH_SIZE new elements
 * to the front of the region growth free list.
 *
 * Parameters:
 *     None.
 *
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
int
r_grow_free_list()
{
    R_RgnGrowItem *rgi;
    int i;

    /*
     * First, malloc the memory..
     */
    rgi = (R_RgnGrowItem *)malloc
        (
            R_FREE_LIST_GROWTH_SIZE * sizeof(R_RgnGrowItem)
        );

    if (rgi == NULL)
        return FALSE;
}
```

```
/*
 * Now make the whole block of memory into a list..
 */
for (i = 0; i < R_FREE_LIST_GROWTH_SIZE - 1; i++)
    rgi[i].rrgi_Next = &rgi[i + 1];
/*
 * Now, add it to the front of the free list..
 */
rgi[R_FREE_LIST_GROWTH_SIZE - 1].rrgi_Next = r_free_list;
r_free_list = rgi;
return TRUE;
}

/*
 * R_add_row_to_region_growth_list
 *
 * This function adds a row from a R_Region to a linked list comprised of
 * R_RgnGrowItem structures. "Adding" implies that the linked list is
 * modified such that the state and coordinate information present
 * in the list is updated to take into account the new row just added.
 * Adding a row has the following properties:
 *
 * * If a pixel run in the row does not exist in the list before,
 *   it is added and it's current state is tagged with the region
 *   to which the row belongs. The previous state is set to 0,
 *   indicating that it did not exist before.
 *
 * * If a pixel run in the row did exist before, but it's present state
 *   indicates that it came from the other region then the run
 *   is retained but it's state is modified to indicate that
 *   both regions are active at this point.
 *
 * * If a pixel run in the row did exist before, and it's present
 *   state indicates that the current region then the region is
 *   removed and it's state is modified to indicate that the run is
 *   now empty.
 *
 * * If a pixel run in the row did exist before, and it's present state
 *   indicates that both regions are currently active then the run
 *   is retained, but its state is modified to indicate that only the
 *   other region is active in this run.
 *
 * Parameters:
 *
 *     row_ptr    A R_Int ** pointer to the row in the region. Used
 *                to return the updates row pointer.
 *
 *     rgn_mask   A mask for the region the row comes from. Must
 *                be either 1 or 2.
 *
 *     first      Whether this is the first region to be processed
 *                on the current scanline.
 *
 * Returns:
 *
 *     TRUE on success, FALSE on failure.
 */
int
R_add_row_to_region_growth_list
(
    R_Int      **row_ptr,
    int        rgn_mask,
    int        first
)
{
    R_Int      *row;
    R_RgnGrowItem *rgi;
    unsigned char rb_prev_run_state;
    int         row_on;

    row = *row_ptr;
    /*
     * Skip over the row's y value at the beginning.
     */
    ASSERT(*row == R_NEXT_IS_Y);
    row += 2;
    ASSERT(*row != R_NEXT_IS_Y && *row != R_EOR);
```

```
If (r_growth_list == NULL)
{
    R_RgnGrowItem  **ptr_next_ptr;
    /*
     * The growth list is currently empty. Therefore, we simply convert
     * the input row to the region growth list format..
     */
    row_on = TRUE;
    ptr_next_ptr = &r_growth_list;
    while (R_NOT_END_OF_ROW(*row))
    {
        if (r_free_list == NULL)
        {
            if (!r_grow_free_list())
                return FALSE;
        }
        rgi = r_free_list;
        *ptr_next_ptr = rgi;
        ptr_next_ptr = &rgi->rrgi_Next;
        r_free_list = *ptr_next_ptr;
        rgi->rrgi_RgnData = *row;
        if (row_on)
            rgi->rrgi_StateData = (rgn_mask << RB_STATE_SIZE);
        else
            rgi->rrgi_StateData = 0;
        row_on = !row_on;
        row++;
    }
    *row_ptr = row;
    *ptr_next_ptr = NULL;
    return TRUE;
}

R_RgnGrowItem  fake_item;
R_RgnGrowItem  *prev_rgi;

/*
 * "fake_item" is used as the head of the list. This is so that we _always_ have
 * a valid pointer to the previous item in the list. Only the next pointer and
 * state data are initialised, as these are they only elements which will be
 * referenced.
 */
fake_item.rrgi_StateData = 0;
fake_item.rrgi_Next = r_growth_list;
prev_rgi = &fake_item;
if (first)
{
    /*
     * If this is the first row to be added on this particular scanline,
     * then we have to update the existing contents of those elements
     * at the beginning of the growth list which precede (in coords) the
     * first element of the row. "Updating" involves updating the
     * previous state of each element to match the current state. This is
     * because none of the elements were effected by the addition of the
     * new row.
     */
    rgi = r_growth_list;
    while (rgi != NULL && *row > rgi->rrgi_RgnData)
    {
#ifdef RB_USE_LOOKUP
        rgi->rrgi_StateData = (rgi->rrgi_StateData & RB_CUR_STATE_MASK) |
                               (rgi->rrgi_StateData >> RB_STATE_SIZE);
#else
        rgi->rrgi_StateData = r_shift_and_dup[rgi->rrgi_StateData];
#endif
        prev_rgi = rgi;
    }
}
```

```
        rgi = rgi->rrgi_Next;
    }
else
{
    /*
     * This is the second row to be added on this particular scanline.
     * Therefore, we don't need to update the state of the elements
     * preceding (in coords) the first run of the row to be added, as
     * they have already been updated by the first row to be added on
     * this scanline. We simply skip over the unaffected elements..
     */
    rgi = r_growth_list;
    while (rgi != NULL && *row > rgi->rrgi_RgnData)
    {
        prev_rgi = rgi;
        rgi = rgi->rrgi_Next;
    }
    if (rgi == NULL)
    {
        /*
         * We've already exhausted the current growth list. Set the start
         * of the next pixel run to be the max. possible and set the state
         * to be 0.
         */
        rb_prev_run_state = 0;
    }
    else
    {
        /*
         * We are still within the current growth list bounds. Set up
         * the run info appropriately.
         */
        if (rgi == r_growth_list)
            rb_prev_run_state = 0;
        else
            rb_prev_run_state = prev_rgi->rrgi_StateData;
    }
    /*
     * We can now start merging the elements of the row with the remaining
     * elements of the growth list.
     */
    row_on = TRUE;
    while (R_NOT_END_OF_ROW(*row))
    {
        if (rgi == NULL || *row < rgi->rrgi_RgnData)
        {
            /*
             * This is the only situation in which we actually have to
             * create a new list element. First, we check that we
             * actually have an element in the free list that we
             * can use in the growth list..
             */
            if (r_free_list == NULL)
            {
                if (!r_growFALSE_list())
                {
                    prev_rgi->rrgi_Next = r_free_list;
                    prev_rgi = r_free_list;
                    r_free_list = r_free_list->rrgi_Next;
                    prev_rgi->rrgi_Next = rgi;
                }
                /*
                 * Now, fill in the data..
                 */
                prev_rgi->rrgi_RgnData = *row;
            }
        }
    }
}
```



```
        if (first)
        {
            /*
             * We are processing the first region. Therefore, we
             * copy the current state of the run to the lowest
             * RB_STATE_SIZE bits.
             */
#ifdef RB_USE_LOOKUP
            prev_rgi->rrgi_StateData = (rb_prev_run_state & RB_CUR_STATE_MASK) |
                                      (rb_prev_run_state >> RB_STATE_SIZE);
#else
            prev_rgi->rrgi_StateData = r_shift_and_dup(rb_prev_run_state);
#endif
        }
        else
        {
            /*
             * We are processing the second region. Therefore, the state data
             * has already been copied to the previous state area so we
             * just copy the state.
             */
            prev_rgi->rrgi_StateData = rb_prev_run_state;
        }
        /*
         * Now, if the row for the current region is active at this transition,
         * we xor the region mask with the current contents of the new list
         * item. This gives the desired behaviour of making that region active
         * if it is not there already, but turns it off if it is...
         */
        if (row_on)
            prev_rgi->rrgi_StateData ^= (rgn_mask << RB_STATE_SIZE);
        /*
         * We now move onto the next row element.
         */
        row++;
        row_on = !row_on;
        continue;
    }
    /*
     * If the current row transition point is equal in x position to the current
     * list item's transition point, we advance the row counter to
     * the next position.
     */
    if (*row == rgi->rrgi_RgnData)
    {
        row++;
        row_on = !row_on;
    }
    /*
     * We update the current list item to deal with the affects of the
     * current row run...
     */
    rb_prev_run_state = rgi->rrgi_StateData;
    if (first)
    {
#ifdef RB_USE_LOOKUP
        rgi->rrgi_StateData = (rb_prev_run_state & RB_CUR_STATE_MASK) |
                              (rb_prev_run_state >> RB_STATE_SIZE);
#else
        rgi->rrgi_StateData = r_shift_and_dup(rb_prev_run_state);
#endif
    }
    if (!row_on)
        rgi->rrgi_StateData ^= (rgn_mask << RB_STATE_SIZE);
    /*
     * We now move onto the next element in the list..
     */
    prev_rgi = rgi;
```

```
        rgi = rgi->rrgi_Next;
    }
    /*
     * Now, simply update the remainder of the elements in the list..
     */
    if (first)
    {
        while (rgi != NULL)
        {
#ifdef RB_USE_LOOKUP
            rgi->rrgi_StateData = (rgi->rrgi_StateData & RB_CUR_STATE_MASK) |
                                   (rgi->rrgi_StateData >> RB_STATE_SIZE);
#else
            rgi->rrgi_StateData = r_shift_and_dup(rgi->rrgi_StateData);
#endif
            rgi = rgi->rrgi_Next;
        }
    }
    /*
     * Now copy "fake_item"'s next pointer to r_growth_list, as it will have
     * changed if something was added to the head of the list..
     */
    r_growth_list = fake_item.rrgi_Next;
    /*
     * Update the return pointer to the region data..
     */
    *row_ptr = row;
    /*
     * Everything should now be OK..
     */
    return TRUE;
}

#ifdef R_USE_NEW_IMP
/*
 * r_union_test_table
 *
 * A 16-int lookup table which when provided with an unsigned char
 * of the following form xxyy, will provide evaluate the key
 * state transition test of the union construction loop.
 * Note that R_STATE_SIZE _must_ be 2 for this lookup table to
 * work.
 */
int r_union_test_table[16] = {
    0, 1, 1, 1,
    1, 0, 0, 0,
    1, 0, 0, 0,
    1, 0, 0, 0
};

/*
 * R_union
 *
 * This function inits a R_Region structure to represent the union
 * of it's two arguments.
 *
 * Parameters:
 *     rgn      The R_Region to be initialised.
 *     r1       A R_Region ptr representing the first region.
 *     r2       A R_Region ptr representing the second region.
 *
 * Returns
 *     TRUE on success, FALSE on failure.
 */
int
R_union
(
    R_Region    *rgn,
```

```
R_Region  *r1,
R_Region  *r2

{

    R_Int    *r1_dat;
    R_Int    *r2_dat;
    int      overlap_flags;

    union_tot++;

    if (!BB_intersect_test(&r1->rr_BBox, &r2->rr_BBox, &overlap_flags))
    {
        /*
         * The bounding boxes don't intersect. This means we can do the
         * union very easily, simply by copying data from the two regions.
         * We malloc a new region data array of size r1->rr_RgnDataSize +
         * r2->rr_RgnDataSize - 1. This is the maximum possible size of
         * resulting region. Not all of this memory will be utilised if
         * the two regions being combined have rows with the same y coordinate
         * (R_NEXT_IS_Y marker is not duplicated).
         */
        rgn->rr_RgnDataSize = r1->rr_RgnDataSize + r2->rr_RgnDataSize - 1;
        rgn->rr_RgnData = (R_Int *)malloc(rgn->rr_RgnDataSize *
                                           sizeof(R_Int));

        if (rgn->rr_RgnData == NULL)
        {
            return FALSE;
        }
        /*
         * Now, check to see if the regions overlap in y...
         */
        if (!(overlap_flags & BB_INTERSECT_OVERLAP_Y))
        {
            /*
             * The regions don't overlap in y. We simply copy one region
             * and then another into the array we malloced. We ensure
             * that r1 points to the region with the smallest y coordinate.
             */
            if (r2->rr_BBox.Y.Min < r1->rr_BBox.Y.Min)
            {
                R_Region  *tmp;
                tmp = r1;
                r1 = r2;
                r2 = tmp;
            }
            memcpy
            (
                rgn->rr_RgnData,
                r1->rr_RgnData,
                (r1->rr_RgnDataSize - 1) * sizeof(R_Int)
            );
            memcpy
            (
                rgn->rr_RgnData + r1->rr_RgnDataSize - 1,
                r2->rr_RgnData,
                r2->rr_RgnDataSize * sizeof(R_Int)
            );
            ASSERT(rgn->rr_RgnData[rgn->rr_RgnDataSize - 1] == R_EOR);
        }
        else
        {
            R_Int    *r1_tmp;
            R_Int    *r2_tmp;
            R_Int    *dest;
            R_Int    min_row;
            int      r1_done;
            int      r1_consumed;
            int      r2_consumed;
```

```
int      num_written;
/*
 * The bboxes overlap in y but not in x. We simply go row
 * by row through each region and memcpy the individual rows as
 * appropriate. We ensure that r1 points to the region with
 * the smallest x coordinate.
 */
if (r2->rr_BBox.X.Min < r1->rr_BBox.X.Min)
{
    R_Region *tmp;
    tmp = r1;
    r1 = r2;
    r2 = tmp;
}
r1_dat = r1->rr_RgnData;
r2_dat = r2->rr_RgnData;
dest = rgn->rr_RgnData;
rgn->rr_RgnDataSize = 0;
r1_consumed = 0;
r2_consumed = 0;
while (*r1_dat != R_EOR && *r2_dat != R_EOR)
{
    ASSERT(*r1_dat == R_NEXT_IS_Y);
    ASSERT(*r2_dat == R_NEXT_IS_Y);
    min_row = min(r1_dat[1], r2_dat[1]);
    r1_done = FALSE;
    if (r1_dat[1] == min_row)
    {
        /*
         * We need to emit r1. We therefore need to find where
         * the next row (if any) starts. When we do this we
         * recall that a y value _must_ be followed by at least
         * two x values..
         */
        r1_tmp = r1_dat + 4;
        while (*r1_tmp != R_NEXT_IS_Y && *r1_tmp != R_EOR)
            r1_tmp++;
        num_written = r1_tmp - r1_dat;
        memcpy(dest, r1_dat, num_written * sizeof(R_Int));
        dest += num_written;
        r1_consumed += num_written;
        rgn->rr_RgnDataSize += num_written;
        r1_dat = r1_tmp;
        r1_done = TRUE;
    }
    if (r2_dat[1] == min_row)
    {
        /*
         * We need to emit r1. We therefore need to find where
         * the next row (if any) starts. When we do this we
         * recall that a y value _must_ be followed by at least
         * two x values. If r1's current row has already been
         * emitted for this y value, we do _not_ emit the
         * R_NEXT_IS_Y marker or the y value itself.
         */
        if (r1_done)
        {
            r2_dat += 2;
            r2_tmp = r2_dat + 2;
            r2_consumed += 2;
        }
        else
        {
            r2_tmp = r2_dat + 4;
        }
        while (*r2_tmp != R_NEXT_IS_Y && *r2_tmp != R_EOR)
            r2_tmp++;
        num_written = r2_tmp - r2_dat;
    }
}
```

```
        memcpy(dest, r2_dat, num_written * sizeof(R_Int));
        dest += num_written;
        r2_consumed += num_written;
        rgn->rr_RgnDataSize += num_written;
        r2_dat = r2_tmp;
    }
}
if (*r1_dat != R_EOR)
{
    /*
     * r1 is the last region left standing. We memcpy
     * the remainder of the region (including the
     * R_EOR marker) to the destination.
     */
    ASSERT(r2_consumed == r2->rr_RgnDataSize - 1);
    memcpy
    (
        dest,
        r1_dat,
        (r1->rr_RgnDataSize - r1_consumed) * sizeof(R_Int)
    );
    rgn->rr_RgnDataSize += (r1->rr_RgnDataSize - r1_consumed);
}
else
{
    /*
     * r2 is the last region left standing. We memcpy
     * the remainder of the region (including the
     * R_EOR marker) to the destination.
     */
    ASSERT(r1_consumed == r1->rr_RgnDataSize - 1);
    memcpy
    (
        dest,
        r2_dat,
        (r2->rr_RgnDataSize - r2_consumed) * sizeof(R_Int)
    );
    rgn->rr_RgnDataSize += (r2->rr_RgnDataSize - r2_consumed);
}
ASSERT
(
    rgn->rr_RgnData[rgn->rr_RgnDataSize - 1] == R_EOR
);
}
}
else
{
    R_Int          min_row;
    int            dest_size;
    R_RgnGrowItem  *rgi;
    R_RgnGrowItem  *rgi_tail;
    int            in_run;
    int            done_r1_in_row;

    union_full++;

    /*
     * The two regions _do_ overlap in x_and_y. We therefore have
     * to do a bit more work in calculating the union of the two
     * regions. We use the a list of R_RgnGrowItem structs to store state
     * regarding the currently active regions as we progress through
     * the rows of each region. After any rows relevent to a y-coord
     * are added to the list, we examine the state of each
     * pixel run in the list. If the addition of the row(s)
     * for the y-coord have caused a transition to or from 0, then
     * the pixel run is emitted.
     */
}
```

```

r1_dat = r1->rr_RgnData;
r2_dat = r2->rr_RgnData;
dest_size = 0;
/*
 * We are now ready to loop through the data of both regions.
 * We continue building the new region whilst there is data
 * remaining in either of the two regions.
 */
while (*r1_dat != R_EOR || *r2_dat != R_EOR)
{
    ASSERT(*r1_dat == R_NEXT_IS_Y || *r1_dat == R_EOR);
    ASSERT(*r2_dat == R_NEXT_IS_Y || *r2_dat == R_EOR);
    if (*r1_dat == R_EOR)
        min_row = r2_dat[1];
    else if (*r2_dat == R_EOR)
        min_row = r1_dat[1];
    else
        min_row = min(r1_dat[1], r2_dat[1]);
    done_r1_in_row = FALSE;
    if (*r1_dat != R_EOR && r1_dat[1] == min_row)
    {
        /*
         * The first region is active on this y coord. We add this
         * row to the current region builder.
         */
        if (!R_add_row_to_region_growth_list(&r1_dat, 0x1, TRUE))
            return FALSE;
        done_r1_in_row = TRUE;
    }
    if (*r2_dat != R_EOR && r2_dat[1] == min_row)
    {
        /*
         * The first region is active on this y coord. We add this
         * row to the current region builder.
         */
        if (!R_add_row_to_region_growth_list(&r2_dat, 0x2,
            !done_r1_in_row))
            return FALSE;
    }
    /*
     * Now, we generate the output row for the input rows.
     */
    if (!r_check_rgn_buf_len(dest_size + 2))
    {
        return FALSE;
    }
    r_RgnBuf[dest_size++] = R_NEXT_IS_Y;
    r_RgnBuf[dest_size++] = min_row;
    in_run = FALSE;
#ifdef R_NEW_IMP_CONSTRUCTION_LOOP
    for (rgi = r_growth_list; rgi != NULL; rgi = rgi->rrgi_Next)
    {
        if
        (
            rgi->rrgi_StateData > 0
            &&
            (
                (rgi->rrgi_StateData & RB_CUR_STATE_MASK) == 0
                ||
                (rgi->rrgi_StateData & RB_PREV_STATE_MASK) == 0
            )
        )
        {
            if (r_union_test_table(rgi->rrgi_StateData))
            {
                /*

```

```

    * We have to emit a run here, if we're not already
    * in one..
    */
    if (!in_run)
    {
        if (!r_check_rgn_buf_len(dest_size + 1))
        {
            return FALSE;
        }
        r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
        in_run = TRUE;
    }
}
else
{
    if (in_run)
    {
        /*
        * We've come to the end of a run. We output the next
        element to end it.
        */
        if (!r_check_rgn_buf_len(dest_size + 1))
        {
            return FALSE;
        }
        r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
    }
    in_run = FALSE;
}
/*
* Not efficient, get rid of it..
*/
if (rgi->rrgi_Next == NULL)
    rgi_tail = rgi;
}

#else

rgi = r_growth_list;
rgi_tail = rgi;
while (rgi != NULL && !r_union_test_table[rgi->rrgi_StateData])
    rgi = rgi->rrgi_Next;
while (rgi != NULL)
{
    if (!r_check_rgn_buf_len(dest_size + 2))
        return FALSE;
    r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
    do
    {
        rgi = rgi->rrgi_Next;
    } while (rgi != NULL && r_union_test_table[rgi->rrgi_StateData]);
    rgi_tail = rgi;
    r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
    do
    {
        rgi = rgi->rrgi_Next;
    } while (rgi != NULL && !r_union_test_table[rgi->rrgi_StateData]);
}

#endif

if (r_RgnBuf[dest_size - 2] == R_NEXT_IS_Y)
{
    /*
    * We didn't output anything for these input rows. Rewind..
    */
    dest_size -= 2;
}

}
/*
* Now, we've completed using the growth list for constructing this
* region. Therefore, we add it to the front of the free list, to
```

```
        * be re-used later.
        */
#ifdef R_NEW_IMP_CONSTRUCTION_LOOP
    while (rgi_tail->rrgi_Next != NULL)
        rgi_tail = rgi_tail->rrgi_Next;
#endif
    rgi_tail->rrgi_Next = r_free_list;
    r_free_list = r_growth_list;
    r_growth_list = NULL;
    /*
     * We've completed constructing the data for the region. We
     * make a copy the constructed data from the permanent buffer to
     * an exactly fitting buffer.
     */
    rgn->rr_RgnData = (R_Int *)malloc(++dest_size * sizeof(R_Int));
    if (rgn->rr_RgnData == NULL)
    {
        return FALSE;
    }
    memcpy(rgn->rr_RgnData, r_RgnBuf, (dest_size - 1) * sizeof(R_Int));
    rgn->rr_RgnData[dest_size - 1] = R_EOR;
    rgn->rr_RgnDataSize = dest_size;
    ASSERT(rgn->rr_RgnDataSize >= 9);
}
/*
 * We now do a bounding box union of the two component bboxes and place
 * the result in the new region.
 */
BB_union(&r1->rr_BBox, &r2->rr_BBox, &rgn->rr_BBox);
/*
 * Done! We can get out..
 */
return TRUE;
}

/*
 * R_union_equals
 *
 * This function basically implements a r1 union= r2 type operation. Ie
 * r1 union r2 is calculated and the result returned in r1.
 *
 * Parameters:
 *     r1          A pointer to an R_Region. This represents
 *                 the first half of the union, and is also used to return
 *                 the eventual result.
 *     r2          A pointer to an R_Region. This represents the second
 *                 half of the union.
 *
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
int
R_union_equals
(
    R_Region *r1,
    R_Region *r2
)
{
    R_Region new_rgn;
    If (r1->rr_RgnData == NULL)
        return R_init_region_with_region(r1, r2);
    if (!R_union(&new_rgn, r1, r2))
        return FALSE;
    R_empty_region(r1);
    *r1 = new_rgn;
    return TRUE;
}

/*
```



```
* r_intersection_test_table
*
* A 16-int lookup table which when provided with an unsigned char
* of the following form xxyy, will provide evaluate the key
* state transition test of the intersection construction loop.
* Note that R_STATE_SIZE _must_ be 2 for this lookup table to
* work.
*/
int r_intersection_test_table[16] = {
    0, 0, 0, 1,
    0, 0, 0, 1,
    0, 0, 0, 1,
    1, 1, 1, 0
};

/*
* R_intersection
*
* This function inits a R_Region structure to represent the intersection
* of it's two arguments.
*
* Parameters:
*     rgn      A R_Region ptr to the R_Region structure to be initialised.
*     r1       A R_Region ptr representing the first region.
*     r2       A R_Region ptr representing the second region.
* Returns
*     TRUE on success, FALSE on failure.
*/
int
R_intersection
(
    R_Region *rgn,
    R_Region *r1,
    R_Region *r2
)
{
    R_Int      *r1_dat;
    R_Int      *r2_dat;
    int         overlap_flags;

    int_tot++;

    rgn->rr_RgnData = NULL;
    if (!BB_intersect_test(&r1->rr_BBox, &r2->rr_BBox, &overlap_flags))
    {
        /*
         * The bounding boxes don't intersect. This means that the regions
         * don't intersect. Therefore, we simply set rgn->rr_RgnData to NULL
         * (signifying an empty region) and get out..
         */
        return TRUE;
    }
    R_Int      min_row;
    int         dest_size;
    R_RgnGrowItem *rgi;
    R_RgnGrowItem *rgi_tail;
    int         in_run;
    int         done_r1_in_row;
    IntXYMinMax new_bbox;

    int_full++;

    /*
     * The two regions _do_ overlap in x _and_ y. We therefore have
     * to do a bit more work in calculating the intersection of the two
     * regions. We use the R_RegionBuilder struct to store state
     * regarding the currently active regions as we progress through

```

```
* the rows of each region. After any rows relevant to a y-coord
* are added to the region builder, we examine the state of each
* pixel run in the region builder. If the addition of the row(s)
* for the y-coord have caused a transition to or from 0x3, then
* the pixel run is emitted.
*/
/*
* Initialise the new_bbox structure for determining the new bounding box.
*/
new_bbox.X.Min = R_INT_MAX_VALUE;
new_bbox.Y.Min = R_INT_MAX_VALUE;
new_bbox.X.Max = R_INT_MIN_VALUE;
new_bbox.Y.Max = R_INT_MIN_VALUE;

/*
* The next thing we do is ensure the current region builder is empty,
* and set up pointers into the region data of the two regions.
*/
r1_dat = r1->rr_RgnData;
r2_dat = r2->rr_RgnData;
dest_size = 0;
/*
* We are now ready to loop through the data from both regions. Notice
* that we only keep looping whilst both regions have some data left
* to give. As soon as either of the region's data has been exhausted,
* then we stop as the intersection region has already been calculated
* and is sitting in the rgn_buf.
*/
while (*r1_dat != R_EOR && *r2_dat != R_EOR)
{
    ASSERT(*r1_dat == R_NEXT_IS_Y || *r1_dat == R_EOR);
    ASSERT(*r2_dat == R_NEXT_IS_Y || *r2_dat == R_EOR);
    If (*r1_dat == R_EOR)
        min_row = r2_dat[1];
    else if (*r2_dat == R_EOR)
        min_row = r1_dat[1];
    else
        min_row = min(r1_dat[1], r2_dat[1]);
    done_r1_in_row = FALSE;
    if (*r1_dat != R_EOR && r1_dat[1] == min_row)
    {
        /*
        * The first region is active on this y coord. We add this
        * row to the current region builder.
        */
        if (!R_add_row_to_region_growth_list(&r1_dat, 0x1, TRUE))
            return FALSE;
        done_r1_in_row = TRUE;
    }
    if (*r2_dat != R_EOR && r2_dat[1] == min_row)
    {
        /*
        * The first region is active on this y coord. We add this
        * row to the current region builder.
        */
        if (!R_add_row_to_region_growth_list(&r2_dat, 0x2, !done_r1_in_row))
            return FALSE;
    }
    /*
    * Now, we generate the output row for the input rows.
    */
    if (!r_check_rgn_buf_len(dest_size + 2))
    {
        return FALSE;
    }
    r_RgnBuf[dest_size++] = R_NEXT_IS_Y;
    r_RgnBuf[dest_size++] = min_row;
    in_run = FALSE;
}
```

```
#ifndef R_NEW_IMP_CONSTRUCTION_LOOP
    for (rgi = r_growth_list; rgi != NULL; rgi = rgi->rrgi_Next)
    {
        #if 0
            if
            (
                rgi->rrgi_StateData != (3 | (3 << RB_STATE_SIZE))
                &&
                (
                    (rgi->rrgi_StateData & RB_PREV_STATE_MASK) == 3
                    ||
                    (rgi->rrgi_StateData & RB_CUR_STATE_MASK) ==
                        (3 << RB_STATE_SIZE)
                )
            )
        #else
            if (r_intersection_test_table[rgi->rrgi_StateData])
        #endif
        {
            /*
             * We have to emit a run here, if we're not already
             * in one..
             */
            if (!in_run)
            {
                if (!r_check_rgn_buf_len(dest_size + 1))
                {
                    return FALSE;
                }
                r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
                in_run = TRUE;
                new_bbox.X.Min = min(new_bbox.X.Min, rgi->rrgi_RgnData);
            }
            else
            {
                if (in_run)
                {
                    /*
                     * We've come to the end of a run. We output the next element
                     */
                    if (!r_check_rgn_buf_len(dest_size + 1))
                    {
                        return FALSE;
                    }
                    r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
                    new_bbox.X.Max = max(new_bbox.X.Max, rgi->rrgi_RgnData);
                }
                in_run = FALSE;
            }
            /*
             * Not efficient, get rid of it..
             */
            if (rgi->rrgi_Next == NULL)
                rgi_tail = rgi;
        }
    }
#else
    rgi = r_growth_list;
    rgi_tail = rgi;
    while (rgi != NULL && !r_intersection_test_table[rgi->rrgi_StateData])
        rgi = rgi->rrgi_Next;
    while (rgi != NULL)
    {
        if (!r_check_rgn_buf_len(dest_size + 2))
            return FALSE;
        r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
        new_bbox.X.Min = min(new_bbox.X.Min, rgi->rrgi_RgnData);
    }

```

```
do
{
    rgi = rgi->rrgi_Next;
} while (rgi != NULL && r_intersection_test_table[rgi->rrgi_StateData]);
rgi_tail = rgi;
r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
new_bbox.X.Max = max(new_bbox.X.Max, rgi->rrgi_RgnData);
do
{
    rgi = rgi->rrgi_Next;
} while (rgi != NULL && !r_intersection_test_table[rgi-
>rrgi_StateData]);
}
#endif
    if (r_RgnBuf[dest_size - 2] == R_NEXT_IS_Y)
    {
        /*
         * We didn't output anything for these input rows. Rewind..
         */
        dest_size -= 2;
    }
    else
    {
        if (min_row < new_bbox.Y.Min)
            new_bbox.Y.Min = min_row;
        else if (min_row > new_bbox.Y.Max)
            new_bbox.Y.Max = min_row;
    }
}
/*
 * Now, we've completed using the growth list for constructing this
 * region. Therefore, we add it to the front of the free list, to
 * be re-used later.
 */
#ifdef R_NEW_IMP_CONSTRUCTION_LOOP
    while (rgi_tail->rrgi_Next != NULL)
        rgi_tail = rgi_tail->rrgi_Next;
#endif
rgi_tail->rrgi_Next = r_free_list;
r_free_list = r_growth_list;
r_growth_list = NULL;
/*
 * We've completed constructing the data for the region. Firstly
 * we check to see if we've emitted anything at all. If we have
 * then dest_size must be > 0. If it isn't we simply free the
 * region we created and get out, as the regions don't really
 * intersect, in spite of their intersecting bounding boxes.
 */
if (dest_size == 0)
{
    return TRUE;
}
/*
 * We make a copy the constructed data from the permanent buffer to
 * an exactly fitting buffer.
 */
rgn->rr_RgnData = (R_Int *)malloc(++dest_size * sizeof(R_Int));
if (rgn->rr_RgnData == NULL)
{
    return FALSE;
}
memcpy(rgn->rr_RgnData, r_RgnBuf, (dest_size - 1) * sizeof(R_Int));
rgn->rr_RgnData[dest_size - 1] = R_EOR;
rgn->rr_RgnDataSize = dest_size;
ASSERT(rgn->rr_RgnDataSize >= 9);
/*
 * Now, copy across the bounding box.. Before we do this, we subtract
 * 1 from X.Max and Y.Max because of the region format.
 */
```

```
    */
    new_bbox.X.Max--;
    new_bbox.Y.Max--;
    rgn->rr_BBox = new_bbox;
    /*
     * Done! We can get out..
     */
    return TRUE;
}

/*
 * r_difference_test_table
 *
 * A 16-int lookup table which when provided with an unsigned char
 * of the following form xxyy, will provide evaluate the key
 * state transition test of the difference construction loop.
 * Note that R_STATE_SIZE _must_ be 2 for this lookup table to
 * work.
 */
int r_difference_test_table[16] = {
    0, 1, 0, 0,
    1, 0, 1, 1,
    0, 1, 0, 0,
    0, 1, 0, 0
};

/*
 * R_difference
 *
 * This function inits a R_Region structure to represent the difference of
 * it's two arguments. It essentially calculates r1 - r2
 *
 * Parameters:
 *     rgn      A R_Region ptr representing the R_Region to be initied.
 *     r1      A R_Region ptr representing the first region.
 *     r2      A R_Region ptr representing the second region.
 * Returns
 *     TRUE on success, FALSE on failure.
 */
int
R_difference
(
    R_Region *rgn,
    R_Region *r1,
    R_Region *r2
)
{
    R_Int *r1_dat;
    R_Int *r2_dat;
    int overlap_flags;

    diff_tot++;

    rgn->rr_RgnData = NULL;
    if (!BB_intersect_test(&r1->rr_BBox, &r2->rr_BBox, &overlap_flags))
    {
        /*
         * The bounding boxes don't intersect. This means that r1 - r2
         * simply equals r1. We make a copy of the relevant bits and get out..
         */
        rgn->rr_BBox = r1->rr_BBox;
        rgn->rr_RgnDataSize = r1->rr_RgnDataSize;
        rgn->rr_RgnData = (R_Int *)malloc(r1->rr_RgnDataSize * sizeof(R_Int));
        if (rgn->rr_RgnData == NULL)
        {
            return FALSE;
        }
    }
}
```

```
memcpy
(
    rgn->rr_RgnData,
    r1->rr_RgnData,
    r1->rr_RgnDataSize * sizeof(R_Int)
);
return TRUE;
}
R_Int      min_row;
int        dest_size;
R_RgnGrowItem *rgi;
R_RgnGrowItem *rgi_tail;
int        in_run;
int        done_r1_in_row;
unsigned char m_high;
unsigned char m_low;
IntXYMinMax new_bbox;

diff_full++;

/*
 * The two regions _do_ overlap in x_and y. We therefore have
 * to do a bit more work in calculating the difference of the two
 * regions. We use the R_RegionBuilder struct to store state
 * regarding the currently active regions as we progress through
 * the rows of each region. After any rows relevant to a y-coord
 * are added to the region builder, we examine the state of each
 * pixel run in the region builder. If the addition of the row(s)
 * for the y-coord have caused the following transitions -
 *
 *      r1      -> 0
 *      0       -> r2
 *      r1 + r2 -> r2
 *      r2      -> r1 + r2
 * ..then the relevant runs are emitted. Firstly, though,
 * we ensure the current region builder is empty,
 * and set up pointers into the region data of the two regions.
 */
r1_dat = r1->rr_RgnData;
r2_dat = r2->rr_RgnData;
dest_size = 0;

/*
 * Initialise the new_bbox structure for determining the new bounding box.
 */
new_bbox.X.Min = 32767;
new_bbox.Y.Min = 32767;
new_bbox.X.Max = -32768;
new_bbox.Y.Max = -32768;

/*
 * We are now ready to loop through the data from both regions. Notice
 * that we only keep looping whilst r1 has data outstanding. When
 * r1's data is consumed, then any transitions made by r2 are
 * irrelevant.
 */
while (*r1_dat != R_EOR)
{
    ASSERT(*r1_dat == R_NEXT_IS_Y || *r1_dat == R_EOR);
    ASSERT(*r2_dat == R_NEXT_IS_Y || *r2_dat == R_EOR);
    if (*r1_dat == R_EOR)
        min_row = r2_dat[1];
    else if (*r2_dat == R_EOR)
        min_row = r1_dat[1];
    else
        min_row = min(r1_dat[1], r2_dat[1]);
    done_r1_in_row = FALSE;
    if (*r1_dat != R_EOR && r1_dat[1] == min_row)
    {
```

```
/*
 * The first region is active on this y coord. We add this
 * row to the current region builder.
 */
if (!R_add_row_to_region_growth_list(&r1_dat, 0x1, TRUE))
    return FALSE;
done_r1_in_row = TRUE;
}
if (*r2_dat != R_EOR && r2_dat[1] == min_row)
{
    /*
     * The first region is active on this y coord. We add this.
     * row to the current region builder.
     */
    if (!R_add_row_to_region_growth_list(&r2_dat, 0x2, !done_r1_in_row))
        return FALSE;
}
/*
 * Now, we generate the output row for the input rows.
 */
if (!r_check_rgn_buf_len(dest_size + 2))
{
    return FALSE;
}
r_RgnBuf[dest_size++] = R_NEXT_IS_Y;
r_RgnBuf[dest_size++] = min_row;
in_run = FALSE;
#ifdef R_NEW_IMP_CONSTRUCTION_LOOP
for (rgi = r_growth_list; rgi != NULL; rgi = rgi->rrgi_Next)
{
    #if 0
        m_high = (rgi->rrgi_StateData & RB_CUR_STATE_MASK) >> RB_STATE_SIZE;
        m_low = rgi->rrgi_StateData & RB_PREV_STATE_MASK;
        if
        (
            (m_low != 1 && m_high == 1)
            ||
            (m_low == 1 && m_high != 1)
        )
        #else
        if (r_difference_test_table[rgi->rrgi_StateData])
        #endif
        {
            /*
             * We have to emit a run here, if we're not already
             * in one..
             */
            if (!in_run)
            {
                if (!r_check_rgn_buf_len(dest_size + 1))
                {
                    return FALSE;
                }
                r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
                in_run = TRUE;
                new_bbox.X.Min = min(new_bbox.X.Min, rgi->rrgi_RgnData);
            }
        }
        else
        {
            if (in_run)
            {
                /*
                 * We've come to the end of a run. We output the next element
                 * to end it.
                 */
            }
        }
    }
}
```

```

        if (!r_check_rgn_buf_len(dest_size + 1))
        {
            return FALSE;
        }
        r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
        new_bbox.X.Max = max(new_bbox.X.Max, rgi->rrgi_RgnData);
    }
    in_run = FALSE;
}
/*
 * Not efficient, get rid of it..
 */
if (rgi->rrgi_Next == NULL)
    rgi_tail = rgi;
}
#else
    rgi = r_growth_list;
    rgi_tail = rgi;
    while (rgi != NULL && !r_difference_test_table(rgi->rrgi_StateData))
        rgi = rgi->rrgi_Next;
    while (rgi != NULL)
    {
        if (!r_check_rgn_buf_len(dest_size + 2))
            return FALSE;
        r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
        new_bbox.X.Min = min(new_bbox.X.Min, rgi->rrgi_RgnData);
        do
        {
            rgi = rgi->rrgi_Next;
        } while (rgi != NULL && r_difference_test_table(rgi->rrgi_StateData));
        rgi_tail = rgi;
        r_RgnBuf[dest_size++] = rgi->rrgi_RgnData;
        new_bbox.X.Max = max(new_bbox.X.Max, rgi->rrgi_RgnData);
        do
        {
            rgi = rgi->rrgi_Next;
        } while (rgi != NULL && !r_difference_test_table(rgi->rrgi_StateData));
    }
#endif
    if (r_RgnBuf[dest_size - 2] == R_NEXT_IS_Y)
    {
        /*
         * We didn't output anything for these input rows. Rewind..
         */
        dest_size -= 2;
    }
    else
    {
        if (min_row < new_bbox.Y.Min)
            new_bbox.Y.Min = min_row;
        else if (min_row > new_bbox.Y.Max)
            new_bbox.Y.Max = min_row;
    }
}
/*
 * Now, we've completed using the growth list for constructing this
 * region. Therefore, we add it to the front of the free list, to
 * be re-used later.
 */
#ifdef R_NEW_IMP_CONSTRUCTION_LOOP
    while (rgi_tail->rrgi_Next != NULL)
        rgi_tail = rgi_tail->rrgi_Next;
#endif
    rgi_tail->rrgi_Next = r_free_list;
    r_free_list = r_growth_list;
    r_growth_list = NULL;
/*
 * We've completed constructing the data for the region. Firstly

```



```

    * we check to see if we've emitted anything at all. If we have
    * then dest_size must be > 0. If it isn't we simply free the
    * region we created and get out, as r2 - r1 must be empty.
    */
    if (dest_size == 0)
    {
        return TRUE;
    }
    /*
    * We make a copy the constructed data from the permanent buffer to
    * an exactly fitting buffer.
    */
    rgn->rr_RgnData = (R_Int *)malloc(++dest_size * sizeof(R_Int));
    if (rgn->rr_RgnData == NULL)
    {
        return FALSE;
    }
    memcpy(rgn->rr_RgnData, r_RgnBuf, (dest_size - 1) * sizeof(R_Int));
    rgn->rr_RgnData[dest_size - 1] = R_EOR;
    rgn->rr_RgnDataSize = dest_size;
    ASSERT(rgn->rr_RgnDataSize >= 9);
    /*
    * Now, copy across the bounding box..
    */
    rgn->rr_BBox = new_bbox;
    /*
    * Done! We can get out..
    */
    return TRUE;
}
#endif /* R_USE_NEW_IMP */

/*
 * R_compare
 *
 * This function compares two regions and determines if they are the same.
 *
 * Parameters:
 *     rgn1    The first R_Region.
 *     rgn2    The second R_Region.
 * Returns:
 *     TRUE if they are the same, FALSE if they aren't.
 */
int
R_compare
(
    R_Region    *rgn1,
    R_Region    *rgn2
)
{
    /*
    * If their region data sizes don't agree, then they aren't the same.
    */
    if (rgn1->rr_RgnDataSize != rgn2->rr_RgnDataSize)
        return FALSE;
    if
    (
        memcmp
        (
            rgn1->rr_RgnData,
            rgn2->rr_RgnData,
            rgn1->rr_RgnDataSize * sizeof(R_Int)
        )
        ==
        0
    )
        return TRUE;
    return FALSE;
}
```

```
}

/*
 * r_check_rect_buf_len
 *
 * This function checks to see if the static rectangle buffer is large
 * enough. If it isn't then it is reallocated to make it large enough.
 *
 * Parameters:
 *     size The required size of the r_RectBuf array.
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
static int
r_check_rect_buf_len
(
    int        size
)
{
    ASSERT(size >= 0);
    if (size > r_RectBufSize)
    {
        int        new_buf_size;
        IntXYMinMax *new_buf;
        new_buf_size = max(size, r_RectBufSize * 2);
        new_buf = (IntXYMinMax *)malloc
            (new_buf_size * sizeof(IntXYMinMax)
            );
        if (new_buf == NULL)
            return FALSE;
        if (r_RectBuf != NULL)
        {
            memcpy(new_buf, r_RectBuf, r_RectBufSize * sizeof(IntXYMinMax));
            free(r_RectBuf);
        }
        r_RectBuf = new_buf;
        r_RectBufSize = new_buf_size;
    }
    return TRUE;
}

#ifdef R_USE_NEW_IMP
/*
 * R_rects_from_region
 *
 * This function returns a group of non-overlapping rectangles which
 * together constitute the region. The group of rectangles returned is
 * currently non-optimal as the function uses the R_RegionBuilder structure
 * to store state. A more specific data structure will be required to
 * make the rectangles produced more optimal.
 *
 * Parameters:
 *     rgn        The region from which a rectangle array is required.
 *     rects      A pointer to a pointer to a IntXYMinMax structure. Used
 *               to return the array.
 *     num_rects  A pointer to an int. Used to return the number of
 *               elements in the array.
 *     static_ok  This boolean arg is passed as TRUE if a pointer to
 *               the r_RectBuf is sufficient. This is TRUE if usefulness of
 *               the rectangle data obtained ends before the next call to
 *               R_rects_from_region (for any region). FALSE is passed if
 *               a newly malloced copy is required. Basically is TRUE is
 *               passed the pointer returned must _not_ be freed.
 * Returns:
 *     TRUE on success, FALSE on failure.
 */
int
R_rects_from_region
```

```
(
R_Region      *rgn,
IntXYMinMax  **rects,
int           *num_rects,
int           static_ok
)
(
R_Int      *rgn_data;
int        dest_index;
int        prev_y;
int        prev_x;
unsigned char *rgn_bld_stat;
R_Int      *rgn_bld_dat;
int        i;
int        in_run;

/*
 * Give "nice" defaults for return stuff in cause we fail..
 */
*rects = NULL;
*num_rects = 0;
/*
 * We grab a pointer to the region data for the region and ensure
 * that the current region builder is empty..
 */
rgn_data = rgn->rr_RgnData;
if (rgn_data == NULL)
/*
 * This is an empty region.. Get out..
 */
return TRUE;
ASSERT(*rgn_data == R_NEXT_IS_Y);
R_CurRB->rrb_Nels = 0;
/*
 * We add the first row of the region to the region builder. We also
 * store the y-coord of this first row.
 */
prev_y = rgn_data[1];
if (!R_add_row_to_region_builder(&rgn_data, 0x1, TRUE))
return FALSE;
ASSERT(*rgn_data == R_NEXT_IS_Y);
ASSERT(*rgn_data != R_EOR);
/*
 * We are now in a position to loop through the data of the region.
 * We continue until the region data runs out. Basically, we output
 * the runs in the current region builder out as rectangles. Using
 * x-coords from the region builder and y coords of the rows. Then,
 * we add then next row to the region builder.
 */
dest_index = 0;
while (*rgn_data != R_EOR)
{
    ASSERT(*rgn_data == R_NEXT_IS_Y);

    rgn_bld_stat = R_CurRB->rrb_StateData;
    rgn_bld_dat = R_CurRB->rrb_RgnData;
    in_run = FALSE;
    for (i = R_CurRB->rrb_Nels; i > 0; i--)
    {
        if ((*rgn_bld_stat & RB_CUR_STATE_MASK) > 0)
        {
            /*
             * We have to emit a run here, if we're not already
             * in one..
             */
            if (!in_run)
            {
                prev_x = *rgn_bld_dat;
            }
        }
    }
}
```

```
        in_run = TRUE;
    }
    else
    {
        if (in_run)
        {
            /*
             * We've come to the end of a run. We output the rectangle
             * right here..
             */
            if (!r_check_rect_buf_len(dest_index + 1))
                return FALSE;
            r_RectBuf[dest_index].X.Min = prev_x;
            r_RectBuf[dest_index].Y.Min = prev_y;
            r_RectBuf[dest_index].X.Max = *rgn_bld_dat - 1;
            r_RectBuf[dest_index++].Y.Max = rgn_data[1] - 1;
        }
        in_run = FALSE;
        rgn_bld_stat++;
        rgn_bld_dat++;
    }
    /*
     * Now, we advance onto the next row..
     */
    prev_y = rgn_data[1];
    if (!R_add_row_to_region_builder(&rgn_data, 0x1, TRUE))
        return FALSE;
}
/*
 * Ok, we have the array of rectangles sitting around. If static_ok
 * is TRUE then we simply set the return pointers and get out.
 * Otherwise, we need to malloc a copy of the r_RectBuf.
 */
*num_rects = dest_index;
if (static_ok)
{
    *rects = r_RectBuf;
}
else
{
    *rects = (IntXYMinMax *)malloc(dest_index * sizeof(IntXYMinMax));
    if (*rects == NULL)
        return FALSE;
    memcpy(*rects, r_RectBuf, dest_index * sizeof(IntXYMinMax));
}
return TRUE;
}
#else
/*
 * R_rects_from_region
 *
 * This function returns a group of non-overlapping rectangles which
 * together constitute the region. The group of rectangles returned is
 * currently non-optimal as the function uses the R_RegionBuilder structure
 * to store state. A more specific data structure will be required to
 * make the rectangles produced more optimal.
 *
 * Parameters:
 *     rgn        The region from which a rectangle array is required.
 *     rects      A pointer to a pointer to a IntXYMinMax structure. Used
 *               to return the array.
 *     num_rects  A pointer to an int. Used to return the number of
 *               elements in the array.
 *     static_ok  This boolean arg is passed as TRUE if a pointer to
 *               the r_RectBuf is sufficient. This is TRUE if usefulness of
 *               the rectangle data obtained ends before the next call to

```

```
*          R_rects_from_region (for any region). FALSE is passed if
*          a newly malloced copy is required. Basically is TRUE is
*          passed the pointer returned must _not_ be freed.
* Returns:
*          TRUE on success, FALSE on failure.
*/
int
R_rects_from_region
(
    R_Region      *rgn,
    IntXYMinMax   **rects,
    int           *num_rects,
    int           static_ok
)
{
    R_Int          *rgn_data;
    int            dest_index;
    R_RgnGrowItem  *rgi;
    R_RgnGrowItem  *rgi_tail;
    int            prev_y;
    int            prev_x;
    int            in_run;

    /*
     * Give "nice" defaults for return stuff in cause we fail..
     */
    *rects = NULL;
    *num_rects = 0;
    /*
     * We grab a pointer to the region data for the region and ensure
     * that the current region builder is empty..
     */
    rgn_data = rgn->rr_RgnData;
    if (rgn_data == NULL)
    /*
     * This is an empty region.. Get out..
     */
        return TRUE;
    ASSERT(*rgn_data == R_NEXT_IS_Y);
    /*
     * We add the first row of the region to the region builder. We also
     * store the y-coord of this first row.
     */
    prev_y = rgn_data[1];
    if (!R_add_row_to_region_growth_list(&rgn_data, 0x1, TRUE))
        return FALSE;
    ASSERT(*rgn_data == R_NEXT_IS_Y);
    ASSERT(*rgn_data != R_EOR);
    /*
     * We are now in a position to loop through the data of the region.
     * We continue until the region data runs out. Basically, we output
     * the runs in the current region builder out as rectangles. Using
     * x-coords from the region builder and y coords of the rows. Then,
     * we add then next row to the region builder.
     */
    dest_index = 0;
    while (*rgn_data != R_EOR)
    {
        ASSERT(*rgn_data == R_NEXT_IS_Y);

        in_run = FALSE;
        for (rgi = r_growth_list; rgi != NULL; rgi = rgi->rrgi_Next)
        {
            if ((rgi->rrgi_StateData & RB_CUR_STATE_MASK) > 0)
            {
                /*
                 * We have to emit a run here, if we're not already
                 * in one..

```

```
        */
        if (!in_run)
        {
            prev_x = rgi->rrgi_RgnData;
            in_run = TRUE;
        }
    }
    else
    {
        if (in_run)
        {
            /*
             * We've come to the end of a run. We output the rectangle
             * right here..
             */
            if (!r_check_rect_buf_len(dest_index + 1))
                return FALSE;
            r_RectBuf[dest_index].X.Min = prev_x;
            r_RectBuf[dest_index].Y.Min = prev_y;
            r_RectBuf[dest_index].X.Max = rgi->rrgi_RgnData - 1;
            r_RectBuf[dest_index++].Y.Max = rgn_data[1] - 1;
        }
        in_run = FALSE;
    }
    /*
     * Not efficient, get rid of it..
     */
    if (rgi->rrgi_Next == NULL)
        rgi_tail = rgi;
}
/*
 * Now, we advance onto the next row..
 */
prev_y = rgn_data[1];
if (!R_add_row_to_region_growth_list(&rgn_data, 0x1, TRUE))
    return FALSE;
}
/*
 * Now, we've completed using the growth list for constructing the
 * rect list. Therefore, we add it to the front of the free list, to
 * be re-used later.
 */
rgi_tail->rrgi_Next = r_free_list;
r_free_list = r_growth_list;
r_growth_list = NULL;
/*
 * Ok, we have the array of rectangles sitting around. If static_ok
 * is TRUE then we simply set the return pointers and get out.
 * Otherwise, we need to malloc a copy of the r_RectBuf.
 */
*num_rects = dest_index;
if (static_ok)
{
    *rects = r_RectBuf;
}
else
{
    *rects = (IntXYMinMax *)malloc(dest_index * sizeof(IntXYMinMax));
    if (*rects == NULL)
        return FALSE;
    memcpy(*rects, r_RectBuf, dest_index * sizeof(IntXYMinMax));
}
return TRUE;
}
#endif /* R_USE_NEW_IMP */

/*
 * R_translate_region
```

```
*
* This function simply translates a region by the delta provided.
*
* Parameters:
*   rgn      A ptr to the R_Region to be translated.
*   delta    An IntXY ptr representing the amount to translate
*            in x and y.
* Returns:
*   Nothing.
*/
void
R_translate_region
(
    R_Region    *rgn,
    IntXY       *delta
)
{
    R_Int    *rgn_data;
    BB_translate(&rgn->rr_BBox, delta);
    rgn_data = rgn->rr_RgnData;
    for (int i = 0; i < rgn->rr_RgnDataSize - 1; i++)
    {
        if (rgn_data[i] == R_NEXT_IS_Y)
        {
            i++;
            rgn_data[i] += + delta->Y;
            continue;
        }
        rgn_data[i] += delta->X;
    }
}

/*
* R_output_region_as_debug_string
*
* This function simply outputs a region's data using the debug string
* functionality.
*
* Parameters:
*   rgn_name  A string used to output a user-defined name for the
*            region.
*   rgn       The region to be output.
* Returns:
*   Nothing.
*/
void
R_output_region_as_debug_string
(
    char        *rgn_name,
    R_Region    *rgn
)
{
    char buffer[128];
    int    index;
    int    line_len;

    sprintf(buffer, "\n+Rgn : %s\n", rgn_name);
    OutputDebugString(buffer);
    if (rgn == NULL)
    {
        sprintf(buffer, "+----End %s (Empty)\n", rgn_name);
        OutputDebugString(buffer);
        return;
    }
    sprintf
    (
        buffer,
        "+----BBox: (%d, %d, %d, %d)\n",

```

```
    rgn->rr_BBox.X.Min,
    rgn->rr_BBox.Y.Min,
    rgn->rr_BBox.X.Max,
    rgn->rr_BBox.Y.Max
);
OutputDebugString(buffer);
sprintf(buffer, "+----Nels: %d\n", rgn->rr_RgnDataSize);
OutputDebugString(buffer);
sprintf(buffer, "+----Data: ...");
OutputDebugString(buffer);
for (index = 0; index < rgn->rr_RgnDataSize; index++)
{
    if (rgn->rr_RgnData[index] == R_NEXT_IS_Y)
    {
        sprintf(buffer, "\n|           Y:%3d--> ", rgn->rr_RgnData[++index]);
        line_len = strlen(buffer);
        OutputDebugString(buffer);
    }
    else if (rgn->rr_RgnData[index] == R_EOR)
    {
        sprintf(buffer, "\n+----End %s\n", rgn_name);
        OutputDebugString(buffer);
    }
    else
    {
        sprintf(buffer, "%3d, ", rgn->rr_RgnData[index]);
        if (strlen(buffer) + line_len > 80)
        {
            OutputDebugString("\n|           ");
            line_len = strlen("\n|           ");
        }
        OutputDebugString(buffer);
        line_len += strlen(buffer);
    }
}
}

#define NUM_ITERATIONS    200

int
R_test_new_region_arithmetic()
{
    R_Region      rgn1;
    R_Region      rgn2;
    R_Region      rgn3;
    R_Region      rgn4;
    R_Region      rgn5;
    R_Region      rgn6;
    IntXYMinMax   rect;
    int           i;
    IntXY          delta;
    char          buf[256];
    unsigned long  ticks_new;
    unsigned long  ticks_old;

    #if 0
    /*
     * Union Test.
     */
    ticks_new = GetTickCount();
    rect.X.Min = 50;
    rect.Y.Min = 50;
    rect.X.Max = 100;
    rect.Y.Max = 100;
    if (!R_init_region_with_rect(&rgn1, &rect))
        return FALSE;
    rect.X.Min = 70;
    rect.Y.Min = 70;
```



```
rect.X.Max = 120;
rect.Y.Max = 120;
if (!R_init_region_with_rect(&rgn2, &rect))
    return FALSE;
if (!R_union_list_equals(&rgn1, &rgn2))
    return FALSE;
delta.X = 5;
delta.Y = 5;
for (i = 0; i < NUM_ITERATIONS; i++)
{
    R_translate_region(&rgn2, &delta);
    if (!R_union_list_equals(&rgn1, &rgn2))
        return FALSE;
}
ticks_new = GetTickCount() - ticks_new;

ticks_old = GetTickCount();
rect.X.Min = 50;
rect.Y.Min = 50;
rect.X.Max = 100;
rect.Y.Max = 100;
if (!R_init_region_with_rect(&rgn3, &rect))
    return FALSE;
rect.X.Min = 70;
rect.Y.Min = 70;
rect.X.Max = 120;
rect.Y.Max = 120;
if (!R_init_region_with_rect(&rgn4, &rect))
    return FALSE;
if (!R_union_equals(&rgn3, &rgn4))
    return FALSE;
delta.X = 5;
delta.Y = 5;
for (i = 0; i < NUM_ITERATIONS; i++)
{
    R_translate_region(&rgn4, &delta);
    if (!R_union_equals(&rgn3, &rgn4))
        return FALSE;
}
ticks_old = GetTickCount() - ticks_old;

if (R_compare(&rgn1, &rgn3))
    sprintf(buf, "New & Old Region Implementations match.\n");
else
    sprintf(buf, "New & Old Region Implementations DO NOT match.\n");
OutputDebugString(buf);
sprintf(buf, "Union Timings - New=%d vs Old=%d\n", ticks_new, ticks_old);
OutputDebugString(buf);
//R_output_region_as_debug_string("New Region Description", &rgn1);
//R_output_region_as_debug_string("Old Region Description", &rgn3);

/*
 * Intersection Test.
 */
R_empty_region(&rgn2);
R_empty_region(&rgn4);
rect.X.Min = 70;
rect.Y.Min = 70;
rect.X.Max = 120;
rect.Y.Max = 120;
if (!R_init_region_with_rect(&rgn2, &rect))
    return FALSE;
delta.X = 5;
delta.Y = 5;
for (i = 0; i < NUM_ITERATIONS; i++)
{
    if (!R_intersection_list(&rgn5, &rgn1, &rgn2))
        return FALSE;
}
```

```
    if (!R_intersection(&rgn6, &rgn3, &rgn2))
        return FALSE;
    if (!R_compare(&rgn5, &rgn6))
    {
        sprintf(buf, "New & Old Region Implementations DO NOT match.\n");
        OutputDebugString(buf);
    }
    R_empty_region(&rgn5);
    R_empty_region(&rgn6);
    R_translate_region(&rgn2, &delta);
}

ticks_new = GetTickCount();
R_empty_region(&rgn2);
rect.X.Min = 70;
rect.Y.Min = 70;
rect.X.Max = 120;
rect.Y.Max = 120;
if (!R_init_region_with_rect(&rgn2, &rect))
    return FALSE;
delta.X = 5;
delta.Y = 5;
for (i = 0; i < NUM_ITERATIONS; i++)
{
    if (!R_intersection_list(&rgn5, &rgn1, &rgn2))
        return FALSE;
    R_empty_region(&rgn5);
    R_translate_region(&rgn2, &delta);
}
ticks_new = GetTickCount() - ticks_new;

ticks_old = GetTickCount();
R_empty_region(&rgn2);
rect.X.Min = 70;
rect.Y.Min = 70;
rect.X.Max = 120;
rect.Y.Max = 120;
if (!R_init_region_with_rect(&rgn2, &rect))
    return FALSE;
delta.X = 5;
delta.Y = 5;
for (i = 0; i < NUM_ITERATIONS; i++)
{
    if (!R_intersection(&rgn6, &rgn3, &rgn2))
        return FALSE;
    R_empty_region(&rgn6);
    R_translate_region(&rgn2, &delta);
}
ticks_old = GetTickCount() - ticks_old;

sprintf(buf, "Intersection Timings - New=%d vs Old=%d\n", ticks_new, ticks_old);
OutputDebugString(buf);
//R_output_region_as_debug_string("New Region Description", &rgn1);
//R_output_region_as_debug_string("Old Region Description", &rgn3);

R_empty_region(&rgn1);
R_empty_region(&rgn2);
R_empty_region(&rgn3);
R_empty_region(&rgn4);
OutputDebugString("Done!!\n");
#endif
return TRUE;
}
```

The claims defining the invention are as follows:

1. A method of creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said method comprising the steps of:

dividing a space in which said outlines are defined into a plurality of mutually exclusive regions wherein each of said regions is defined by a region outline substantially following at least one of said predetermined outlines or parts thereof;

examining each said region to determine those said objects which contribute to said region;

modifying said compositing expression on the basis of the contribution of each of said objects within said region to form an optimized compositing expression for each said region; and

compositing said image using each of said optimized compositing expressions.

2. A method according to claim 1, further comprising the step of approximating each said predetermined outline on the outside and the inside to form an outline region.

3. A method according to claims 2, wherein each said outline region is approximated to a grid.

4. A method according to claim 3, wherein said examining comprises determining whether or not an opacity of each said object within the corresponding region has non-zero opacity.

5. A method according to claim 4, wherein said region outline is further defined by at least one attribute of at least one said object within the corresponding region.

6. A method according to claim 5, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

7. A method according to any one of claims 1 to 6, wherein the compositing expression is a hierarchically structured representation of the image.

8. A method according to any one of claims 1 to 7, wherein said image is at least in part a pixel-based image.

9. A method according to any one of the preceding claims, wherein a flag is stored to indicate whether data of an object is opaque or ordinary.

10. A method according to claim 9, wherein said compositing expression is optimized based on a value of said flag for contributing objects.

11. A method according to any one of the preceding claims, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expressions.

12. A method according to any one of the preceding claims, wherein a wholly transparent object in said region eliminates at least itself from said compositing expression.

13. A method according to any one of claims 1 to 12, wherein said modifying comprises modifying a manner in which said compositing expression is evaluated without modifying said hierarchically structured representation.

14. A method of creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said method comprising the steps of:

dividing a space in which said outlines are defined into a plurality of mutually exclusive regions;

examining each said region to determine those said objects which contribute to said region;

modifying said compositing expression on the basis of the contribution of each of said objects within said region; and

compositing said image using said modified compositing expression.

15. A method according to claim 14, wherein each of said regions is defined by a region outline substantially formed of at least one of said predetermined outlines or parts thereof.

16. A method according to claim 14, further comprising the step of approximating each said predetermined outline on the outside and the inside to form an outline region.

10

17. A method according to claim 16, wherein each said outline region is approximated to a grid.

18. A method according to any one of claims 14 to 17, wherein modifying said compositing expression forms an optimized compositing expression.

15

19. A method according to any one of claims 14 to 18, wherein said examining comprises determining whether or not an opacity of each said object within the corresponding region has non-zero opacity.

20

20. A method according to any one of claims 15 to 19, wherein said region outline is further defined by at least one attribute of at least one said object within said corresponding region.

25

21. A method according to claim 20, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

22. A method according to any one of claims 14 to 21, wherein the compositing expression is a hierarchical structure representation of the image.

30

23. A method according to any one of claims 14 to 22, wherein said image is at least in part a pixel-based image.

24. A method according to any one of claims 14 to 23, wherein a flag is stored to indicate whether data of an object is opaque or ordinary.

25. A method according to claim 24, wherein said compositing expression is optimized based on a value of said flag for contributing objects.

26. A method according to any one of claims 14 to 25, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expression.

10

27. A method according to any one of claims 14 to 26, wherein a wholly transparent object eliminates at least itself from said compositing expression.

28. A method according to any one of claims 14 to 27, wherein said modifying comprises modifying a manner in which said compositing expression is evaluated without modifying said hierarchical structure representation.

15

29. A method of creating an image, said image comprising a plurality of graphical objects to be composited according to a compositing expression, said method comprising the steps of:

20

dividing a space in which said graphical objects are defined into a plurality of regions;

examining each said region to determine those said objects which contribute to said region;

25

modifying said compositing expression on the basis of said examination; and compositing said image using said modified compositing expression.

30. A method according to claim 29, wherein each said object has a predetermined outline.

30

31. A method according to claims 29 or 30, wherein said regions are mutually exclusive.

32. A method according to any one of claims 30 or 31, further comprising the step of approximating each said predetermined outline on the outside and the inside to form an outline region.

5 33. A method according to claim 32, wherein each said outline region is approximated to a grid.

34. A method according to any one of claims 29 to 33, wherein said compositing expression is modified on the basis of the contribution of each of said
10 objects within each said region.

35. A method according to any one of claims 29 to 34, wherein each of said regions is defined by a region outline substantially formed of at least one of said predetermined outlines or parts thereof.
15

36. A method according to any one of claims 29 to 35, wherein modifying said compositing expression forms an optimized compositing expression.

37. A method according to any one of claims 29 to 36, wherein said
20 examining comprises determining whether or not an opacity of each said object within the corresponding region has non-zero opacity.

38. A method according to any one of claims 35 to 37, wherein said region outline is further defined by at least one attribute of at least one said object within the
25 corresponding region.

39. A method according to claim 38, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

30 40. A method according to any one of claims 29 to 39, wherein the compositing expression is a hierarchical structured representation of the image.

41. A method according to any one of claims 29 to 40, wherein said image is at least in part a pixel-based image component.

42. A method according to any one of claims 29 to 41, wherein a flag is stored to indicate whether data of an object is opaque or ordinary.

5 43. A method according to claim 42, wherein said compositing expression is optimized based on a value of said flag for contributing objects.

44. A method according to any one of claims 29 to 43, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from
10 said compositing expression.

45. A method according to any one of claims 29 to 44, wherein a wholly transparent object in said region eliminates at least itself from compositing expression.

15 46. A method according to any one of claims 29 to 45, wherein said modifying comprises modifying a manner in which said compositing expression is evaluated without modifying said hierarchical structured representation.

20 47. An apparatus for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said apparatus comprising:

25 dividing means for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions wherein each of said regions is defined by a region outline substantially following at least one of said predetermined outlines or parts thereof;

examining means for examining each said region to determine those said objects which contribute to said region;

30 modifying means for modifying said compositing expression on the basis of the contribution of each of said objects within said region to form an optimized compositing expression for each said region; and

compositing means for compositing said image using each of said optimized compositing expressions.

48. An apparatus according to claim 47, further comprising approximating means for approximating each said predetermined outline on the outside and the inside to form an outline region.

5 49. An apparatus according to claims 48, wherein each said outline region is approximated to a grid.

50. An apparatus according to claim 49, wherein said examining comprises determining whether or not an opacity of each said object within the corresponding region
10 has non-zero opacity.

51. An apparatus according to claim 50, wherein said region outline is further defined by at least one attribute of at least one said object within the corresponding region.
15

52. An apparatus according to claim 51, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

53. An apparatus according to any one of claims 47 to 52, wherein the compositing expression is a hierarchically structured representation of the image.
20

54. An apparatus according to any one of claims 47 to 53, wherein said image is at least in part a pixel-based image.

25 55. An apparatus according to any one of claims 47 to 54, wherein a flag is stored to indicate whether data of an object is opaque or ordinary.

56. An apparatus according to claim 55, wherein said compositing expression is optimized based on a value of said flag for contributing objects.
30

57. An apparatus according to any one of claims 47 to 56, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expressions.

58. An apparatus according to any one of claims 47 to 57, wherein a wholly transparent object in said region eliminates at least itself from said compositing expression.

5 59. An apparatus according to any one of claims 47 to 58, wherein said modifying comprises modifying a manner in which said compositing expression is evaluated without modifying said hierarchically structured representation.

10 60. An apparatus for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said apparatus comprising:

dividing means for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions;

15 examining means for examining each said region to determine those said objects which contribute to said region;

modifying means for modifying said compositing expression on the basis of the contribution of each of said objects within said region; and

20 compositing means for compositing said image using said modified compositing expression.

25 61. An apparatus according to claim 60, wherein each of said regions is defined by a region outline substantially formed of at least one of said predetermined outlines or parts thereof.

62. An apparatus according to claim 60, further comprising approximating means for approximating each said predetermined outline on the outside and the inside to form an outline region.

30 63. An apparatus according to claim 62, wherein each said outline region is approximated to a grid.

64. An apparatus according to any one of claims 60 to 63, wherein modifying said compositing expression forms an optimized compositing expression.

65. An apparatus according to any one of claims 60 to 64, wherein said examining comprises determining whether or not an opacity of each said object within the corresponding region has non-zero opacity.

5

66. An apparatus according to any one of claims 61 to 65, wherein said region outline is further defined by at least one attribute of at least one said object within said corresponding region.

10

67. An apparatus according to claim 66, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

68. An apparatus according to any one of claims 60 to 67, wherein the compositing expression is a hierarchical structure representation of the image.

15

69. An apparatus according to any one of claims 60 to 68, wherein said image is at least in part a pixel-based image.

20

70. An apparatus according to any one of claims 60 to 69, wherein a flag is stored to indicate whether data of an object is opaque or ordinary.

71. An apparatus according to claim 70, wherein said compositing expression is optimized based on a value of said flag for contributing objects.

25

72. An apparatus according to any one of claims 60 to 71, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expression.

30

73. An apparatus according to any one of claims 60 to 72, wherein a wholly transparent object eliminates at least itself from said compositing expression.

74. An apparatus according to any one of claims 60 to 73, wherein said modifying comprises modifying a manner in which said compositing expression is evaluated without modifying said hierarchical structure representation.

75. An apparatus for creating an image, said image comprising a plurality of graphical objects to be composited according to a compositing expression, said apparatus comprising:

5 dividing means for dividing a space in which said graphical objects are defined into a plurality of regions;

 examining means for examining each said region to determine those said objects which contribute to said region;

 modifying means for modifying said compositing expression on the basis of said
10 examination; and

 compositing means for compositing said image using said modified compositing expression.

76. An apparatus according to claim 75, wherein each said object has a
15 predetermined outline.

77. An apparatus according to claims 75 or 76, wherein said regions are mutually exclusive.

20 78. An apparatus according to any one of claims 76 or 77, further comprising approximating means for approximating each said predetermined outline on the outside and the inside to form an outline region.

25 79. An apparatus according to claim 78, wherein each said outline region is approximated to a grid.

80. An apparatus according to any one of claims 75 to 79, wherein said compositing expression is modified on the basis of the contribution of each of said objects within each said region.

30

81. An apparatus according to any one of claims 75 to 80, wherein each of said regions is defined by a region outline substantially formed of at least one of said predetermined outlines or parts thereof.

82. An apparatus according to any one of claims 75 to 81, wherein modifying said compositing expression forms an optimized compositing expression.

83. An apparatus according to any one of claims 75 to 82, wherein said
5 examining comprises determining whether or not an opacity of each said object within the corresponding region has non-zero opacity.

84. An apparatus according to any one of claims 81 to 83, wherein said
10 region outline is further defined by at least one attribute of at least one said object within the corresponding region.

85. An apparatus according to claim 84, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

86. An apparatus according to any one of claims 75 to 85, wherein the
15 compositing expression is a hierarchical structured representation of the image.

87. An apparatus according to any one of claims 75 to 86, wherein said
image is at least in part a pixel-based image component.

88. An apparatus according to any one of claims 75 to 87, wherein a flag is
20 stored to indicate whether data of an object is opaque or ordinary.

89. An apparatus according to claim 88, wherein said compositing expression
25 is optimized based on a value of said flag for contributing objects.

90. An apparatus according to any one of claims 75 to 81, wherein a wholly
opaque object in said region acts to eliminate one or more objects within said region from
said compositing expression.

30

91. An apparatus according to any one of claims 75 to 90, wherein a wholly
transparent object in said region eliminates at least itself from compositing expression.

92. An apparatus according to any one of claims 75 to 91, wherein said modifying comprises modifying a manner in which said compositing expression is evaluated without modifying said hierarchical structured representation.

- 5 93. A method of creating a series of images, each member of said series being related to a preceding member, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure representing a compositing expression, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a
- 10 predetermined outline, said method comprising the steps of:
- (a) for each said node:
 - (i) dividing a component image space in which said outlines are defined into at least one mutually exclusive region, each said region being related to at least one graphical object;
 - 15 (ii) examining each said region to determine those objects that contribute to the region;
 - (b) creating internodal dependency information identifying those said regions that will be affected by a change in any one of said regions;
 - (c) rendering a first image of said series by compositing all regions
 - 20 substantially according to said hierarchical structure;
 - (d) in response to at least one change to at least one of said nodes;
 - (i) examining said internodal dependency information to identify those of said regions affected by said at least one change;
 - (ii) for each node with affected regions, updating the corresponding
 - 25 identified regions and incorporating into said node those (any) new regions arising from the change and/or removing any of said regions that are no longer relevant;
 - (iii) updating said internodal dependency information to reflect changes to said hierarchical structure;
 - (iv) rendering a further image of said series by compositing (only)
 - 30 those regions affected by said at least one change; and
 - (e) repeating step (d) for further changes to at least one of said nodes.

94. A method according to claim 93, further comprising the step of approximating each said predetermined outline on the outside and the inside to form an outline region.

5 95. A method according to claim 94, wherein each said outline region is approximated to a grid.

96. A method according to claim 93, wherein step (a)(ii) includes examining each said region to determine an opacity of each of said objects within said region.

10

97. A method according to any one of claims 95 to 96, wherein said internodal dependency information is created for each of said regions.

15 98. A method according to any one of claims 93, 96 or 97, wherein said internodal dependency information includes:

a first internodal dependency list identifying those regions directly affected by a change to said one region; and

a second internodal dependency list identifying those regions indirectly affected by a change in said one region.

20

99. A method according to any one of claims 97 or 98, wherein directly affected regions are those regions having content modified as a consequence of change.

25 100. A method according to any one of claims 97 to 99, wherein indirectly affected regions are those regions which may include modified region outlines and/or content generation as a result of change.

30 101. A method according to any one of claims 95 to 100, wherein said region outline is further defined by at least one attribute of at least one said object within the corresponding region.

102. A method according to claim 101, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

103. A method according to any one of claims 93 to 102, wherein said updating include functions selected from the group consisting of deleting regions, altering the boundaries or regions.

5 104. A method according to any one of claims 93 to 103, wherein at least one change includes changing the attributes of nodes in said hierarchical structure.

10 105. A method according to any one of claims 93 to 104, wherein new regions can be added to said hierarchical structure as a result of said at least one change to at least one of said nodes.

15 106. A method according to any one of claims 93 to 105, wherein said image is at least in part a pixel-based image.

20 107. A method according to any one of claims 93 to 106, wherein each of said mutually exclusive regions include a descriptor which represents an outline of said mutually exclusive region.

25 108. A method according to any one of claims 93 to 107, wherein each of said regions includes a region descriptor which represents a union of all region descriptors of said node.

30 109. A method according to any one of claims 93 to 108, wherein each of said regions is represented by a single proxy that provides for the reproduction of pixel data.

 110. A method according to claim 109, wherein a flag is stored within each said proxy to indicate whether data in that region is opaque or ordinary.

 111. A method according to claim 110, wherein said compositing expression is optimized based on a value of said flag.

 112. A method according to any one of claims 93 to 111, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expressions.

113. A method according to any one of claims 93 to 112, wherein a wholly transparent object in said region eliminates at least itself from said composition expression.

5

114. A method of creating a series of images, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a predetermined outline, said method comprising the steps of:

10

(a) for each said node:

(iii) dividing a space in which said outlines are defined into at least one mutually exclusive region;

15

(iv) examining each said region to determine those objects that contribute to the region;

(b) creating internodal dependency information based on said examination;

(c) rendering a first image of said series utilising said hierarchical structure; and then, in response to at least one change to at least one of said nodes;

(d) examining said internodal dependency information;

20

(i) for a node with affected regions, updating the corresponding regions;

(ii) updating said internodal dependency information;

(iii) rendering a further image of said series by compositing those regions affected by said at least one change; and

25

(e) repeating step (d) for further changes to at least one of said nodes.

115. A method according to claim 114, further comprising the step of approximating each said predetermined outline on the outside and the inside to form an outline region.

30

116. A method according to claim 115, wherein each said outline region is approximated to a grid.

117. A method according to claim 115, wherein each member of said series of images is related to a preceding member.

118. A method according to any one of claims 116 or 117, wherein each said
5 region is related to at least one graphical object.

119. A method according to any one of claims 114 to 118, wherein rendering of said first image is executed by compositing all regions of said hierarchical structure.

10 120. A method according to any one of claims 114 to 119, wherein said examining of said internodal dependency information identifies those of said regions affected by said at least one change.

121. A method according to any one of claims 114 to 120, wherein said
15 updating of said internodal dependency information reflects changes to said hierarchical structure.

122. A method according to any one of claims 114 to 121, wherein step (a)(ii) includes examining each said region to determine an opacity of each of said objects
20 within said region.

123. A method according to any one of claims 114 to 122, wherein said internodal dependency information is created for each of said regions.

25 124. A method according to any one of claims 114 or 123, wherein said internodal dependency information includes:

a first internodal dependency list identifying those regions directly affected by a change to said one region; and

a second internodal dependency list identifying those regions indirectly affected
30 by a change in said one region.

125. A method according to claim 123, wherein directly affected regions are those regions having content modified as a consequence of change.

126. A method according to any one of claims 123 to 125, wherein indirectly affected regions are those regions which may include modified region outlines and/or content generation as a result of change.

5 127. A method according to any one of claims 114 to 126, wherein said region outline is further defined by at least one attribute of at least one said object within the corresponding region.

128. A method according to claim 127, wherein said attribute is selected from
10 the group consisting of colour, opacity and object outline.

125. A method according to any one of claims 114 to 128, wherein said
updating include functions selected from the group consisting of deleting regions, altering
the boundaries or regions.
15

130. A method according to any one of claims 114 to 128, wherein at least one
change includes changing the attributes of nodes in said hierarchical structure.

131. A method according to any one of claims 114 to 130, wherein new
20 regions can be added to said hierarchical structure as a result of said at least one change to
at least one of said nodes.

132. A method according to any one of claims 114 to 131, wherein said image
is at least in part a pixel-based image.
25

133. A method according to any one of claims 114 to 132, wherein each of
said mutually exclusive regions include a descriptor which represents an outline of said
mutually exclusive region.

30 134. A method according to any one claims 119 to 133, wherein each of said
regions includes a region descriptor which represents a union of all region descriptors of
said node.

135. A method according to any one claims 114 to 134, wherein each of said regions is represented by a single proxy that provides for the reproduction of pixel data.

136. A method according to claim 135, wherein a flag is stored within each
5 said proxy to indicate whether data in that region is opaque or ordinary.

137. A method according to claim 136, wherein said compositing expression is optimized based on a value of said flag.

10 138. A method according to any one of claims 113 to 135, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expressions.

139. A method according to any one of claims 113 to 136, wherein a wholly transparent object in said region eliminates at least itself from said composition
15 expression.

140. A method of creating a series of images, said images being formed by rendering at least a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each
20 representing a component of at least one of said images, said method comprising the steps of:

- (a) for each said node:
 - (i) dividing a component image space in which said graphical objects are defined into at least one region;
 - 25 (ii) examining each said region;
- (b) creating internodal dependency information for each of said regions;
- (c) rendering a first image of said series utilising said hierarchical structure; and then, in response to at least one change to at least one of said nodes;
- (d) examining said internodal dependency information;
30 (i) for a node with affected regions, updating the corresponding information;
- (ii) updating said internodal dependency record;
- (iii) rendering a further image of said series; and
- (e) repeating step (d) for further changes to at least one of said nodes.

141. A method according to claim 140, wherein each of said objects has a predetermined outline.

5 142. A method according to claim 141, further comprising the step of approximating each said predetermined outline on the outside and the inside to form an outline region.

10 143. A method according to claim 142, wherein each said outline region is approximated to a grid.

144. A method according to any one of claims 140 to 143, wherein said regions are mutually exclusive.

15 145. A method according to any one of claims 140 to 144, wherein said rendering a further image of said series is executed by compositing those regions affected by said at least one change.

20 146. A method according to any one of claims 140 to 144, wherein each member of said series of images is related to a preceding member.

147. A method according to any one of claims 140 to 146, wherein each said region is related to at least one graphical object.

25 148. A method according to any one of claims 140 to 147, wherein rendering of said first image is executed by compositing all regions of said hierarchical structure.

30 149. A method according to any one of claims 140 to 148, wherein said examining of said internodal dependency information identifies those of said regions affected by said at least one change.

150. A method according to any one of claims 140 to 149, wherein said updating of said internodal dependency information reflects changes to said hierarchical structure.

151. A method according to any one of claims 140 to 150, wherein step (a)(ii) includes examining each said region to determine an opacity of each of said objects within said region.

5

152. A method according to any one of claims 140 to 151, wherein said intermodal dependency information is created for each of said regions.

10 153. A method according to any one of claims 140 to 152, wherein said intermodal dependency information includes:

a first intermodal dependency list identifying those regions directly affected by a change to said one region; and

a second intermodal dependency list identifying those regions indirectly affected by a change in said one region.

15

154. A method according to any one of claims 152 to 153, wherein directly affected regions are those regions having content modified as a consequence of change.

20 155. A method according to any one of claims 152, wherein indirectly affected regions are those regions which may include modified region outlines and/or content generation as a result of change.

25 156. A method according to any one of claims 140 to 155, wherein said region outline is further defined by at least one attribute of at least one said object within the corresponding region.

157. A method according to claim 156, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

30 158. A method according to any one of claims 140 to 157, wherein said updating include functions selected from the group consisting of deleting regions, altering the boundaries or regions.

159. A method according to any one of claims 140 to 158, wherein at least one change includes changing the attributes of nodes in said hierarchical structure.

5 160. A method according to any one of claims 140 to 159, wherein new regions can be added to said hierarchical structure as a result of said at least one change to at least one of said nodes.

10 161. A method according to any one of claims 140 to 160, wherein said image is at least in part a pixel-based image.

162. A method according to any one of claims 140 to 161, wherein each of said mutually exclusive regions include a descriptor which represents an outline of said mutually exclusive region.

15 163. A method according to any one claims 140 to 161, wherein each of said regions includes a region descriptor which represents a union of all region descriptors of said node.

20 164. A method according to any one claims 140 to 163, wherein each of said regions is represented by a single proxy that provides for the reproduction of pixel data.

165. A method according to claim 164, wherein a flag is stored within each said proxy to indicate whether data in that region is opaque or ordinary.

25 166. A method according to claim 165, wherein said compositing expression is optimized based on a value of said flag.

30 167. A method according to any one of claims 140 to 166, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expressions.

168. A method according to any one of claims 140 to 167, wherein a wholly transparent object in said region eliminates at least itself from said composition expression.

169. An apparatus for creating a series of images, each member of said series being related to a preceding member, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure representing a
5 compositing expression, said hierarchical structure including a plurality of nodes each representing a component of at least of one of said images, each of said objects having a predetermined outline, said apparatus comprising:

dividing means for dividing a component image space in which said outlines are defined , for each said node, into at least one mutually exclusive region, each said region
10 being related to at least one graphical object ;

first examining means for examining each said region, for each said node, to determine those objects that contribute to the region;

creating means for creating an internodal dependency information identifying those said regions that will be affected by a change in any one of said regions;

15 rendering means for rendering a first image of said series by compositing all regions substantially according to said hierarchical structure;

second examining means for examining said internodal dependency information to identify those of said regions affected by at least one change to at least one of said nodes;

20 first updating means for updating the corresponding identified regions for each node with affected regions and incorporating into said node those (any) new regions arising from the change;

second updating means for updating said internodal dependency information to reflect changes to said hierarchical structure; and

25 rendering means for rendering a further image of said series by compositing (only) those regions affected by said at least one change.

170. An apparatus according to claim 169, further comprising an approximating means for approximating each said predetermined outline on the outside
30 and the inside to form an outline region.

171. An apparatus according to claim 170, wherein each said outline region is approximated to a grid.

172. An apparatus according to claim 169, wherein said first examining means examines each said region to determine an opacity of each of said objects within said region.

5 173. An apparatus according to anyone of claims 169 to 172, wherein said internodal dependency information is created for each of said regions.

174. An apparatus according to any one of claims 169 or 173, wherein said internodal dependency information includes:

10 a first internodal dependency list identifying those regions directly affected by a change to said one region; and

 a second internodal dependency list identifying those regions indirectly affected by a change in said one region.

15 175. An apparatus according to claim 173, wherein directly affected regions are those regions having content modified as a consequence of change.

176. An apparatus according to any one of claims 173, wherein indirectly affected regions are those regions which may include modified region outlines and/or
20 content generation as a result of change.

177. An apparatus according to any one of claims 169 to 172, wherein said region outline is further defined by at least one attribute of at least one said object within the corresponding region.

25

178. An apparatus according to claim 177, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

30 179. An apparatus according to any one of claims 167 to 178, wherein said updating the corresponding identified regions include functions selected from the group consisting of deleting regions and altering the boundaries of regions.

180. An apparatus according to any one of claims 169 to 179, wherein at least one change includes changing the attributes of nodes in said hierarchical structure.

181. An apparatus according to any one of claims 169 to 180, wherein new regions can be added to said hierarchical structure as a result of said at least one change to at least one of said nodes.

5

182. An apparatus according to any one of claims 169 to 181, wherein said image is at least in part a pixel-based image.

183. An apparatus according to any one of claims 169 to 182, wherein each of
10 said mutually exclusive regions include a descriptor which represents an outline of said mutually exclusive region.

184. An apparatus according to any one of claims 169 to 183, wherein each of
15 said regions includes a region descriptor which represents a union of all region descriptors of said node.

185. An apparatus according to any one of claims 169 to 184, wherein each of
20 said regions is represented by a single proxy that provides for the reproduction of pixel data.

186. An apparatus according to claim 185, wherein a flag is stored within each
said proxy to indicate whether data in that region is opaque or ordinary.

187. An apparatus according to claim 186, wherein said compositing
25 expression is optimized based on a value of said flag.

188. An apparatus according to any one of claims 169 to 187, wherein a
wholly opaque object in said region acts to eliminate one or more objects within said
region from said compositing expressions.

30

189. An apparatus according to any one of claims 169 to 188, wherein a
wholly transparent object in said region eliminates at least itself from said composition
expression.

190. An apparatus for creating a series of images, said images being formed by rendering at least a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a predetermined outline, said apparatus comprising:

5 dividing means for dividing a space in which said outlines are defined, for each said node, into at least one mutually exclusive region;

first examining means for examining each said region, for each said node, to determine those objects that contribute to the region;

10 creating means for creating internodal dependency information based on said examination;

rendering means for rendering a first image of said series utilising said hierarchical structure; and

15 second examining means for examining said internodal dependency information in response to at least one change to at least one of said nodes and, for a node with affected regions, updating the corresponding regions, updating said internodal dependency information and, rendering a further image of said series by compositing those regions affected by said at least one change.

20 191. An apparatus according to claim 190, further comprising an approximating means for approximating each said predetermined outline on the outside and the inside to form an outline region.

25 192. An apparatus according to claim 191, wherein each said outline region is approximated to a grid.

193. An apparatus according to claim 190, wherein each member of said series of images is related to a preceding member.

30 194. An apparatus according to any one of claims 192 or 193, wherein each said region is related to at least one graphical object.

195. An apparatus according to any one of claims 190 to 194, wherein rendering of said first image is executed by compositing all regions of said hierarchical structure.

5 196. An apparatus according to any one of claims 190 to 195, wherein said examining of said internodal dependency information identifies those of said regions affected by said at least one change.

10 197. An apparatus according to any one of claims 190 to 196, wherein said updating of said internodal dependency record reflects changes to said hierarchical structure.

15 198. An apparatus according to any one of claims 190 to 197, wherein said first examining means examines each said region to determine an opacity of each of said objects within said region.

 199. An apparatus according to anyone of claims 190 to 198, wherein said internodal dependency information is created for each of said regions.

20 200. An apparatus according to any one of claims 190 or 198, wherein said internodal dependency information includes:

 a first internodal dependency list identifying those regions directly affected by a change to said one region; and

25 a second internodal dependency list identifying those regions indirectly affected by a change in said one region.

 201. An apparatus according to claim 200, wherein directly affected regions are those regions having content modified as a consequence of change.

30 202. An apparatus according to any one of claims 200, wherein indirectly affected regions are those regions which may include modified region outlines and/or content generation as a result of change.

203. An apparatus according to any one of claims 190 to 202, wherein said region outline is further defined by at least one attribute of at least one said object within the corresponding region.

5 204. An apparatus according to claim 203, wherein said attribute is selected from the group consisting of colour, opacity and object outline.

205. An apparatus according to any one of claims 190 to 204, wherein said updating include functions selected from the group consisting of deleting regions, altering the boundaries or regions.

10 206. An apparatus according to any one of claims 190 to 205, wherein at least one change includes changing the attributes of nodes in said hierarchical structure.

15 207. An apparatus according to any one of claims 190 to 205, wherein new regions can be added to said hierarchical structure as a result of said at least one change to at least one of said nodes.

20 208. An apparatus according to any one of claims 190 to 207, wherein said image is at least in part a pixel-based image.

25 209. An apparatus according to any one of claims 190 to 208, wherein each of said mutually exclusive regions include a descriptor which represents an outline of said mutually exclusive region.

210. An apparatus according to any one claims 190 to 209, wherein each of said regions includes a region descriptor which represents a union of all region descriptors of said node.

30 211. An apparatus according to any one claims 190 to 210, wherein each of said regions is represented by a single proxy that provides for the reproduction of pixel data.

212. An apparatus according to claim 211, wherein a flag is stored within each said proxy to indicate whether data in that region is opaque or ordinary.

213. An apparatus according to claim 212, wherein said compositing
5 expression is optimized based on a value of said flag.

214. An apparatus according to any one of claims 190 to 212, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expressions.

10 215. An apparatus according to any one of claims 190 to 214, wherein a wholly transparent object in said region eliminates at least itself from said composition expression.

216. An apparatus for creating a series of images, said images being formed
15 by rendering at least a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, said apparatus comprising:

dividing means for dividing a component image space, for each said node, in which said graphical objects are defined into at least one region;

20 first examining means for examining each said region;

creating means for creating internodal dependency information for each of said regions;

rendering means for rendering a first image of said series utilising said hierarchical structure;

25 second examining means for examining said internodal dependency information, in response to at least one change to at least one of said nodes; and

first updating means for updating the corresponding regions for an affected node;

second updating means for updating said internodal dependency information;

and

30 rendering means for rendering a further image of said series.

217. An apparatus according to claim 216, wherein each of said objects has a predetermined outline.

218. An apparatus according to claim 217, further comprising approximating means for approximating each said predetermined outline on the outside and the inside to form an outline region.

5 219. An apparatus according to claim 218, wherein each said outline region is approximated to a grid.

220. An apparatus according to any one of claims 216 to 218, wherein said regions are mutually exclusive.

10

221. An apparatus according to any one of claims 216 to 220, wherein said rendering a further image of said series is executed by compositing those regions affected by said at least one change.

15

222. An apparatus according to any one of claims 216 to 220, wherein each member of said series of images is related to a preceding member.

223. An apparatus according to any one of claims 216 to 222, wherein each said region is related to at least one graphical object.

20

224. An apparatus according to any one of claims 216 to 223, wherein rendering of said first image is executed by compositing all regions of said hierarchical structure.

25 225. An apparatus according to any one of claims 216 to 224, wherein said examining of said internodal dependency record identifies those of said regions affected by said at least one change.

30 226. An apparatus according to any one of claims 216 to 225, wherein said updating of said internodal dependency record reflects changes to said hierarchical structure.

227. An apparatus according to any one of claims 216 to 226, wherein said first examining means includes examining each said region to determine an opacity of each of said objects within said region.

228. An apparatus according to anyone of claims 216 to 227, wherein said internodal dependency information is created for each of said regions.

5 229. An apparatus according to any one of claims 216 or 228, wherein said internodal dependency information includes:

 a first internodal dependency list identifying those regions directly affected by a change to said one region; and

 a second internodal dependency list identifying those regions indirectly affected
10 by a change in said one region.

 230. An apparatus according to claim 229, wherein directly affected regions are those regions having content modified as a consequence of change.

15 231. An apparatus according to any one of claims 229, wherein indirectly affected regions are those regions which may include modified region outlines and/or content generation as a result of change.

 232. An apparatus according to any one of claims 216 to 231, wherein said
20 region outline is further defined by at least one attribute of at least one said object within the corresponding region.

 233. An apparatus according to claim 232, wherein said attribute is selected
25 from the group consisting of colour, opacity and object outline.

 234. An apparatus according to any one of claims 216 to 233, wherein said updating include functions selected from the group consisting of deleting regions, altering the boundaries or regions.

30 235. An apparatus according to any one of claims 216 to 234, wherein at least one change includes changing the attributes of nodes in said hierarchical structure.

236. An apparatus according to any one of claims 216 to 235, wherein new regions can be added to said hierarchical structure as a result of said at least one change to at least one of said nodes.

5 237. An apparatus according to any one of claims 216 to 236, wherein said image is at least in part a pixel-based image.

238. An apparatus according to any one of claims 216 to 237, wherein each of said mutually exclusive regions include a descriptor which represents an outline of said
10 mutually exclusive region.

239. An apparatus according to any one claims 216 to 238, wherein each of said regions includes a region descriptor which represents a union of all region descriptors of said node.
15

240. An apparatus according to any one claims 216 to 238, wherein each of said regions is represented by a single proxy that provides for the reproduction of pixel data.

20 241. An apparatus according to claim 216 to 240, wherein a flag is stored within each said proxy to indicate whether data in that region is opaque or ordinary.

242. An apparatus according to claim 241, wherein said compositing expression is optimized based on a value of said flag.
25

243. An apparatus according to any one of claims 216 to 242, wherein a wholly opaque object in said region acts to eliminate one or more objects within said region from said compositing expressions.

30 244. An apparatus according to any one of claims 216 to 243, wherein a wholly transparent object in said region eliminates at least itself from said composition expression.

245. A computer program product including a computer readable medium having a plurality of software modules for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said computer program product comprising:

dividing module for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions wherein each of said regions is defined by a region outline substantially following at least one of said predetermined outlines or parts thereof;

examining module for examining each said region to determine those said objects which contribute to said region;

modifying module for modifying said compositing expression on the basis of the contribution of each of said objects within said region to form an optimized compositing expression for each said region; and

compositing module for compositing said image using each of said optimized compositing expressions.

246. A computer program product including a computer readable medium having a plurality of software modules for creating an image, said image being formed by rendering at least a plurality of graphical objects to be composited according to a compositing expression, each said object having a predetermined outline, said computer program product comprising:

dividing module for dividing a space in which said outlines are defined into a plurality of mutually exclusive regions;

examining module for examining each said region to determine those said objects which contribute to said region;

modifying module for modifying said compositing expression on the basis of the contribution of each of said objects within said region; and

compositing module for compositing said image using said modified compositing expression.

247. A computer program product including a computer readable medium having a plurality of software modules for creating an image, said image comprising a

plurality of graphical objects to be composited according to a compositing expression, said computer program product comprising:

dividing module for dividing a space in which said graphical objects are defined into a plurality of regions;

5 examining module for examining each said region to determine those said objects which contribute to said region;

modifying module for modifying said compositing expression on the basis of said examination; and

10 compositing module for compositing said image using said modified compositing expression.

248. A computer program product including a computer readable medium having a plurality of software modules for creating a series of images, each member of said series being related to a preceding member, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure representing a compositing expression, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a predetermined outline, said computer program product comprising:

15 dividing module for dividing a component image space in which said outlines are defined, for each said node, into at least one mutually exclusive region, each said region being related to at least one graphical object ;

first examining module for examining each said region, for each said node, to determine those objects that contribute to the region;

25 creating module for creating an internodal dependency information identifying those said regions that will be affected by a change in any one of said regions;

rendering module for rendering a first image of said series by compositing all regions of said hierarchical structure;

30 second examining module for examining said internodal dependency information to identify those of said regions affected by at least one change to at least one of said nodes;

first updating module for updating the corresponding identified regions for each node with affected regions and incorporating into said node those (any) new regions arising from the change;

second updating module for updating said internodal dependency information to reflect changes to said hierarchical structure; and

rendering module for rendering a further image of said series by compositing (only) those regions affected by said at least one change.

5

249. A computer program product including a computer readable medium having a plurality of software modules for creating a series of images, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of at least one of said images, each of said objects having a predetermined outline, said computer program product comprising:

10

dividing module for dividing a space in which said outlines are defined, for each said node, into at least one mutually exclusive region;

15

first examining module for examining each said region, for each said node, to determine those objects that contribute to the region;

creating module for creating an internodal dependency information based on said examination;

rendering module for rendering a first image of said series utilising said hierarchical structure; and

20

second examining module for examining said internodal dependency information in response to at least one change to at least one of said nodes and, for a node with affected regions, updating the corresponding regions, updating said internodal dependency information and, rendering a further image of said series by compositing those regions affected by said at least one change.

25

250. A computer program product including a computer readable medium having a plurality of software modules for creating a series of images, said images being formed by rendering a plurality of graphical objects to be composited according to a hierarchical structure, said hierarchical structure including a plurality of nodes each representing a component of said image, said computer program product comprising:

30

dividing module for dividing a component image space, for each said node, in which said graphical objects are defined into at least one region;

first examining module for examining each said region;

creating module for creating internodal dependency information for each of said regions;

rendering module for rendering a first image of said series utilising said hierarchical structure;

5 second examining module for examining said internodal dependency information, in response to at least one change to at least one of said nodes; and

first updating module for updating the corresponding regions for a node with affected regions;

second updating module for updating said internodal dependency information;

10 and

rendering module for rendering a further image of said series.

251. A method of processing image data for creating an image by rendering graphical objects to be composited according to a compositing expression, comprising the steps of:

15 dividing a space in which said objects are defined into a plurality of regions in accordance with outlines of the objects;

examining a part of the space by utilizing each said region; and

modifying the compositing expression based on a result of said examining step.

20

252. A method according to claim 251, wherein said examining step comprises a step for determining the existence of each said objects.

253. A method according to claim 252, wherein said examining step
25 comprises a step for determining an opacity of each said objects.

254. A method according to claim 251, wherein said examining step comprises a step for determining a change of the part between images of a plurality of images.



30

DATED this Twentieth Day of August 1999

Canon Kabushiki Kaisha

Patent Attorneys for the Applicant

SPRUSON & FERGUSON

**Fig. 1****Fig. 2**




Fig. 1




Fig. 2




Fig. 3




Fig. 4







**Fig. 5****Fig. 6****Fig. 7**

Fig. 8A




RG1




RG2

Fig. 8B




New Region 1




New Region 2

Fig. 8C




New Region 3

Fig. 8D






New Region 4




New Region 5

Fig. 8



**Fig. 9****Fig. 10**





 Primary Damage
 Secondary Damage

Fig. 11






Fig. 12

**Fig. 15**




Fig. 16




Fig. 17








Fig. 18

**Fig. 19**

**Fig. 20**

**Fig. 21**

**Fig. 22**




Fig. 23




Fig. 24

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)